

The Clavister logo is rendered in a bold, black, sans-serif font. The letter 'a' is lowercase and features a unique design with a horizontal bar that extends to the right, resembling a stylized 'v' or a specific character. The rest of the letters are standard uppercase characters. A registered trademark symbol (®) is positioned at the end of the word.

CLAVISTER®

Clavister cOS Core CLI Reference Guide

Version: 10.22.01

Clavister AB
Sjögatan 6J
SE-89160 Örnsköldsvik
SWEDEN

Phone: +46-660-299200
www.clavister.com

Published 2015-03-13
Copyright © 2015 Clavister AB

**Clavister cOS Core
CLI Reference Guide
Version: 10.22.01**

Published 2015-03-13

Copyright © 2015 Clavister AB

Copyright Notice

This publication, including all photographs, illustrations and software, is protected under international copyright laws, with all rights reserved. Neither this manual, nor any of the material contained herein, may be reproduced without the written consent of Clavister.

Disclaimer

The information in this document is subject to change without notice. Clavister makes no representations or warranties with respect to the contents hereof and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Clavister reserves the right to revise this publication and to make changes from time to time in the content hereof without any obligation to notify any person or parties of such revision or changes.

Limitations of Liability

UNDER NO CIRCUMSTANCES SHALL CLAVISTER OR ITS SUPPLIERS BE LIABLE FOR DAMAGES OF ANY CHARACTER (E.G. DAMAGES FOR LOSS OF PROFIT, SOFTWARE RESTORATION, WORK STOPPAGE, LOSS OF SAVED DATA OR ANY OTHER COMMERCIAL DAMAGES OR LOSSES) RESULTING FROM THE APPLICATION OR IMPROPER USE OF THE CLAVISTER PRODUCT OR FAILURE OF THE PRODUCT, EVEN IF CLAVISTER IS INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. FURTHERMORE, CLAVISTER WILL NOT BE LIABLE FOR THIRD-PARTY CLAIMS AGAINST CUSTOMER FOR LOSSES OR DAMAGES. CLAVISTER WILL IN NO EVENT BE LIABLE FOR ANY DAMAGES IN EXCESS OF THE AMOUNT CLAVISTER RECEIVED FROM THE END-USER FOR THE PRODUCT.

Table of Contents

Preface	9
1. Introduction	11
1.1. Running a command	11
1.2. Help	12
1.2.1. Help for commands	12
1.2.2. Help for object types	12
1.3. Function keys	13
1.4. Command line history	14
1.5. Tab completion	15
1.5.1. Inline help	15
1.5.2. Autocompleting Current and Default value	16
1.5.3. Configuration object type categories	16
1.6. User roles	18
2. Command Reference	20
2.1. Configuration	20
2.1.1. activate	20
2.1.2. add	20
2.1.3. cancel	22
2.1.4. cc	22
2.1.5. commit	23
2.1.6. delete	23
2.1.7. psongen	24
2.1.8. reject	25
2.1.9. reset	26
2.1.10. set	27
2.1.11. show	28
2.1.12. undelete	29
2.2. Runtime	31
2.2.1. about	31
2.2.2. alarm	31
2.2.3. appcontrol	31
2.2.4. arp	32
2.2.5. arpsnoop	33
2.2.6. ats	34
2.2.7. authagent	34
2.2.8. authagentsnoop	35
2.2.9. blacklist	35
2.2.10. buffers	37
2.2.11. cam	37
2.2.12. certcache	38
2.2.13. cfglog	38
2.2.14. connections	39
2.2.15. cpuid	40
2.2.16. crashdump	40
2.2.17. cryptostat	40
2.2.18. dconsole	41
2.2.19. dhcp	41
2.2.20. dhcprelay	42
2.2.21. dhcpserver	43
2.2.22. dhcpv6server	44
2.2.23. dns	44
2.2.24. dnsbl	45
2.2.25. dynroute	45
2.2.26. frags	46
2.2.27. ha	47
2.2.28. hostmon	47

2.2.29. httpalg	47
2.2.30. httpposter	48
2.2.31. hwm	49
2.2.32. idppipes	49
2.2.33. ifstat	50
2.2.34. igmp	50
2.2.35. ihs	51
2.2.36. ikesnoop	51
2.2.37. ippool	52
2.2.38. ipsecdefines	53
2.2.39. ipsecglobalstats	53
2.2.40. ipsechastat	53
2.2.41. ipsecstats	54
2.2.42. ipsectunnels	54
2.2.43. killsa	55
2.2.44. languagefiles	56
2.2.45. ldap	56
2.2.46. license	57
2.2.47. linkmon	58
2.2.48. logout	58
2.2.49. memory	58
2.2.50. natpool	59
2.2.51. nd	59
2.2.52. ndsnoop	60
2.2.53. netcon	61
2.2.54. netobjects	61
2.2.55. ospf	61
2.2.56. pcapdump	63
2.2.57. pciscan	65
2.2.58. pipes	66
2.2.59. pptpalg	67
2.2.60. reconfigure	67
2.2.61. rekeysa	68
2.2.62. route	68
2.2.63. routemon	68
2.2.64. routes	69
2.2.65. rtmonitor	70
2.2.66. rules	70
2.2.67. selftest	71
2.2.68. services	73
2.2.69. sessionmanager	74
2.2.70. settings	75
2.2.71. shutdown	75
2.2.72. sipalg	76
2.2.73. sshserver	78
2.2.74. sslvpn	79
2.2.75. stats	79
2.2.76. sysmsgs	80
2.2.77. techsupport	80
2.2.78. time	80
2.2.79. uarules	81
2.2.80. updatecenter	81
2.2.81. userauth	82
2.2.82. vlan	83
2.2.83. vpnstats	84
2.3. Utility	85
2.3.1. ping	85
2.4. Misc	86
2.4.1. echo	86
2.4.2. help	86
2.4.3. history	87

2.4.4. logsnoop	87
2.4.5. ls	89
2.4.6. script	90
3. Configuration Reference	94
3.1. Access	98
3.2. Address	100
3.2.1. AddressFolder	100
3.2.2. EthernetAddress	103
3.2.3. EthernetAddressGroup	103
3.2.4. IP4Address	103
3.2.5. IP4Group	103
3.2.6. IP4HAddress	103
3.2.7. IP6Address	103
3.2.8. IP6Group	103
3.3. AdvancedScheduleProfile	104
3.3.1. AdvancedScheduleOccurrence	104
3.4. ALG	105
3.4.1. ALG_FTP	105
3.4.2. ALG_H323	106
3.4.3. ALG_HTTP	106
3.4.4. ALG_POP3	108
3.4.5. ALG_PPTP	109
3.4.6. ALG_SIP	109
3.4.7. ALG_SMTP	110
3.4.8. ALG_TFTP	112
3.4.9. ALG_TLS	112
3.5. AntiVirusPolicy	114
3.6. AppControlSettings	115
3.7. ApplicationRuleSet	116
3.7.1. ApplicationRule	116
3.8. ARPND	118
3.9. ARPNDSettings	119
3.10. AuthAgent	122
3.11. AuthenticationSettings	123
3.12. BlacklistWhiteHost	124
3.13. BNE2EthernetPCIDriver	125
3.14. BroadcomEthernetPCIDriver	126
3.15. Certificate	127
3.16. COMPortDevice	128
3.17. ConfigModePool	129
3.18. ConnTimeoutSettings	130
3.19. DateTime	131
3.20. DefaultInterface	132
3.21. Device	133
3.22. DHCPRelay	134
3.23. DHCPRelaySettings	136
3.24. DHCPServer	137
3.24.1. DHCPServerPoolStaticHost	138
3.24.2. DHCPServerCustomOption	138
3.25. DHCPServerSettings	140
3.26. DHCPv6Server	141
3.26.1. DHCPv6ServerPoolStaticHost	142
3.27. DHCPv6ServerSettings	143
3.28. DiagnosticsSettings	144
3.29. DNS	145
3.30. DynamicRoutingRule	146
3.30.1. DynamicRoutingRuleExportOSPF	147
3.30.2. DynamicRoutingRuleAddRoute	147
3.31. DynDnsClientCjbNet	149
3.32. DynDnsClientDyndnsOrg	150
3.33. DynDnsClientDyngCx	151

3.34. DynDnsClientPeanutHull	152
3.35. E1000EthernetPCIDriver	153
3.36. E100EthernetPCIDriver	154
3.37. Ethernet	155
3.38. EthernetDevice	157
3.39. EthernetSettings	158
3.40. EventReceiverSNMP2c	160
3.40.1. LogReceiverMessageException	160
3.41. FileControlPolicy	161
3.42. FragSettings	162
3.43. GRE Tunnel	164
3.44. HighAvailability	165
3.45. HTTPALGBanners	166
3.46. HTTPAuthBanners	167
3.47. HTTPPoster	168
3.48. HWM	169
3.49. HWMSettings	170
3.50. ICMPSettings	171
3.51. IDList	172
3.51.1. ID	172
3.52. IDPRule	173
3.52.1. IDPRuleAction	173
3.53. IGMPRule	175
3.54. IGMPSetting	177
3.55. IKEAlgorithms	178
3.56. InterfaceGroup	180
3.57. IP6in4Tunnel	181
3.58. IPPolicy	182
3.59. IPPool	185
3.60. IPRule	186
3.61. IPRuleFolder	189
3.61.1. IPPolicy	189
3.61.2. IPRule	189
3.62. IPRuleSet	190
3.62.1. IPPolicy	190
3.62.2. IPRule	190
3.62.3. IPRuleFolder	190
3.63. IPsecAlgorithms	191
3.64. IPsecTunnel	193
3.65. IPsecTunnelSettings	196
3.66. IPSettings	198
3.67. ixgbeEthernetPCIDriver	201
3.68. IXP4NPEEthernetDriver	202
3.69. L2TPClient	203
3.70. L2TPServer	205
3.71. L2TPServerSettings	207
3.72. L2TPv3Client	208
3.73. L2TPv3Server	209
3.74. LDAPDatabase	210
3.75. LDAPServer	211
3.76. LengthLimSettings	212
3.77. LinkAggregation	213
3.78. LinkMonitor	215
3.79. LocalReassSettings	216
3.80. LocalUserDatabase	217
3.80.1. User	217
3.81. LogReceiverFWLog	218
3.81.1. LogReceiverMessageException	218
3.82. LogReceiverMemory	219
3.82.1. LogReceiverMessageException	219
3.83. LogReceiverSyslog	220

3.83.1. LogReceiverMessageException	220
3.84. LogSettings	221
3.85. LoopbackInterface	222
3.86. MarvellEthernetPCIDriver	223
3.87. MiscSettings	224
3.88. MulticastSettings	226
3.89. NATPool	227
3.90. OSPFProcess	228
3.90.1. OSPFArea	229
3.91. Pipe	233
3.92. PipeRule	236
3.93. PPPoETunnel	237
3.94. PPPSettings	239
3.95. PSK	240
3.96. R8139EthernetPCIDriver	241
3.97. R8169EthernetPCIDriver	242
3.98. RadiusAccounting	243
3.99. RadiusRelay	244
3.100. RadiusServer	246
3.101. RealTimeMonitorAlert	247
3.102. RemoteIDList	248
3.103. RemoteMgmtHTTP	249
3.104. RemoteMgmtNetcon	250
3.105. RemoteMgmtSettings	251
3.106. RemoteMgmtSNMP	253
3.107. RemoteMgmtSSH	254
3.108. RouteBalancingInstance	256
3.109. RouteBalancingSpilloverSettings	257
3.110. RouterAdvertisement	258
3.110.1. RA_PrefixInformation	259
3.111. RoutingRule	260
3.112. RoutingSettings	261
3.113. RoutingTable	263
3.113.1. Route	263
3.113.2. Route6	265
3.113.3. SwitchRoute	266
3.114. ScheduleProfile	267
3.115. ServiceGroup	268
3.116. ServiceCMP	269
3.117. ServiceCMPv6	271
3.118. ServicePPProto	273
3.119. ServiceTCPUDP	274
3.120. SSHClientKey	275
3.121. SSLSettings	276
3.122. SSLVPNInterface	277
3.123. SSLVPNInterfaceSettings	278
3.124. ST201EthernetPCIDriver	279
3.125. StateSettings	280
3.126. TCPSettings	281
3.127. ThresholdRule	283
3.127.1. ThresholdAction	283
3.128. TulipEthernetPCIDriver	285
3.129. UpdateCenter	286
3.130. URLFilterPolicy	287
3.130.1. URLFilterPolicy_URL	287
3.131. UserAuthRule	288
3.132. VLAN	291
3.133. VLANSettings	293
3.134. WebContentFilteringPolicy	294
3.135. X3C905EthernetPCIDriver	295
Alphabetical Index	297

List of Examples

1. Command option notation	9
1.1. Help for commands	12
1.2. Help for object types	12
1.3. Command line history	14
1.4. Tab completion	15
1.5. Inline help	15
1.6. Edit an existing property value	16
1.7. Using categories with tab completion	16
2.1. Create a new object	21
2.2. Change context	22
2.3. Delete an object	24
2.4. Reject changes	25
2.5. Set property values	27
2.6. Show objects	28
2.7. Undelete an object	30
2.8. Block hosts	36
2.9. frags	46
2.10. List network objects which have names containing "net".	61
2.11. Show all monitored objects in the alg/http category	70
2.12. Show a range of rules	70
2.13. Interface ping test between all interfaces	72
2.14. Interface ping test between interfaces 'if1' and 'if2'	72
2.15. Start 30 min burn-in, testing RAM, storage media and crypto accelerator	72
2.16. List all services which names begin with "http"	74
2.17. Show a range of rules	81
2.18. Hello World	86
2.19. Show log message having 'warning' followed by 'udp' somewhere in the message	87
2.20. Rate limit log flow to five logs per second	88
2.21. Show logs from the memlog buffer	88
2.22. Show logs having a source IP value	88
2.23. Show logs having a severity of warning or higher	88
2.24. Transfer script files to and from the device	89
2.25. Upload license data	90
2.26. Upload certificate data	90
2.27. Upload ssh public key data	90
2.28. Execute script	90

Preface

Audience

The target audience for this reference guide is:

- Administrators that are responsible for configuring and managing the Clavister Security Gateway.
- Administrators that are responsible for troubleshooting the Clavister Security Gateway.

This guide assumes that the reader is familiar with the Clavister Security Gateway, and has the necessary basic knowledge in network security.

Notation

The following notation is used throughout this reference guide when specifying the options of a command:

Angle brackets <code><name></code> or -option=<description>	Used for specifying the <i>name</i> of an option or a description of a value.
Square brackets <code>[option]</code> or -option[=value]	Used for specifying that an option or a value for an option is <i>optional</i> and can be omitted.
Curly brackets <code>{value1 value2 value3}</code>	Used for specifying the <i>available values</i> for an option.
Ellipsis ...	Used for specifying that <i>more than one</i> value can be specified for the option.

Example 1. Command option notation

One of the usages for the **help** command looks like this:

```
help -category={COMMANDS | TYPES} [<Topic>]
```

This means that help has an option called `category` which has two possible values which are `COMMANDS` and `TYPES`. There is also an optional option called `Topic` which in this case is a search string used to specify what help topic to display. Since the topic is optional, it is possible to exclude it when running the command.

Both of the following examples are valid for the usage described above:

```
Device:/> help -category=COMMANDS
Device:/> help -category=COMMANDS activate
```

The usage for the **routes** command is:

```
routes [-all] [-switched] [-flushl3cache[=<percent>]] [-num=<n>]
        [-nonhost] [-tables] [-lookup=<ip address>] [-verbose]
        [-setmtu=<mtu>] [-cacheinfo] [<table name>]...
```

None of the options of this command are mandatory. The `flushl3cache` option also has an

optional value. This is because that option has a default value, *100*, which will be used if no value is specified.

The following two examples will yield the same result:

```
Device:/> routes -flushl3cache=100
Device:/> routes -flushl3cache
```

Because the `table name` option is followed by ellipses it is possible to specify more than one routing table. Since `table name` is optional as well, the user can specify zero or more policy-based routing tables.

```
Device:/> routes Virroute Virroute2
```

Chapter 1: Introduction

- Running a command, page 11
- Help, page 12
- Function keys, page 13
- Command line history, page 14
- Tab completion, page 15
- User roles, page 18

This guide is a reference for all commands and configuration object types that are available in the command line interface for Clavister cOS Core.

1.1. Running a command

The commands described in this guide can be run by typing the command name and then pressing the return key. Many commands require options to be set to run. If a required option is missing a brief syntax help will be displayed.

1.2. Help

1.2.1. Help for commands

There are two ways of getting help about a command. A brief help is displayed if the command name is typed followed by `-?` or `-h`. This applies to all commands and is therefore not listed in the option list for each command in this guide. Using the **help** command gives a more detailed help corresponding to the information found in this guide. In most cases it is possible to simply type **help** followed by the command name to get the full help. See Section 2.4.2, “help” for a more detailed description. To list the available commands, just type **help** and press return.

Example 1.1. Help for commands

Brief help for the **activate** command:

```
Device:/> activate -?  
Device:/> activate -h
```

Full help for **activate**:

```
Device:/> help activate
```

Help for the **arp** command. Arp is also the name of a configuration object type, so it is necessary to specify that the help text for the command should be displayed:

```
Device:/> help -category=COMMANDS arp
```

List all available commands:

```
Device:/> help
```

1.2.2. Help for object types

To get help about configuration object types, use the **help** command. It is also possible to get information about each property in an object type, such as data type, default value, etc. by entering the `?` character when entering the value of a property and pressing tab. More on this in Section 1.5.1, “Inline help”.

Example 1.2. Help for object types

Full help for IP4Address:

```
Device:/> help IP4Address
```

Help for the ARP configuration object type, which collides with the **arp** command:

```
Device:/> help -category=TYPES ARP
```

1.3. Function keys

In addition to the return key there are a number of function keys that are used in the CLI.

Backspace	Delete the character to the left of the cursor.
Tab	Complete current word.
Ctrl-A or Home	Move the cursor to the beginning of the line.
Ctrl-B or Left Arrow	Move the cursor one character to the left.
Ctrl-C	Clear line or cancel page view if more than one page of information is shown.
Ctrl-D or Delete	Delete the character to the right of the cursor.
Ctrl-E or End	Move the cursor to the end of the line.
Ctrl-F or Right Arrow	Move the cursor one character to the right.
Ctrl-K	Delete from the cursor to the end of the line.
Ctrl-N or Down Arrow	Show the next entry in the command history.
Ctrl-P or Up Arrow	Show the previous entry in the command history.
Ctrl-T	Transpose the current and the previous character.
Ctrl-U	Delete from the cursor to the beginning of line.
Ctrl-W	Delete word backwards.

1.4. Command line history

Every time a command is run, the command line is added to a history list. The up and down arrow keys are used to access previous command lines (up arrow for older command lines and down arrow to move back to a newer command line). See also Section 2.4.3, "history".

Example 1.3. Command line history

Using the command line history via the arrow keys:

```
Device:/> show Address  
Device:/> (up arrow)  
Device:/> show Address (the previous commandline is displayed)
```

1.5. Tab completion

By using the tab function key in the CLI the names of commands, options, objects and object properties can be automatically completed. If the text entered before pressing tab only matches one possible item, e.g. "activate" is the only match for "acti", and a command is expected, the name will be autocompleted. Should there be more than one match the part common to all matches will be completed. At this point the user can either enter more characters or press tab again, which will display a list of the possible completions. This can also be done without entering any characters, but the resulting list might be long if there are many possible completions, e.g. all commands.

Example 1.4. Tab completion

An example of tab completion when using the **add** command:

```
Device:/> add Add (tab)
Device:/> add Address ("ress" was autocompleted)
Device:/> add Address i (tab)
Device:/> add Address IP4 ("IP4" was autocompleted)
Device:/> add Address IP4
      (tab, or double tab if IP4 were entered manually)
A list of all types starting with IP4 is listed.
Device:/> add Address IP4a (tab)
Device:/> add Address IP4Address ("Address" was autocompleted)
Device:/> add Address IP4Address example_ip a (tab)
Device:/> add Address IP4Address example_ip Address=
      ("Address=" was autocompleted)
Device:/> add Address IP4Address example_ip Address=1.2.3.4
```

Tab completion of references:

```
Device:/> set Address IP4Group examplegroup Members= (tab, tab)
A list of valid objects is displayed.
Device:/> set Address IP4Group examplegroup Members=e (tab)
Device:/> set Address IP4Group examplegroup Members=example_ip
      ("example_ip" was autocompleted)
```

1.5.1. Inline help

It is possible to get help about available properties of configuration objects while a command line is being typed by using the ? character. Write ? instead of a property name and press tab and a help text for the available properties is shown. If ? is typed in stead of a property value and tab is pressed a help text for that property which contains more information such as data type, default value, etc. is displayed.

Example 1.5. Inline help

Get inline help for all properties of an IP4Address:

```
Device:/> set IP4Address example_ip ? (tab)
A help text describing all available properties is displayed.
```

Getting inline help for the Address property:

```
Device:/> set IP4Address example_ip Address=? (tab)
```

A more detailed help text about Address is displayed.

1.5.2. Autocompleting Current and Default value

Another special character that can be used together with tab completion is the period "." character. If "." is entered instead of a property value and tab is pressed it will be replaced by the current value of that property. This is useful when editing an existing list of items or a long text value.

The "<" character before a tab can be used to automatically fill in the default value for a parameter if no value has yet been set. If the "." character is used, all possible values will be shown and these can then be edited with the back arrow and backspace keys.

Example 1.6. Edit an existing property value

Edit the current value:

```
Device:/> add IP4Address example_ip Address=1.2.3.4
Device:/> set IP4Address example_ip Address=. (tab)
Device:/> set IP4Address example_ip Address=1.2.3.4
      (the value was inserted)
The value can now be edited by using the arrow keys or backspace.
```

```
Device:/> set IP4Group examplegroup Members=ip1,ip2,ip3,ip5
Device:/> set IP4Group examplegroup Members=. (tab)
Device:/> set IP4Group examplegroup Members=ip1,ip2,ip3,ip5
      (the value was inserted)
It is now possible to add or remove a member to the list without
having to enter all the other members again.
```

Edit the default value:

```
Device:/> add LogReceiverSyslog example Address=example_ip
      LogSeverity=. (tab)
Device:/> add LogReceiverSyslog example Address=example_ip
      LogSeverity=Emergency,Alert,Critical,Error,Warning,Notice,Info
```

Now it is easy to remove a log severity.

1.5.3. Configuration object type categories

Some object types are grouped together in a category in the CLI. This only matters when using tab completion as they are used to limit the number of possible completions when tab completing object types. The category can always be omitted when running commands if the type name is entered manually.

Example 1.7. Using categories with tab completion

Accessing an IP4Address object with the use of categories:

```
Device:/> show ad (tab)
Device:/> show Adress (the category is autocompleted)
Device:/> show Address ip4a (tab)
Device:/> show Address IP4Address (the type is autocompleted)
Device:/> show Address IP4Address example_ip
```


Accessing an IPAddress object without the use of categories:

```
Device:/> show IPAddress example_ip
```

1.6. User roles

Some commands and options cannot be used unless the logged-in user has administrator privileges. This is indicated in this guide by a note following the command or **Admin only** written next to an option.

Chapter 2: Command Reference

- Configuration, page 20
- Runtime, page 31
- Utility, page 85
- Misc, page 86

2.1. Configuration

2.1.1. activate

Activate changes.

Description

Activate the latest changes.

This will issue a reconfiguration, using the new configuration. If the reconfiguration is successful a **commit** command must be issued within the configured timeout interval in order to save the changes to media. If not, the system will revert to using the previous version of the configuration.

Usage

```
activate
```



Note

Requires Administrator privileges.

2.1.2. add

Create a new object.

Description

Create a new object and add it to the configuration.

Specify the type of object you want to create and the identifier, if the type has one, unless the object is identified by an index. Set the properties of the object by writing the propertyname equals (=) and then the value. An optional category can be specified for some object types when using tab completion.

If a mandatory property isn't specified a list of errors will be shown after the object is created. If an invalid property or value type is specified or if the identifier is missing the command will fail and not create an object.

Adjustments can be made after the object is created by using the **set** command.

Example 2.1. Create a new object

```
Add objects with an identifier property (not index):
gw-world:/> add Address IP4Address example_ip Address=1.2.3.4
Comments="This is an example"
gw-world:/> add IP4Address example_ip2 Address=2.3.4.5
Add an object with an index:
gw-world:/main> add Route Interface=lan
Add an object without identifier:
gw-world:/> add DynDnsClientDynDnsOrg DNSName=example Username=example
```

Usage

```
add [<Category>] <Type> [<Identifier>] [-force] [-silent]
[<key-value pair>]...
```

Options

-force	Add object, even if it has errors.
-silent	Do not show any errors.
<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<key-value pair>	One or more property-value pairs, i.e. <property name>=<value> or <property name>="<value>".
<Type>	Type of configuration object to perform operation on.



Note

Requires Administrator privileges.

2.1.3. cancel

Cancel ongoing commit.

Description

Cancel commit operation immediately, without waiting for the timeout.

Usage

```
cancel
```



Note

Requires Administrator privileges.

2.1.4. cc

Change the current context.

Description

Change the current configuration context.

A context is a group of objects that are dependent on and grouped by a parent object. Many objects lie in the "root" context and do not have a specific parent. Other objects, e.g. User objects lie in a sub-context (or child context) of the root - in this case in a LocalUserDatabase. In order to add or modify users you have to be in the correct context, e.g. a LocalUserDatabase called "exampledb". Only objects in the current context can be accessed.

Example 2.2. Change context

```
Change to a sub/child context:
gw-world:/> cc LocalUserDatabase exampledb
gw-world:/exampledb>
Go back to the parent context:
gw-world:/ospf1/areal> cc ..
gw-world:/ospf1> cc ..
gw-world:/>
Go back to the root context:
gw-world:/ospf1/areal> cc
gw-world:/>
or
gw-world:/ospf1/areal> cc /
gw-world:/>
```

Usage

```
cc [<Category>] <Type> <Identifier>
```

Change the current context.

```
cc -print
```

Print the current context.

```
cc
```

Change to root context (same as "cc /").

Options

-print	Print the current context.
<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Type>	Type of configuration object to perform operation on.

2.1.5. commit

Save new configuration to media.

Description

Save the new configuration to media. This command can only be issued after a successful activate command.

Usage

```
commit
```



Note

Requires Administrator privileges.

2.1.6. delete

Delete specified objects.

Description

Delete the specified object, removing it from the configuration.

Add the force flag to delete the object even if it is referenced by other objects or if it is a context that has child objects that aren't deleted. This may cause objects referring to the specified object or one of its children to get errors that must be corrected before the configuration can be

activated.

See also: **undelete**

Example 2.3. Delete an object

```
Delete an unreferenced object:
gw-world:/> delete Address IP4Address example_ip
Delete a referenced object:
(will cause error in exemplerule)
gw-world:/> set IPRule exemplerule SourceNetwork=examplenet
gw-world:/> delete Address IP4Address examplenet -force
```

Usage

```
delete [<Category>] <Type> [<Identifier>] [-force]
```

Options

-force	Force object to be deleted even if it's used by other objects or has children.
<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Type>	Type of configuration object to perform operation on.



Note

Requires Administrator privileges.

2.1.7. pskgen

Generate random pre-shared key.

Description

Generate a pre-shared key of specified size, containing randomized key data. If a key with the specified name exists, the existing key is modified. Otherwise a new key object is created.

Usage

```
pskgen <Name> [-comments=<String>] [-size={64 | 128 | 256 | 512 |
1024 | 2048 | 4096}]
```


Options

-comments=<String>	Comments for this key.
-size={64 128 256 512 1024 2048 4096}	Number of bits of data in the generated key. (Default: 64)
<Name>	Name of key.

**Note**

Requires Administrator privileges.

2.1.8. reject

Reject changes.

Description

Reject the changes made to the specified object by reverting to the values of the last committed configuration.

All changes made to the object will be lost. If the object is added after the last commit, it will be removed.

To reject the changes in more than one object, use either the `-recursive` flag to delete a context and all its children recursively or the `-all` flag to reject the changes in *all* objects in the configuration.

See also: **activate, commit**

Example 2.4. Reject changes

```
Reject changes in individual objects:
gw-world:/> set Address IP4Address example_ip
Comments="This comment will be rejected"
gw-world:/> reject Address IP4Address example_ip
gw-world:/> add Address IP4Address example_ip2 Address=1.2.3.4
Comments="This whole object will be removed"
gw-world:/> reject Address IP4Address example_ip2
Reject changes recursively:
(will reject changes in the user database and all users)
gw-world:/exampleddb> set User user1 Comments="Something"
gw-world:/exampleddb> set User user2 Comments="that will be"
gw-world:/exampleddb> set User user3 Comments="rejected"
gw-world:/exampleddb> cc ..
gw-world:/> reject LocalUserDatabase exampleddb -recursive
Reject all changes:
gw-world:/anycontext> reject -all
All changes since the last commit will be rejected:
(example_ip will be removed since it is newly added)
gw-world:/> add IP4Address example_ip Address=1.2.3.4
gw-world:/> delete IP4Address example_ip
gw-world:/> reject IP4Address example_ip
```

Usage

```
reject [<Category>] <Type> [<Identifier>] [-recursive]
```

Reject changes made to the specified object.

```
reject -all
```

Reject all changes in the configuration.

Options

-all	Reject all changes in the configuration.
-recursive	Recursively reject changes.
<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Type>	Type of configuration object to perform operation on.



Note

Requires Administrator privileges.

2.1.9. reset

Reset unit configuration and/or binaries.

Description

Reset configuration to the base configuration as generated by the current core or reset binaries to factory defaults.

Usage

```
reset -configuration
```

Reset the configuration to factory defaults.

```
reset -unit
```

Reset the unit to factory defaults.

Options

-configuration	Reset configuration to current core default.
-----------------------	--

-unit

Reset unit to factory defaults.

**Note***Requires Administrator privileges.*

2.1.10. set

Set property values.

Description

Set property values of configuration objects.

Specify the type of object you want to modify and the identifier, if the type has one. Set the properties of the object by writing the propertyname equals (=) and then the value. An optional category can be specified for some object types when using tab completion.

If a mandatory property hasn't been specified or if a property has an error a list of errors will be shown after the specified properties have been set. If an invalid property or value type is specified the command will fail and not modify the object.

See also: **add**

Example 2.5. Set property values

```
Set properties for objects that have an identifier property:
gw-world:/> set Address IP4Address example_ip Address=1.2.3.4
Comments="This is an example"
gw-world:/> set IP4Address example_ip2 Address=2.3.4.5
Comments=comment_without_whitespace
gw-world:/main> set Route 1 Comment="A route"
gw-world:/> set IPRule 12 Index=1
Set properties for an object without identifier:
gw-world:/> set DynDnsClientDynDnsOrg Username=example
```

Usage

```
set [<Category>] <Type> [<Identifier>] [-disable] [-enable]
[-force] [<key-value pair>]...
```

Options

-disable

Disable object. This option is not available if the object is already disabled.

-enable

Enable object. This option is not available if the object is already enabled.

-force

Set values, even if they contain errors.

<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<key-value pair>	One or more property-value pairs, i.e. <property name>=<value> or <property name>="<value>".
<Type>	Type of configuration object to perform operation on.

**Note**

Requires Administrator privileges.

2.1.11. show

Show objects.

Description

Show objects.

Show the properties of a specified object. There are a number of flags that can be specified to show otherwise hidden properties. To show a list of object types and categories available in the current context, just type **show**. Show a table of all objects of a type by specifying a type or a category. Use the `-errors` or `-changes` flags to show what objects have been changed or have errors in the configuration.

When showing a table of all objects of a certain type, the status of each object since the last time the configuration was committed is indicated by a flag. The flags used are:

- The object is deleted.
- o The object is disabled.
- ! The object has errors.
- + The object is newly created.
- * The object is modified.

Additional flags:

- D** The object has dynamic properties which are updated by the system.

When listing categories and object types, categories are indicated by [] and types where objects may be contexts by /.

Example 2.6. Show objects

```
Show the properties of an individual object:
```

```

gw-world:/> show Address IP4Address example_ip
gw-world:/main> show Route 1
gw-world:/> show Client DynDnsClientDynDnsOrg
Show a table of all objects of a type and a selection of their
properties as well as their status:
gw-world:/> show Address IP4Address
gw-world:/> show IP4Address
Show a table of all objects for each type in a category:
gw-world:/> show Address
Show objects with changes and errors:
gw-world:/> show -changes
gw-world:/> show -errors
Show what objects use (refer to) a certain object:
gw-world:/> show Address IP4Address example_ip -references

```

Usage

```
show
```

Show the types and categories available in the current context.

```
show [<Category>] [<Type> [<Identifier>]] [-disabled] [-references]
```

Show an object or list a type or category.

```
show -errors [-verbose]
```

Show all errors.

```
show -changes
```

Show all changes.

Options

-changes	Show all changes in the current configuration.
-disabled	Show disabled properties.
-errors	Show all errors in the current configuration.
-references	Show all references to this object from other objects.
-verbose	Show error details.
<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Type>	Type of configuration object to perform operation on.

2.1.12. undelete

Restore previously deleted objects.

Description

Restore a previously deleted object.

This is possible as long as the **activate** command has not been called.

See also: **delete**

Example 2.7. Undelete an object

```
Undelete an unreferenced object:
gw-world:/> delete Address IP4Address example_ip
gw-world:/> undelete Address IP4Address example_ip
Undelete a referenced object:
(will remove the error in exemplerule)
gw-world:/> set IPRule exemplerule SourceNetwork=examplenet
gw-world:/> delete Address IP4Address examplenet -force
gw-world:/> undelete Address IP4Address examplenet
```

Usage

```
undelete [<Category>] <Type> [<Identifier>]
```

Options

<Category>	Category that groups object types.
<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Type>	Type of configuration object to perform operation on.



Note

Requires Administrator privileges.

2.2. Runtime

2.2.1. about

Show copyright/build information.

Description

Show copyright and build information.

Usage

```
about
```

2.2.2. alarm

Show alarm information.

Description

Show list of currently active alarms.

Usage

```
alarm [-history] [-active]
```

Options

- | | |
|-----------------|-----------------------------------|
| -active | Show the currently active alarms. |
| -history | Show the 20 latest alarms. |
-

2.2.3. appcontrol

Show application control status.

Description

Browse the applications defined in the Application Control functionality. Saved browsing results as filters that can be later used to define IPPolicies.

Usage

```
appcontrol
```

Show general information about application control system.

```
appcontrol -show_lists
```

List information about specified application.

```
appcontrol -delete_lists={ALL | <Integer>}
```

List information about specified application.

```
appcontrol <Name>
```

List information about specified application.

```
appcontrol -application=<String> [-save_list]
```

Define a filter selecting individual applications.

```
appcontrol -filter [-name=<String>] [-family=<String>]
               [-risk={VERY_LOW | LOW | MEDIUM | HIGH | VERY_HIGH}]
               [-tag=<String>] [-save_list]
```

Define a filter selecting families, tags, risks and a matching expression for the applications names.

Options

-application=<String>	Exact application name.
-delete_lists={ALL <Integer>}	Free saved Strings.
-family=<String>	Application family.
-filter	Shows applications matching certain criteria.
-name=<String>	Application name (wildcards allowed).
-risk={VERY_LOW LOW MEDIUM HIGH VERY_HIGH}	Application risk level.
-save_list	Saved filter result.
-show_lists	List saved strings.
-tag=<String>	Application tag.
<Name>	Application name.

2.2.4. arp

Show ARP entries for given interface.

Description

List the ARP cache entries of specified interfaces.

If no interface is given the ARP cache entries of all interfaces will be presented.

The presented list can be filtered using the *ip* and *hw* options.

Usage

```
arp
```

Show all ARP entries.

```
arp -show [<Interface>] [-ip=<pattern>] [-hw=<pattern>] [-num=<n>]
```

Show ARP entries.

```
arp -hashinfo [<Interface>]
```

Show information on hash table health.

```
arp -flush [<Interface>]
```

Flush ARP cache of specified interface.

```
arp -notify=<ip> [<Interface>] [-hwsender=<Ethernet Address>]
```

Send gratuitous ARP for IP.

Options

-flush	Flush ARP cache of all specified interfaces.
-hashinfo	Show information on hash table health.
-hw=<pattern>	Show only hardware addresses matching pattern.
-hwsender=<Ethernet Address>	Sender ethernet address.
-ip=<pattern>	Show only IP addresses matching pattern.
-notify=<ip>	Send gratuitous ARP for <ip>.
-num=<n>	Show only the first <n> entries per interface. (Default: 20)
-show	Show ARP entries for given interface(s).
<Interface>	Interface name.

2.2.5. arpsnoop

Toggle snooping and displaying of ARP requests.

Description

Toggle snooping and displaying of ARP queries and responses on-screen.

The snooped messages are displayed before the access section validates the sender IP addresses in the ARP data.

Usage

```
arpsnoop
```

Show snooped interfaces.

```
arpsnoop {ALL | NONE | <interface>} [-verbose]
```

Snoop specified interface.

Options

-verbose Verbose.

{ALL | NONE | <interface>} Interface name.

2.2.6. ats

Show active ARP Transaction States.

Description

Show active ARP Transaction States.

Usage

```
ats [-num=<n>]
```

Options

-num=<n> Limit list to <n> entries. (Default: 20)

2.2.7. authagent

Shows the state of the Authentication Agents.

Description

Shows the state of the Authentication Agents.

Usage

```
authagent -version
```

Shows the state of the configured Authentication Agents including the protocol version.

```
authagent
```

Shows the state of the configured Authentication Agents.

```
authagent {ALL | <AuthAgent>}
```

Shows the state of the configured Authentication Agents.

```
authagent -reconnect {ALL | <AuthAgent>}
```

Closes the connection with the Agent and attempt to reconnect.

Options

-reconnect	Closes the connection with the Agent and attempt to reconnect. (Admin only)
-version	Show protocol version.
{ALL <AuthAgent>}	Authentication Agent name.

2.2.8. authagentsnoop

Toggle snooping and displaying of Authentication Agents traffic.

Description

Toggle snooping and displaying of Authentication Agents queries and responses on-screen.

Usage

```
authagentsnoop
```

Show snooped Authentication Agents.

```
authagentsnoop {ALL | NONE | <AuthAgent>} [-verbose]
```

Snoop specified Authentication Agent.

Options

-verbose	Verbose.
{ALL NONE <AuthAgent>}	Authentication Agent name.



Note

Requires Administrator privileges.

2.2.9. blacklist

Blacklist.

Description

Block and unblock hosts on the black and white list.

Note: Static blacklist hosts cannot be unblocked.

If *-force* is not specified, only the exact host with the service, protocol/port and destiny specified is unblocked.

Example 2.8. Block hosts

```
blacklist -show -black -listtime -info
blacklist -block 100.100.100.0/24 -serv=FTP -dest=50.50.50.1 -time=6000
```

Usage

```
blacklist -show [-num={ALL | <Integer>}] [-creationtime] [-dynamic]
[-listtime] [-info] [-black] [-white] [-all]
```

Show information about the blacklisted hosts.

```
blacklist -block <host> [-serv=<service>] [-prot={TCP | UDP | ICMP
| OTHER | TCPUDP | ALL}] [-port=<port number>]
[-dest=<ip address>] [-time=<seconds>]
```

Block specified netobject.

```
blacklist -unblock <host> [-serv=<service>] [-prot={TCP | UDP |
ICMP | OTHER | TCPUDP | ALL}] [-port=<port number>]
[-dest=<ip address>] [-time=<seconds>] [-force]
```

Unblock specified netobject.

Options

-all	Show all the information.
-black	Show blacklist hosts only.
-block	Block specified netobject. (Admin only)
-creationtime	Show creation time.
-dest=<ip address>	Destination address to block/unblock (ExceptEstablished flag is set on).
-dynamic	Show dynamic hosts only.
-force	Unblock all services for the host that matches to options.
-info	Show detailed information.
-listtime	Show time in list (for dynamic hosts).

-num={ALL <Integer>}	Maximum number of entries to show (default: 20).
-port=<port number>	Number of the port to block/unblock.
-prot={TCP UDP ICMP OTHER TCPUDP ALL}	Protocol to block/unblock.
-serv=<service>	Service to block/unblock.
-show	Show information about the blacklisted hosts.
-time=<seconds>	The time that the host will remain blocked.
-unblock	Unblock specified netobject. (Admin only)
-white	Show whitelist hosts only.
<host>	IP address range.

2.2.10. buffers

List packet buffers or the contents of a buffer.

Description

Lists the 20 most recently freed packet buffers, or in-depth information about a specific buffer.

Usage

```
buffers
```

List the 20 most recently freed buffers.

```
buffers -recent
```

Decode the most recently freed buffer.

```
buffers <Num>
```

Decode buffer number <Num>.

Options

-recent	Decode most recently freed buffer.
<Num>	Decode given buffer number.

2.2.11. cam

CAM table information.

Description

Show information about the CAM table(s) and their entries.

Usage

```
cam -num=<n>
```

Show CAM table information.

```
cam <Interface> [-num=<n>]
```

Show interface-specified CAM table information.

```
cam <Interface> [-flush]
```

Flush CAM table information of specified interface.

```
cam -flush
```

Flush CAM table information.

Options

-flush	Flush CAM table. If interface is specified, only entries using this interface are flushed. (Admin only)
-num=<n>	Limit list to <n> entries per CAM table. (Default: 20)
<Interface>	Interface.

2.2.12. certcache

Show the contents of the certificate cache.

Description

Show all certificates in the certificate cache.

Usage

```
certcache [-verbose]
```

Options

-verbose	Show verbose information.
-----------------	---------------------------

2.2.13. cfglog

Display configuration log.

Description

Display the log of the last configuration read attempt.

Usage

```
cfglog
```

2.2.14. connections

List current state-tracked connections.

Description

List current state-tracked connections.

Usage

```
connections -show [-num=<n>] [-verbose] [-srciface=<interface>]
               [-destiface=<interface>] [-protocol=<name/num>]
               [-srcport=<port>] [-destport=<port>] [-srcip=<ip addr>]
               [-destip=<ip addr>] [-ipver={IPV6 | IPV4}]
```

List connections.

```
connections
```

Same as "connections -show".

```
connections -close [-all] [-ipver={IPV6 | IPV4}]
                  [-srciface=<interface>] [-destiface=<interface>]
                  [-protocol=<name/num>] [-srcport=<port>]
                  [-destport=<port>] [-srcip=<ip addr>]
                  [-destip=<ip addr>]
```

Close connections.

Options

-all	Mark all connections.
-close	Close all connections that match the filter expression. (Admin only)
-destiface=<interface>	Filter on destination interface.
-destip=<ip addr>	Filter on destination IP address.
-destport=<port>	Show only given destination TCP/UDP port.
-ipver={IPV6 IPV4}	List only connections of the specified IP version.
-num=<n>	Limit list to <n> connections. (Default: 20)

-protocol=<name/num>	Show only given IP protocol.
-show	Show connections.
-srciface=<interface>	Filter on source interface.
-srcip=<ip addr>	Filter on source IP address.
-srcport=<port>	Show only given source TCP/UDP port.
-verbose	Verbose (more information).

2.2.15. cpuid

Display info about the cpu.

Description

Display the make and model of the machine's CPU.

Usage

```
cpuid
```

2.2.16. crashdump

Show the contents of the crash.dmp file.

Description

Show the contents of the crash.dmp file, if it exists.

Usage

```
crashdump
```

2.2.17. cryptostat

Show information about crypto accelerators.

Description

Show information about installed crypto accelerators.

Usage


```
cryptostat [-hashinfo]
```

Options

-hashinfo Show information about the hardware fastpath hash.

2.2.18. dconsole

Displays the content of the diagnose console.

Description

The diagnose console is used to help troubleshooting internal problems within the security gateway

Usage

```
dconsole [-clean] [-flush] [-date=<date>] [-onlyhigh]
```

Options

-clean Remove all diagnose entries. (Admin only)

-date=<date> YYYY-MM-DD. Only show entries from this date and forward.

-flush Flush all diagnose entries to disk. (Admin only)

-onlyhigh Only show entries with severity high. (Admin only)

2.2.19. dhcp

Display information about DHCP-enabled interfaces or modify/update their leases.

Description

Display information about a DHCP-enabled interface.

Usage

```
dhcp
```

List DHCP enabled interfaces.

```
dhcp -list
```

List DHCP enabled interfaces.

```
dhcp -show [<interface>]
```

Show information about DHCP enabled interface.

```
dhcp -lease={RENEW | RELEASE} <interface>
```

Modify interface lease.

Options

-lease={RENEW RELEASE}	Modify interface lease.
-list	List all DHCP enabled interfaces.
-show	Show information about DHCP enabled interface.
<interface>	DHCP Interface.

2.2.20. dhcprelay

Show DHCP/BOOTP relay ruleset.

Description

Display the content of the DHCP/BOOTP relay ruleset and the current routed DHCP relays.

Display filter filters relays based on interface/ip (example: if1 192.168.*)

Usage

```
dhcprelay
```

Show the currently relayed DHCP sessions.

```
dhcprelay -show [-rules] [-routes] [<display filter>]...
```

Show DHCP/BOOTP relay ruleset.

```
dhcprelay -release <ip address> [-interface=<Interface>]
```

Terminate relayed session.

Options

-interface=<Interface>	Interface.
-release	Terminate relayed session <[interface:]ip>. (Admin only)
-routes	Show the currently relayed DHCP sessions.
-rules	Show the DHCP/BOOTP relay ruleset.
-show	Show ruleset.

<display filter>	Display filter, filters relays based on interface/ip.
<ip address>	IP address.

2.2.21. dhcpserver

Show content of the DHCP server ruleset.

Description

Show the content of the DHCP server ruleset and various information about active/inactive leases.

Display filter filters entries based on Interface/MAC/IP (example: If1 192.168.*)

Usage

```
dhcpserver
```

Show DHCP server leases.

```
dhcpserver -show [-rules] [-leases] [-num=<Integer>]
              [-fromentry=<Integer>] [-mappings] [-utilization]
              [<Display filter>]...
```

Show DHCP server ruleset.

```
dhcpserver -release={BLACKLIST}
```

Release a specific types of IPs.

```
dhcpserver -releaseip <Interface> <IP address>
```

Release an active IP.

Options

-fromentry=<Integer>	Show entry list from offset <n>.
-leases	Show DHCP server leases.
-mappings	Show DHCP server IP mappings.
-num=<Integer>	Limit list to <n> entries.
-release={BLACKLIST}	Release specific type of IPs. (Admin only)
-releaseip	Release an active IP. (Admin only)
-rules	Show DHCP server rules.
-show	Show ruleset.
-utilization	Show IP pool utilization.
<Display filter>	Display filter based on Interface/MAC/IP (eg. If1

	192.168.*).
<Interface>	Interface.
<IP address>	IP address.

2.2.22. dhcpv6server

Show content of the DHCPv6 server ruleset.

Description

Show the content of the DHCPv6 server ruleset and various information about active/inactive leases.

Display filter filters leases based on interface/mac/ip (example: if1 2001:DB8::*)

Usage

```
dhcpv6server
```

Show DHCPv6 server leases.

```
dhcpv6server -releaseip <interface> <IPv6 address>
```

Release an active IP6.

```
dhcpv6server -show [-rules] [-leases] [-num=<Integer>]
                 [-fromentry=<Integer>] [<display filter>]...
```

Show DHCP server ruleset.

Options

-fromentry=<Integer>	Shows dhcp server lease list from offset <n>.
-leases	Show DHCPv6 server leases.
-num=<Integer>	Limit list to <n> leases.
-releaseip	Release an active IP. (Admin only)
-rules	Show DHCPv6 server rules.
-show	Show ruleset.
<display filter>	Display filters for leases based on interface/mac/ip (eg. if1 2001:DB8::*).
<interface>	Interface.
<IPv6 address>	IPv6 address.

2.2.23. dns

DNS client and queries.

Description

Show status of the DNS client and manage pending DNS queries.

Usage

```
dns [-query=<domain name>] [-list] [-remove]
```

Options

-list	List pending DNS queries.
-query=<domain name>	Resolve domain name.
-remove	Remove all pending DNS queries.

2.2.24. dnsbl

DNSBL.

Description

Show status of DNSBL.

Usage

```
dnsbl [-show] [<SMTP ALG>] [-clean]
```

Options

-clean	Clear DNSBL statistics for ALG.
-show	Show DNSBL statistics for ALG.
<SMTP ALG>	Name of SMTP ALG.

2.2.25. dynroute

Show dynamic routing policy.

Description

Show the dynamic routing policy filter ruleset and current exports.

In the "Flags" field of the dynrouting exports, the following letters are used:

- o Route describe the optimal path to the network
- u Route is unexported

Usage

```
dynroute [-rules] [-exports]
```

Options

-exports	Show current exports.
-rules	Show dynamic routing, filter ruleset.

2.2.26. frags

Show active fragment reassemblies.

Description

List active fragment reassemblies.

More detailed information can optionally be obtained for specific reassemblies:

NEW	Newest reassembly
ALL	All reassemblies
0..1023	Assembly 'N'

Example 2.9. frags

```
frags NEW
frags 254
```

Usage

```
frags [{NEW | ALL | <reassembly id>}] [-free] [-done] [-num=<n>]
```

Options

-done	List done (lingering) reassemblies.
-free	List free instead of active.

-num=<n>	List <n> entries. (Default: 20)
{NEW ALL <reassembly id>}	Show in-depth info about reassembly <n>. (Default: all)

2.2.27. ha

Show current HA status.

Description

Show current HA status.

Usage

```
ha [-activate] [-deactivate]
```

Options

-activate	Go active.
-deactivate	Go inactive.

2.2.28. hostmon

Show Host Monitor statistics.

Description

Show active Host Monitor sessions.

Usage

```
hostmon [-verbose] [-num=<n>]
```

Options

-num=<n>	Limit list to <n> entries. (Default: 20)
-verbose	Verbose output.

2.2.29. httpalg

Commands related to the HTTP Application Layer Gateway.

Description

Show information about the WCF cache or list the overridden WCF hosts.

Usage

```
httpalg -override [-flush]
```

List or flush hosts that have overridden the wcf filter.

```
httpalg -wcfcache [-show] [-url=<String>] [-flush] [-verbose]
  [-count] [-server[={STATUS | CONNECT | DISCONNECT}]]
  [-num=<n>]
```

Display URL cache information.

Options

-count	Only display cache count.
-flush	Removes all entries.
-num=<n>	Limit list to <n> entries. (Default: 20)
-override	List hosts that have overridden the wcf filter.
-server[={STATUS CONNECT DISCONNECT}]	Web Content Filtering Server options. (Default: status)
-show	Show Web Content Filtering cache data.
-url=<String>	Limits the output from the show command to only match the specified characters.
-verbose	Verbose.
-wcfcache	Show statistics of WCF functionality.

2.2.30. httpposter

Display HTTP Poster status.

Description

Display configuration and status of configured HTTPPoster_URLx targets.

Usage

```
httpposter [-repost=<Integer>]
```

Options

-repost=<Integer> Re-post URL now. (Admin only)

2.2.31. hwm

Show hardware monitor sensor status.

Description

Show hardware monitor sensor status.

Usage

```
hwm [-all] [-verbose]
```

Options

-all Show ALL sensors, WARNING: use at own risk, may take long time for highspeed ifaces to cope.

-verbose Show sensor number, type and limits.

2.2.32. idppipes

Show and remove hosts that are piped by IDP.

Description

Show list of currently piped hosts.

Usage

```
idppipes
```

List all idppipes.

```
idppipes --show [-host=<ip addr>]
```

Lists hosts for which new connections are piped by IDP.

```
idppipes --unpipe [-all] [-host=<ip addr>]
```

Remove piping for the specified host.

Options

-all mark all hosts.

-host=<ip addr> Filter on source IP address.

-show	Lists hosts for which new connections are piped by IDP.
-unpipe	Remove piping for the specified host. (Admin only)

2.2.33. ifstat

Show interface statistics.

Description

Show list of attached interfaces, or in-depth information about a specific interface.

Usage

```
ifstat [<Interface>] [-filter=<expr>] [-pbr=<table name>]
      [-num=<n>] [-restart] [-allindepth] [-maclist]
```

Options

-allindepth	Show in-depth information about all interfaces.
-filter=<expr>	Filter list of interfaces.
-maclist	Show MAC addresses for all interfaces.
-num=<n>	Limit list to <n> lines. (Default: 20)
-pbr=<table name>	Only list members of given PBR table(s).
-restart	Stop and restart the interface. (Admin only)
<Interface>	Name of interface.

2.2.34. igmp

IGMP Interfaces.

Description

Show information about the current state of the IGMP interfaces.

Send simulated messages to test configuration of the interface.

Usage

```
igmp
```

Prints the current IGMP state.

```
igmp -state [<Interface>]
```

Prints the current IGMP state. If an interface is specified, more details are provided.

```
igmp -query <Interface> [<MC address> [<router address>]]
```

Simulate an incoming IGMP query message.

```
igmp -join <Interface> <MC address> [<host address>]
```

Simulate an incoming IGMP join message.

```
igmp -leave <Interface> <MC address> [<host address>]
```

Simulate an incoming IGMP leave message.

Options

-join	Simulate an incoming IGMP join message.
-leave	Simulate an incoming IGMP leave message.
-query	Simulate an incoming IGMP query message.
-state	Show the current IGMP state.
<host address>	Host IP address.
<Interface>	Interface.
<MC address>	Multicast Address.
<router address>	Router IP address.

2.2.35. ihs

Alias for **ipsechastat**.

2.2.36. ikesnoop

Enable or disable IKE-snooping.

Description

Turn IKE on-screen snooping on/off. Useful for troubleshooting IPsec connections.

Usage

```
ikesnoop
```

Show IKE snooping status.

```
ikesnoop -on [<ip address>] [-verbose]
```

Enable IKE snooping.

```
ikesnoop -off
```

Disable IKE snooping.

Options

-off	Turn IKE snooping off.
-on	Turn IKE snooping on.
-verbose	Enable IKE snooping with verbose output.
<ip address>	IP address to snoop.

2.2.37. ippool

Show IP pool information.

Description

Show information about the current state of the configured IP pools.

Usage

```
ippool
```

Show IP pool information.

```
ippool -release [<ip address>] [-all]
```

Forcibly free IP assigned to subsystem.

```
ippool -renew [<ip address>] [-all]
```

Try to renew IP leases through DHCP Server.

```
ippool -show [-verbose] [-num=<n>]
```

Show IP pool information.

Options

-all	Free or renew all IP addresses.
-num=<n>	Limit list to <n> entries. (Default: 10)
-release	Forcibly free IP assigned to subsystem. (Admin only)
-renew	Try to renew IP leases through DHCP Server. (Admin only)
-show	Show IP pool information.
-verbose	Verbose output.

<ip address>

IP address to free or renew.

2.2.38. ipsecdefines

Display various DEFINES that specify the system performance.

Description

Display various DEFINES that specify the system performance.

Usage

```
ipsecdefines
```

2.2.39. ipsecglobalstats

Show global ipsec statistics.

Description

List global IPsec statistics.

Usage

```
ipsecglobalstats -mem [-verbose]
```

Start IKE test.

```
ipsecglobalstats -verbose
```

Start IKE test.

```
ipsecglobalstats
```

Show interfaces.

Options

-mem Show memory statistics.

-verbose Show all statistics.

2.2.40. ipsechastat

Show statistics about HA synchronization for IPsec.

Description

Shows statistics about IKE/IPsec SAs synchronized and how many that failed to import. Sent statistics shows how many packets that has been sent to the other cluster member when this node was active and receive statistics show how many packets/failures it got as inactive.

Usage

```
ipsechastat [-clear]
```

Options

-clear	Reset all statistics.
---------------	-----------------------

2.2.41. ipsecstats

Show the SAs in use.

Description

List the currently active IKE and IPsec SAs, optionally only showing SAs matching the pattern given for the argument "tunnel".

Usage

```
ipsecstats [-ike] [<tunnel>] [-ipsec] [-usage] [-verbose]  
           [-num={ALL | <Integer>}] [-force]
```

Options

-force	Bypass confirmation question.
-ike	Show IKE SAs.
-ipsec	Show IPsec SAs.
-num={ALL <Integer>}	Maximum number of entries to show (default: 40/8).
-usage	Show detailed SA statistics information.
-verbose	Show verbose information.
<tunnel>	Only show SAs matching pattern.

2.2.42. ipsectunnels

Lists the current IPsec configuration.

Description

Lists the current IPsec configuration,

Usage

```
ipsectunnels -iface=<recv iface>
```

Show specific interface.

```
ipsectunnels -num={ALL | <Integer>} [-force]
```

Show specific number if interface.

```
ipsectunnels
```

Show interfaces.

Options

-force	Bypass confirmation question.
-iface=<recv iface>	IPsec interface to show information about.
-num={ALL <Integer>}	Maximum number of entries to show (default: 40).

2.2.43. killsa

Kill all SAs belonging to the given remote SG/peer.

Description

Kill all (IPsec and IKE) SAs associated with a given remote IKE peer IP or optional all SA:s in the system. IKE delete messages are sent.

Usage

```
killsa <ip address> [-iface=<interface>]
```

Delete SAs belonging to provided remote SG/peer.

```
killsa -all [-iface=<interface>]
```

Delete all SAs.

Options

-all	Kill all SAs.
-iface=<interface>	Remote interface for SG/peer.

<ip address>

IP address of remote SG/peer.

**Note**

Requires Administrator privileges.

2.2.44. languagefiles

Manage language files on disk.

Description

Manage language files on disk

Usage

```
languagefiles
```

Show all language files on disk.

```
languagefiles -remove=<String>
```

Remove a language file from disk.

Options

-remove=<String>

Specify language file to delete.

2.2.45. ldap

LDAP information.

Description

Status and statistics for the configured LDAP databases.

Usage

```
ldap
```

List all LDAP databases.

```
ldap -list
```

List all LDAP databases.

```
ldap -show [<LDAP Server>]
```


Show LDAP database status and statistics.

```
ldap -reset [<LDAP Server>]
```

Reset LDAP database.

Options

-list	List all LDAP databases.
-reset	Reset status for LDAP database.
-show	Show status and statistics.
<LDAP Server>	LDAP database.

2.2.46. license

License management.

Description

Manage the contents of the current license.

Usage

```
license
```

Show the contents of the current license.

```
license --show
```

Show the contents of the current license.

```
license -activate [-request] [-username=<String>]
                 [-password=<String>]
```

Activates a license.

```
license -remove
```

Deletes the current license.

```
license -update
```

Initiate a license update.

Options

-activate	Manages license activation. (Admin only)
-password=<String>	Sets password to be used. (Admin only)
-remove	Remove license file from the Security Gateway. (Admin only)

-request	Send request to Clavister server to activate license. (Admin only)
-show	Show current status and credentials.
-update	Initiate a license update. (Admin only)
-username=<String>	Sets username to be used. (Admin only)

2.2.47. linkmon

Display link monitoring statistics.

Description

. If link monitor hosts have been configured, linkmon will monitor host reachability to detect link/NIC problems.

Usage

```
linkmon
```

2.2.48. logout

Logout user.

Description

Logout current user.

Usage

```
logout
```

2.2.49. memory

Show memory information.

Description

Show core memory consumption. Also show detailed memory use of some components and lists.

Usage

```
memory
```

2.2.50. natpool

Show current NAT Pools.

Description

Show current NAT Pools and in-depth information.

Usage

```
natpool [-verbose] [<pool name> [<IP4 Address>]] [-num=<Integer>]
```

Options

-num=<Integer>	Maximum number of items to list (default: 20).
-verbose	Verbose (more information).
<IP4 Address>	Translated IP.
<pool name>	NAT Pool name.

2.2.51. nd

Show Neighbor Discovery entries for given interface.

Description

List the Neighbor Discovery cache entries of specified interfaces.

If no interface is given the Neighbor Discovery cache entries of all interfaces will be presented.

The presented list can be filtered using the *ip* and *hw* options.

Usage

```
nd
```

Show all Neighbor Discovery entries.

```
nd -show [<Interface>] [-ip=<pattern>] [-hw=<pattern>] [-num=<n>]
```

Show Neighbor Discovery entries.

```
nd -hashinfo [<Interface>]
```

Show information on hash table health.

```
nd -flush [<Interface>]
```

Flush Neighbor Discovery cache of specified interface.

```
nd -query=<ip> <Interface>
```

Send Neighbor Solicitation for IP.

```
nd -del=<ip> <Interface>
```

Delete ND cache entry.

Options

-del=<ip>	Delete ND cache entry <ip>.
-flush	Flush Neighbor Discovery cache of all specified interfaces.
-hashinfo	Show information on hash table health.
-hw=<pattern>	Show only hardware addresses matching pattern.
-ip=<pattern>	Show only IP addresses matching pattern.
-num=<n>	Show only the first <n> entries per interface. (Default: 20)
-query=<ip>	Send Neighbor Solicitation for <ip>.
-show	Show Neighbor Discovery entries for given interface(s).
<Interface>	Interface name.

2.2.52. ndsnoop

Toggle snooping and displaying of ARP requests.

Description

Toggle snooping and displaying of Neighbor Discovery queries and responses on-screen.

The snooped messages are displayed before the access section validates the sender IP addresses in the ARP data.

Usage

```
ndsnoop
```

Show snooped interfaces.

```
ndsnoop {ALL | NONE | <interface>} [-verbose]
```

Snoop specified interface.

Options

-verbose	Verbose.
{ALL NONE <interface>}	Interface name.

2.2.53. netcon

List all NetCon users.

Description

Show a list of connected NetCon users.

Usage

```
netcon
```

2.2.54. netobjects

Show runtime values of network objects.

Description

Displays named network objects and their contents.

Example 2.10. List network objects which have names containing "net".

```
netobjects *net*
```

Usage

```
netobjects [<String>] [-num=<num>]
```

Options

-num=<num>	Number of entries to show. (Default: 20)
<String>	Name or pattern.

2.2.55. ospf

Show runtime OSPF information.

Description

Show runtime information about the OSPF router process(es).

Note: `-process` is only required if there are >1 OSPF router processes.

Usage

```
ospf
```

Show runtime information.

```
ospf -iface [<interface>] [-process=<OSPF Router Process>]
```

Show interface information.

```
ospf -area [<OSPF Area>] [-process=<OSPF Router Process>]
```

Show area information.

```
ospf -neighbor [<OSPF Neighbor>] [-process=<OSPF Router Process>]
```

Show neighbor information.

```
ospf -route [{HA | ALT}] [-process=<OSPF Router Process>]
```

Show the internal OSPF process routingtable.

```
ospf -database [-verbose] [-process=<OSPF Router Process>]
```

Show the LSA database.

```
ospf -lsa <lsaID> [-process=<OSPF Router Process>]
```

Show details for a specified LSA.

```
ospf -snoop={ON | OFF} [-process=<OSPF Router Process>]
```

Show troubleshooting messages on the console.

```
ospf -ifacedown <interface> [-process=<OSPF Router Process>]
```

Take specified interface offline.

```
ospf -ifaceup <interface> [-process=<OSPF Router Process>]
```

Take specified interface online.

```
ospf -execute={STOP | START | RESTART}
      [-process=<OSPF Router Process>]
```

Start/stop/restart OSPF process.

Options

-area Show area information.

-database	Show the LSA database.
-execute={STOP START RESTART}	Start/stop/restart OSPF process. (Admin only)
-iface	Show interface information.
-ifacedown	Take specified interface offline. (Admin only)
-ifaceup	Take specified interface online. (Admin only)
-lsa	Show details for a specified LSA <lsaID>.
-neighbor	Show neighbor information.
-process=<OSPF Router Process>	Required if there are >1 OSPF router processes.
-route	Show the internal OSPF process routingtable.
-snoop={ON OFF}	Show troubleshooting messages on the console.
-verbose	Increase amount of information to display.
<interface>	OSPF enabled interface.
<interface>	OSPF enabled interface.
<lsaID>	LSA ID.
<OSPF Area>	OSPF Area.
<OSPF Neighbor>	Neighbor.
{HA ALT}	Show HA routingtable.

2.2.56. pcapdump

Packet capturing.

Description

Packet capture engine

Usage

```
pcapdump
```

Show capture status.

```
pcapdump -start [<interface(s)>] [-size=<value>] [-snaplen=<value>]
[-count=<value>] [-out] [-out-nocap]
[-eth=<Ethernet Address>] [-ethsrc=<Ethernet Address>]
[-ethdest=<Ethernet Address>] [-ip=<IP4 Address>]
[-ipsrc=<IP4 Address>] [-ipdest=<IP4 Address>]
[-port=<0...65535>] [-srcport=<0...65535>]
[-destport=<0...65535>] [-proto=<0...255>] [-icmp] [-tcp]
[-udp] [-promisc] [-ipversion=<1...15>]
```

Start capture.

```
pcapdump -stop [<interface(s)>]
```

Stop capture.

```
pcapdump -status
```

Show capture status.

```
pcapdump -show [<interface(s)>] [-num={ALL | <Integer>}]
```

Show a captured packets brief.

```
pcapdump -write [<interface(s)>] [-filename=<String>]
```

Write the captured packets to disk.

```
pcapdump -wipe
```

Remove all captured packets from memory.

```
pcapdump -cleanup
```

Remove all captured packets, release capture mode and delete all written capture files from disk.

Options

-cleanup	Remove all captured packets, release capture mode and delete all written capture files from disk.
-count=<value>	Number of packets to capture.
-destport=<0...65535>	Destination TCP/UDP port filter.
-eth=<Ethernet Address>	Ethernet address filter.
-ethdest=<Ethernet Address>	Ethernet destination address filter.
-ethsrc=<Ethernet Address>	Ethernet source address filter.
-filename=<String>	Filename for capture file.
-icmp	ICMP filter.
-ip=<IP4 Address>	IP address filter.
-ipdest=<IP4 Address>	Destination IP address filter.
-ipsrc=<IP4 Address>	Source IP address filter.
-ipversion=<1...15>	IP version filter.
-num={ALL <Integer>}	Maximum number of entries to show (default: 20).
-out	Realtime packet brief dumped to console.
-out-nocap	Unbuffered (not stored in memory) realtime packet brief dumped to console.
-port=<0...65535>	TCP/UDP port filter.
-promisc	Set iface in promiscuous mode.

-proto=<0...255>	IP protocol filter.
-show	Show a captured packets brief.
-size=<value>	Size (kb) of buffer to store captured packets in memory (default 512kb).
-snaplen=<value>	Maximum length of each packet to capture.
-srcport=<0...65535>	Source TCP/UDP port filter.
-start	Start capture.
-status	Show capture status.
-stop	Stop capture.
-tcp	TCP filter.
-udp	UDP filter.
-wipe	Remove all captured packets from memory.
-write	Write the captured packets to disk.
<interface(s)>	Name of interface(s).

**Note**

Requires Administrator privileges.

2.2.57. pciscan

Show detected PCI devices.

Description

Usage

```
pciscan
```

Show identified ethernet devices.

```
pciscan -all
```

Show all detected devices.

```
pciscan -ethernet
```

Show all detected ethernet devices.

```
pciscan -cfgupdate
```

Updates the config with detected devices.

```
pciscan -force_driver <Integer> {BROADCOM | BNE2 | E100 | E1000 |
R8139 | R8169 | MARVELL | NITROXII | ST201 | TULIP |
X3C905}
```

Force a certain driver to a device.

Options

-all	Show all detected devices.
-cfgupdate	Updates the config with detected devices. (Admin only)
-ethernet	Show all detected ethernet devices.
-force_driver	Force a certain device to a specific driver. (Admin only)
<Integer>	Index of device to update.
{BROADCOM BNE2 E100 E1000 R8139 R8169 MARVELL NITROXII ST201 TULIP X3C905}	Interface driver to use.

2.2.58. pipes

Show pipes information.

Description

Show list of configured pipes / pipe details / pipe users.

Note: The "pipes" command is not executed right away; it is queued until the end of the second, when pipe values are calculated.

Usage

```
pipes
```

List all pipes.

```
pipes -users [<Pipe>] [-expr=<String>]
```

List users of a given pipe.

```
pipes -show [<Pipe>] [-expr=<String>]
```

Show pipe details.

Options

-expr=<String>	Pipe wildcard(*) expression.
-show	Show pipe details.
-users	List users of a given pipe.

<Pipe>

Show pipe details.

2.2.59. pptpalg

Show PPTP ALG information.

Description

Shows information and statistics of the PPTP ALGs.

Usage

```
pptpalg
```

Show all configured PPTP ALGs.

```
pptpalg -sessions <PPTP ALG> [-verbose] [-num=<Integer>]
```

List all PPTP sessions.

```
pptpalg -services <PPTP ALG>
```

List all services attached to PPTP ALG.

Options

-num=<Integer>	Number of entries to list.
-services	List all services attached to PPTP ALG.
-sessions	List all session using a PPTP tunnel.
-verbose	Verbose output.
<PPTP ALG>	PPTP ALG.

2.2.60. reconfigure

Initiates a configuration re-read.

Description

Restart the Security Gateway using the currently active configuration.

Usage



Note

Requires Administrator privileges.

2.2.61. rekeysa

Rekey IPsec or IKE SAs established with given remote peer.

Description

Rekey IPsec or IKE SAs associated with a given remote IKE peer, or optionally all IPsec or IKE SAs in the system.

Usage

```
rekeysa -ike <ip address>
```

Rekey IKE SAs.

```
rekeysa -ipsec <ip address>
```

Rekey IPsec SAs.

```
rekeysa <ip address>
```

Rekey IPsec SAs.

Options

-ike	Rekey IKE SAs.
-ipsec	Rekey IPsec SAs.
<ip address>	IP address of remote peer.



Note

Requires Administrator privileges.

2.2.62. route

Alias for **routes**.

2.2.63. routemon

List the currently monitored interfaces and gateways.

Description

List the currently monitored interfaces and/or gateways.

Usage

```
routemon
```

2.2.64. routes

Display routing lists.

Description

Display information about the routing table(s):

- Contents of a (named) routing table.
- The list of routing tables, along with a total count of route entries in each table, as well as how many of the entries are single-host routes.

Note that "core" routes for interface IP addresses are not normally shown. Use the `-all` switch to show core routes also.

Use the `-switched` switch to show only switched routes.

Explanation of Flags field of the routing tables:

- O** Learned via OSPF
- X** Route is Disabled
- M** Route is Monitored
- A** Published via Proxy ARP
- D** Dynamic (from e.g. DHCP relay, IPsec, L2TP/PPP servers, etc.)
- H** HA synced from cluster peer

Usage

```
routes [-all] [<table name>] [-switched] [-flushl3cache] [-num=<n>]
      [-nonhost] [-tables] [-lookup=<ip address>] [-verbose]
```

Options

- | | |
|-----------------------------------|---|
| -all | Also show routes for interface addresses. |
| -flushl3cache | Flush Layer 3 Cache. |
| -lookup=<ip address> | Lookup the route for the given IP address. |
| -nonhost | Do not show single-host routes. |
| -num=<n> | Limit display to <n> entries. (Default: 20) |
| -switched | Only show switched routes and L3C entries. |

-tables	Display list of named (PBR) routing tables.
-verbose	Verbose.
<table name>	Name of routing table.

2.2.65. rtmonitor

Real-time monitor information.

Description

Show information about real-time monitor objects, and real-time monitor alerts.

All objects matching the specified filter are displayed. The filter can be the name of an object, or the beginning of a name. If no filter is specified, all objects are displayed.

If the option "monitored" is specified, only objects that have an associated real-time monitor alert are displayed.

Example 2.11. Show all monitored objects in the alg/http category

```
gw-world: /> rtmonitor alg/http -m
```

Usage

```
rtmonitor [<filter>] [-terse] [-monitored]
```

Options

-monitored	Only show monitored objects.
-terse	Only show object name.
<filter>	Object filter.

2.2.66. rules

Show rules lists.

Description

Shows the content of the various types of rules, i.e. main ruleset, pipe ruleset, etc.

Example 2.12. Show a range of rules

```
rules -verbose 1-5 7-9
```

Usage

```
rules -type=IP [-ruleset={* | MAIN | <IP Rule Set>}] [-verbose]
      [-schedule] [<rules>]...
```

Show IP rules.

```
rules -type={ROUTING | PIPE | IDP | THRESHOLD | IGMP} [-verbose]
      [-schedule] [<rules>]...
```

Show a specific type of rules.

Options

-ruleset={* MAIN <IP Rule Set>}	Show a specified IP ruleset.
-schedule	Filter out rules that are not currently allowed by selected schedules.
-type={IP ROUTING PIPE IDP THRESHOLD IGMP}	Type of rules to display. (Default: IP)
-verbose	Verbose: show all parameters of the rules.
<rules>	Range of rules to display. (default: all rules).

2.2.67. selftest

Run appliance self tests.

Description

The appliance self tests are used to verify the correct function of hardware components.

IMPORTANT: In order for a selftest result to be reliable the test must be run using a default configuration and having the SGW disconnected from any networks.

IMPORTANT: Normal SGW operations might be disrupted during the test(s).

The outcome of the throughput crypto accelerator tests are dependent on configuration values. If the number of large buffers (LocalReassSettings->LocalReass_NumLarge) too low, it might lower throughput result. In the field 'Drop/Fail', the 'Drop' column contains the number of packets that were dropped before ever reaching the crypto accelerator and the 'Fail' column contains the number of packets that for some reason failed encryption. The 'Pkt In/Out' field shows the total number of packets sent to, and returned from the accelerator.

The interface tests 'traffic' and 'throughput' are dependent on the settings for the NIC ring sizes and possibly also license limitations. The 'traffic' test uses a uniform random distribution of six packet sizes between 60 and 1518 bytes. The content of each received packet is validated. The 'throughput' test uses only the largest packet size, and does not validate the contents of the received packets.

Example 2.13. Interface ping test between all interfaces

```
selftest -ping
```

Example 2.14. Interface ping test between interfaces 'if1' and 'if2'

```
selftest -ping -interfaces=if1,if2
```

Example 2.15. Start 30 min burn-in, testing RAM, storage media and crypto accelerator

```
selftest -burnin -minutes 30 -media -memory -cryptoaccel
```

Usage

```
selftest -memory [-num=<Integer>]
```

Check the sanity of the RAM.

```
selftest -media [-size=<Integer>]
```

Check the sanity of the disk drive.

```
selftest -mac
```

Check if there are MAC address collisions on the interfaces.

```
selftest -ping [-interfaces=<Interface>]
```

Run a ping test over the interfaces.

```
selftest -throughput [-interfaces=<Interface>]
```

Run a throughput test over the interfaces.

```
selftest -traffic [-interfaces=<Interface>]
```

Run a traffic test over the interfaces.

```
selftest -cryptoaccel
```

Verify the correct functioning of the accelerator cards.

```
selftest -burnin [-hours[=<Integer>]] [-minutes[=<Integer>]]
           [-memory] [-media] [-ping] [-throughput] [-traffic]
           [-cryptoaccel]
```

Run burn-in tests for a set of sub tests. If no sub tests are specified the following are included: -memory, -ping, -traffic, -cryptoaccel.


```
selftest -abort
```

Abort a running self test.

```
selftest
```

Show the status of a running test.

Options

-abort	Abort a running self test.
-burnin	Run burn-in tests for a selected set of sub tests.
-cryptoaccel	Verify the correct functioning of available crypto accelerator cards.
-hours[=<Integer>]	Test duration in hours. (Default: 48)
-interfaces=<Interface>	Ethernet interface(s).
-mac	Check if there are MAC address collisions on the interfaces.
-media	Check the sanity of the disk drive.
-memory	Check the sanity of the RAM.
-minutes[=<Integer>]	Test duration in minutes. (Default: 0)
-num=<Integer>	Number of times to execute the test. (Default: 1)
-ping	Run a ping test over the interfaces.
-size=<Integer>	Size of media space to utilize in the test. Set in MB. (Default: 1)
-throughput	Run a throughput test over the interfaces. This will show the maximal achievable interface throughput.
-traffic	Run a traffic test over the interfaces. The traffic test uses mixed frame sizes and verifies the content of each received frame.



Note

Requires Administrator privileges.

2.2.68. services

Show runtime values of configured services.

Description

Shows the runtime values of all configured services.

Example 2.16. List all services which names begin with "http"

```
services http*
```

Usage

```
services [<String>]
```

Options

<String> Name or pattern.

2.2.69. sessionmanager

Session Manager.

Description

Show information about the Session Manager, and list currently active users.

Explanation of Timeout flags for sessions:

- D** Session is disabled
- S** Session uses a timeout in its subsystem
- Session does not use timeout

Usage

```
sessionmanager
```

Show Session Manager status.

```
sessionmanager -status
```

Show Session Manager status.

```
sessionmanager -list [-num=<n>]
```

List active sessions.

```
sessionmanager -info <session name> <database>
```

Show in-depth information about session(s).

```
sessionmanager -message <session name> <database> <message text>
```

Send message to session with console.

```
sessionmanager -disconnect <session name> <database> [<IP Address>
[{{LOCAL | SSH | NETCON | HTTP | HTTPS}}]]
```

Forcibly terminate session(s).

Options

-disconnect	Forcibly terminate session(s). (Admin only)
-info	Show in-depth information about session.
-list	List active sessions.
-message	Send message to session.
-num=<n>	List <n> number of session.
-status	Show Session Manager status.
<database>	Name of user database.
<IP Address>	IP address.
<message text>	Message to send.
<session name>	Name of session.
{LOCAL SSH NETCON HTTP HTTPS}	Session type.

2.2.70. settings

Show settings.

Description

Show the contents of the settings section, category by category.

Usage

```
settings
```

Show list of categories.

```
settings <category>
```

Show settings in category.

Options

<category>	Show settings in category.
-------------------------	----------------------------

2.2.71. shutdown

Initiate core or system shutdown.

Description

Initiate restart of the core/system.

Usage

```
shutdown [<seconds>] [-normal] [-reboot]
```

Options

-normal	Initiate core shutdown.
-reboot	Initiate system reboot.
<seconds>	Seconds until shutdown. (Default: 5)



Note

Requires Administrator privileges.

2.2.72. sipalg

SIP ALG.

Description

List running SIP-ALG configurations, SIP registration and call information.

The `-flags` option with `-snoop` allows any combination of the following values:

- 0x00000001 GENERAL
- 0x00000002 ERRORS
- 0x00000004 OPTIONS
- 0x00000008 PARSE
- 0x00000010 VALIDATE
- 0x00000020 SDP
- 0x00000040 ALLOW_CHANGES
- 0x00000080 SUPPORTED_CHANGES
- 0x00000100 2543COMPLIANCE
- 0x00000200 RECEPTION
- 0x00000400 SESSION

- 0x00000800 REQUEST
- 0x00001000 RESPONSE
- 0x00002000 TOPO_CHANGES
- 0x00004000 MEDIA
- 0x00008000 CONTACT
- 0x00010000 CONN
- 0x00020000 PING
- 0x00040000 TRANSACTION
- 0x00080000 CALLE
- 0x00100000 REGISTRY

Flags can be added in the usual way. The default value is 0x00000003 (GENERAL and ERRORS).

NOTE: 'verbose' option outputs a lot of information on the console which may lead to system instability. Use with caution.

Usage

```
sipalg -definition <alg>
```

Show running ALG configuration parameters.

```
sipalg -registration[={SHOW | FLUSH}] <alg>
```

Show or flush current registration table.

```
sipalg -calls <alg>
```

Show active calls table.

```
sipalg -session <alg>
```

Show active SIP sessions.

```
sipalg -connection <alg>
```

Show SIP connections.

```
sipalg -statistics[={SHOW | FLUSH}] <alg>
```

Show or flush SIP counters.

```
sipalg -snoop={ON | OFF | VERBOSE} [<ipaddr>] [-flags=<String>]
```

Control SIP snooping. Useful for troubleshooting SIP transactions. NOTE: 'verbose' option outputs a lot of information on the console which may lead to system instability. Use with caution.

Options

-calls	Show active calls table.
-connection	Show SIP connections.
-definition	Show running ALG configuration parameters.
-flags=<String>	SIP snooping for certain levels. Expected number in hexadecimal notation.
-registration[={SHOW FLUSH}]	Show or flush registration table. (Default: show)
-session	Show active SIP sessions.
-snoop={ON OFF VERBOSE}	Enable or disable SIP snooping. NOTE: 'verbose' option outputs a lot of information on the console which may lead to system instability. Use with caution.
-statistics[={SHOW FLUSH}]	Show or flush SIP counters. (Default: show)
<alg>	SIP-ALG name.
<ipaddr>	IP Address to snoop.

2.2.73. sshserver

SSH Server.

Description

Show SSH Server status, or start/stop/restart SSH Server.

Usage

```
sshserver
```

Show server status and list all connected clients.

```
sshserver -status [-verbose]
```

Show server status and list all connected clients.

```
sshserver -keygen [-b=<bits>] [-t={RSA | DSA}]
```

Generate SSH Server private keys.

```
sshserver -restart <ssh server>
```

Restart SSH Server.

Options

-b=<bits>	Bitsize. (Default: 1024)
-keygen	Generate SSH Server private keys. This operation may take a long time to finish, up to several

	minutes!
-restart	Stop and start the SSH Server.
-status	Show server status and list all connected clients.
-t={RSA DSA}	Type, (default: both RSA and DSA keys will be created).
-verbose	Verbose output.
<ssh server>	SSH Server.



Note
Requires Administrator privileges.

2.2.74. sslvpn

SSLVPN tunnels.

Description

List running SSLVPN configurations, SSLVPN active tunnels and call information.

Usage

```
sslvpn [ -num=<n> ]
```

Options

-num=<n> Limit display to <n> entries. (Default: 20)

2.2.75. stats

Display various general firewall statistics.

Description

Display general information about the firewall, such as uptime, CPU load, resource consumption and other performance data.

Usage

```
stats
```

2.2.76. sysmsgs

System messages.

Description

Show contents of the FWLoader sysmsg buffer.

Usage

```
sysmsgs
```

2.2.77. techsupport

Technical Support information.

Description

Generate information useful for technical support.

Due to the large amount of output, this command might show a truncated result when execute from the local console.

Usage

```
techsupport
```

2.2.78. time

Display current system time.

Description

Display/set the system date and time.

Usage

```
time
```

Display current system time.

```
time -set <date> <time>
```

Set system local time: <YYYY-MM-DD> <HH:MM:SS>.

```
time -sync [-force]
```


Synchronize time with timeserver(s) (specified in settings).

Options

-force	Force synchronization regardless of the MaxAdjust setting.
-set	Set system local time: <YYYY-MM-DD> <HH:MM:SS>.
-sync	Synchronize time with timeserver(s) (specified in settings).
<date>	Date YYYY-MM-DD.
<time>	Time HH:MM:SS.

2.2.79. uarules

Show user authentication rules.

Description

Displays the contents of the user authentication ruleset.

Example 2.17. Show a range of rules

```
uarules -v 1-2,4-5
```

Usage

```
uarules [-verbose] [<Integer Range>]
```

Options

-verbose	Verbose output.
<Integer Range>	Range of rules to list.

2.2.80. updatecenter

Show status and manage autoupdate information.

Description

Show autoupdate mechanism status or force an update.

Usage

```
updatecenter
```

Show update status and database information.

```
updatecenter -status[={ANTIVIRUS | IDP | ALL}] [-verbose]
```

Show update status and database information.

```
updatecenter -update[={ANTIVIRUS | IDP | ALL}]
```

Initiate an update check of the specified database.

```
updatecenter -removedb={ANTIVIRUS | IDP}
```

Remove the specified signature database.

```
updatecenter -servers
```

Show status of update servers.

Options

-removedb={ANTIVIRUS IDP}	Remove the database for the specified service.
-servers	Show autoupdate server information.
-status[={ANTIVIRUS IDP ALL}]	Show update status and service information. (Admin only; Default: all)
-update[={ANTIVIRUS IDP ALL}]	Force an update now for the specified service. (Admin only; Default: all)
-verbose	Show verbose status information. (Admin only)

2.2.81. userauth

Show logged-on users.

Description

Show currently logged-on users and other information. Also allows logged-on users to be forcibly logged out.

Note: In the user listing *-list*, only privileges actually used by the policy are displayed.

Usage

```
userauth
```

List all authenticated users.

```
userauth -list [-num=<n>]
```

List all authenticated users.

```
userauth -privilege
```

List all known privileges (usernames and groups).

```
userauth -user <user ip>
```

Show all information for user(s) with this IP address.

```
userauth -remove <user ip> <Interface>
```

Forcibly log out an authenticated user.

Options

-list	List all authenticated users.
-num=<n>	Limit list of authenticated users. (Default: 20)
-privilege	List all known privileges (usernames and groups).
-remove	Forcibly log out an authenticated user. (Admin only)
-user	Show all information for user(s) with this IP address.
<Interface>	Interface.
<user ip>	IP address for user(s).

2.2.82. vlan

Show information about VLAN.

Description

Show list of attached Virtual LAN Interfaces, or in-depth information about a specified VLAN.

Usage

```
vlan
```

List attached VLANs.

```
vlan -num=<n> [-page[=<n>]]
```

Set number of display lines per page and display page.

```
vlan <Interface>
```

Display in-depth information about a VLAN interface, and/or the VLAN interfaces that are based on a specific interface.

Options

-num=<n>	Limit display lines to <n> entries in page. (Default: 20)
-page[=<n>]	Set page <n> for lines to display. (Default: 1)
<Interface>	Display VLAN information about this interface.

2.2.83. vpnstats

Alias for **ipseccstats**.

2.3. Utility

2.3.1. ping

Ping host.

Description

Sends one or more ICMP ECHO, TCP SYN or UDP datagrams to the specified IP address of a host. All datagrams are sent preloaded-style (all at once).

The data size *-length* given is the ICMP or UDP data size. 1472 bytes of ICMP data results in a 1500-byte IP datagram (1514 bytes ethernet).

Usage

```
ping <host> [-srcif=<interface>] [-srcip=<ip address>]
  [-pbr=<table>] [-count=<1...10>] [-length=<2...8192>]
  [-port=<0...65535>] [-udp] [-tcp] [-tos=<0...255>] [-verbose]
```

Options

-count=<1...10>	Number of packets to send. (Default: 1)
-length=<2...8192>	Packet size. (Default: 4)
-pbr=<table>	Route using PBR Table.
-port=<0...65535>	Destination port of UDP or TCP ping.
-srcif=<interface>	Pass packet through the rule set, simulating that the packet was received by <srcif>.
-srcip=<ip address>	Use this source IP.
-tcp	Send TCP ping.
-tos=<0...255>	Type of service.
-udp	Send UDP ping.
-verbose	Verbose (more information).
<host>	IP address of host to ping.

2.4. Misc

2.4.1. echo

Print text.

Description

Print text to the console.

Example 2.18. Hello World

```
echo Hello World
```

Usage

```
echo [<String>]...
```

Options

<String> Text to print.

2.4.2. help

Show help for selected topic.

Description

The help system contains information about commands and configuration object types.

The fastest way to get help is to simply type **help** followed by the topic that you want help with. A topic can be for example a command name (e.g. **set**) or the name of a configuration object type (e.g. **User**).

When you don't know the name of what you are looking for you can specify the category of the wanted topic with the `-category` option and use tab-completion to display a list of matching topics.

Usage

```
help
```

List commands alphabetically.

```
help <Topic>
```

Display help about selected topic from any category.

```
help -category={COMMANDS | TYPES} [<Topic>]
```

Display help from a specific topic category.

Options

-category={COMMANDS TYPES}	Topic category.
<Topic>	Help topic.

2.4.3. history

Dump history to screen.

Description

List recently typed commands that have been stored in the command history.

Usage

```
history
```

2.4.4. logsnoop

Display and filter system log messages.

Description

The logsnoop command can be used to display system log events. The source of the log events can be MemLog, real-time or both MemLog followed by real-time logs.

MemLog searching will only be functioning if a LogReceiverMemory object has been configured.

Since the system log rate may be high, displaying real time logs must be done with some caution. For this purpose, it is possible to limit the real time log display rate.

When filtering for log messages to display, there are many parameters that can be filtered on. The most powerful filtering tool is the wildcard matching in which the character '*' is interpreted as none/many characters and '?' as any single character.

It should be noted that all log filtering will have a negative effect on system performance.

Example 2.19. Show log message having 'warning' followed by 'udp' somewhere in the message

```
:/> logsnoop -on -pattern=*warning*udp*
```

Example 2.20. Rate limit log flow to five logs per second

```
:/> logsnoop -on -rate=5
```

Example 2.21. Show logs from the memlog buffer

```
:/> logsnoop -on -source=memlog
```

Example 2.22. Show logs having a source IP value

```
:/> logsnoop -on -srcip=0.0.0.0/0
```

Example 2.23. Show logs having a severity of warning or higher

```
:/> logsnoop -on -severity=warning
```

Usage

```
logsnoop -on [-source={MEMLOG | REALTIME | BOTH}]
[-category=<String>] [-logid=<Integer>] [-event=<String>]
[-action={NONE | DROP | ALLOW | BLOCK | REJECT |
<String>}] [-severity={EMERGENCY | ALERT | CRITICAL |
ERROR | WARNING | NOTICE | INFO | DEBUG}]
[-starttime=<DateTime>] [-endtime=<DateTime>]
[-pattern=<String>] [-srcip=<IPAddress>]
[-destip=<IPAddress>] [-srcport=<0...65535>]
[-destport=<0...65535>] [-srcif=<Interface>]
[-destif=<Interface>] [-ipproto={TCP | UDP | ICMP |
<String>}] [-rate=<Integer>] [-num=<Integer>]
```

Start log session.

```
logsnoop -off
```

Stop log session.

```
logsnoop
```

Show log snoop status.

Options

-action={NONE | DROP | ALLOW | BLOCK | REJECT | <String>} Log action to filter on.

-category=<String> Log category to filter on.

-destif=<Interface>	Destination interface to filter on.
-destip=<IPAddress>	Destination IP address or network to filter on.
-destport=<0...65535>	Destination port to filter on.
-endtime=<DateTime>	End time of log snooping. Format: year-month-day [HH:MM:SS].
-event=<String>	Log event to filter on.
-ipproto={TCP UDP ICMP <String>}	Protocol to filter on.
-logid=<Integer>	Numeric log ID to filter on.
-num=<Integer>	Total log limit, number of logs.
-off	Stop log session.
-on	Start log session.
-pattern=<String>	Free text filter supporting wildcards.
-rate=<Integer>	Rate limit, logs/sec. Only applicable for real time logs.
-severity={EMERGENCY ALERT CRITICAL ERROR WARNING NOTICE INFO DEBUG}	Log severity to filter on. Equal or higher severity matches.
-source={MEMLOG REALTIME BOTH}	Log source. (Default: realtime)
-srcif=<Interface>	Source interface to filter on.
-srcip=<IPAddress>	Source IP address or network to filter on.
-srcport=<0...65535>	Source port to filter on.
-starttime=<DateTime>	Start time of log snooping. Format: year-month-day [HH:MM:SS].

**Note**

Requires Administrator privileges.

2.4.5. ls

Lists device data accessible by SCP.

Description

Lists device data which are available through SCP.

Example 2.24. Transfer script files to and from the device

```
Upload: scp myscript user@sgw-ip:script/myscript
```

```
Download: scp user@sgw-ip:script/myscript ./myscript
```

In addition to the files listed it is possible to upload license, certificates and ssh public key files.

Example 2.25. Upload license data

```
scp licence.lic user@sgw-ip:license.lic
```

Certificates and ssh client key objects are created if they do not exist.

Example 2.26. Upload certificate data

```
scp certificate.cer user@sgw-ip:certificate/certificate_name
scp certificate.key user@sgw-ip:certificate/certificate_name
```

Example 2.27. Upload ssh public key data

```
scp sshkey.pub user@sgw-ip:sshclientkey/sshclientkey_name
```

Usage

Options

-long	Enable long listing format.
<File>	File to list.

2.4.6. script

Handle CLI scripts.

Description

Run, create, show, store of delete script files.

Script files are transferred to and from the device by the SCP protocol. On the device they are stored in the "/script" folder.

Example 2.28. Execute script

```
"script.sgs":
add IP4Address Name=$1 Address=$2 Comment="$0: \$100".
:/> script -execute -name=script.sgs ip_test 127.0.0.1
is executed as line:
add IP4Address Name=ip_test Address=127.0.0.1 Comment="script.sgs: $100"
```

Usage

```
script -create [[<Category>] <Type> [<Identifier>]] [-name=<Name>]
```

Create configuration script from specified object, class or category.

```
script -execute [-verbose] [-force] [-quiet] -name=<Name>
[<Parameters>]...
```

Execute script.

```
script -show [-all] [-name=<Name>]
```

Show script in console window.

```
script -store [-all] [-name=<Name>]
```

Store a script to persistent storage.

```
script -remove [-all] [-name=<Name>]
```

Remove script.

```
script
```

List script files.

Options

-all	Apply to all scripts.
-create	Create configuration script from specified object, class or category.
-execute	Execute script.
-force	Force script execution.
-name=<Name>	Name of script.
-quiet	Quiet script execution.
-remove	Remove script.
-show	Show script in console window.
-store	Store a script to persistent storage.
-verbose	Verbose mode.
<Category>	Category that groups object types.

<Identifier>	The property that identifies the configuration object. May not be applicable depending on the specified <Type>.
<Parameters>	List of input arguments.
<Type>	Type of configuration object to perform operation on.



Note

Requires Administrator privileges.

Chapter 3: Configuration Reference

- Access, page 98
- Address, page 100
- AdvancedScheduleProfile, page 104
- ALG, page 105
- AntiVirusPolicy, page 114
- AppControlSettings, page 115
- ApplicationRuleSet, page 116
- ARPND, page 118
- ARPNDSettings, page 119
- AuthAgent, page 122
- AuthenticationSettings, page 123
- BlacklistWhiteHost, page 124
- BNE2EthernetPCIDriver, page 125
- BroadcomEthernetPCIDriver, page 126
- Certificate, page 127
- COMPortDevice, page 128
- ConfigModePool, page 129
- ConnTimeoutSettings, page 130
- DateTime, page 131
- DefaultInterface, page 132
- Device, page 133
- DHCPRelay, page 134
- DHCPRelaySettings, page 136

- DHCPServer, page 137
- DHCPServerSettings, page 140
- DHCPv6Server, page 141
- DHCPv6ServerSettings, page 143
- DiagnosticsSettings, page 144
- DNS, page 145
- DynamicRoutingRule, page 146
- DynDnsClientCjbNet, page 149
- DynDnsClientDyndnsOrg, page 150
- DynDnsClientDynsCx, page 151
- DynDnsClientPeanutHull, page 152
- E1000EthernetPCIDriver, page 153
- E100EthernetPCIDriver, page 154
- Ethernet, page 155
- EthernetDevice, page 157
- EthernetSettings, page 158
- EventReceiverSNMP2c, page 160
- FileControlPolicy, page 161
- FragSettings, page 162
- GRE Tunnel, page 164
- HighAvailability, page 165
- HTTPALGBanners, page 166
- HTTPAuthBanners, page 167
- HTTPPoster, page 168
- HWM, page 169
- HWMSettings, page 170
- ICMPSettings, page 171
- IDList, page 172
- IDPRule, page 173
- IGMPRule, page 175
- IGMPSetting, page 177
- IKEAlgorithms, page 178

- InterfaceGroup, page 180
- IP6in4Tunnel, page 181
- IPPolicy, page 182
- IPPool, page 185
- IPRule, page 186
- IPRuleFolder, page 189
- IPRuleSet, page 190
- IPsecAlgorithms, page 191
- IPsecTunnel, page 193
- IPsecTunnelSettings, page 196
- IPSettings, page 198
- ixgbeEthernetPCIDriver, page 201
- IXP4NPEEthernetDriver, page 202
- L2TPClient, page 203
- L2TPServer, page 205
- L2TPServerSettings, page 207
- L2TPv3Client, page 208
- L2TPv3Server, page 209
- LDAPDatabase, page 210
- LDAPServer, page 211
- LengthLimSettings, page 212
- LinkAggregation, page 213
- LinkMonitor, page 215
- LocalReassSettings, page 216
- LocalUserDatabase, page 217
- LogReceiverFWLog, page 218
- LogReceiverMemory, page 219
- LogReceiverSyslog, page 220
- LogSettings, page 221
- LoopbackInterface, page 222
- MarvellEthernetPCIDriver, page 223
- MiscSettings, page 224

- MulticastSettings, page 226
- NATPool, page 227
- OSPFProcess, page 228
- Pipe, page 233
- PipeRule, page 236
- PPPoETunnel, page 237
- PPPSettings, page 239
- PSK, page 240
- R8139EthernetPCIDriver, page 241
- R8169EthernetPCIDriver, page 242
- RadiusAccounting, page 243
- RadiusRelay, page 244
- RadiusServer, page 246
- RealTimeMonitorAlert, page 247
- RemoteIDList, page 248
- RemoteMgmtHTTP, page 249
- RemoteMgmtNetcon, page 250
- RemoteMgmtSettings, page 251
- RemoteMgmtSNMP, page 253
- RemoteMgmtSSH, page 254
- RouteBalancingInstance, page 256
- RouteBalancingSpilloverSettings, page 257
- RouterAdvertisement, page 258
- RoutingRule, page 260
- RoutingSettings, page 261
- RoutingTable, page 263
- ScheduleProfile, page 267
- ServiceGroup, page 268
- ServiceICMP, page 269
- ServiceICMPv6, page 271
- ServiceIPProto, page 273
- ServiceTCPUDP, page 274

- SSHClientKey, page 275
- SSLSettings, page 276
- SSLVPNInterface, page 277
- SSLVPNInterfaceSettings, page 278
- ST201EthernetPCIDriver, page 279
- StateSettings, page 280
- TCPSettings, page 281
- ThresholdRule, page 283
- TulipEthernetPCIDriver, page 285
- UpdateCenter, page 286
- URLFilterPolicy, page 287
- UserAuthRule, page 288
- VLAN, page 291
- VLANSettings, page 293
- WebContentFilteringPolicy, page 294
- X3C905EthernetPCIDriver, page 295

3.1. Access

Description

Use an access rule to allow or block specific source IP addresses on a specific interface.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the object.
Action	Accept, Expect or Drop. (Default: Drop)
Interface	The interface the packet must arrive on for this rule to be carried out. Exception: the Expect rule.
Network	The IP span that the sender must belong to for this rule to be carried out.
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.2. Address

This is a category that groups the following object types.

3.2.1. AddressFolder

Description

An address folder can be used to group related address objects for better overview.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Comments	Text describing the current object. (Optional)

3.2.1.1. IP6Address

Description

Use an IP6 Address item to define a name for a specific IP6 host, network or range.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Address	IPv6 address, e.g. "2001:DB8::/32".
ActiveAddress	The dynamically set address used by e.g. DHCPv6 enabled Ethernet interfaces. (Optional)
Comments	Text describing the current object. (Optional)

3.2.1.2. IP6Group

Description

An IP6 Address Group is used for combining several IP6 Address objects for simplified management.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Members	Group members.
Comments	Text describing the current object. (Optional)

3.2.1.3. EthernetAddress

Description

Use an Ethernet Address item to define a symbolic name for an Ethernet MAC address.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Address	Ethernet MAC address, e.g. "12-34-56-78-ab-cd".
Comments	Text describing the current object. (Optional)

3.2.1.4. EthernetAddressGroup

Description

An Ethernet Address Group is used for combining several Ethernet Address objects for simplified management.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Members	Group members.
Comments	Text describing the current object. (Optional)

3.2.1.5. IP4HAAddress

Description

Use an IP4 HA Address item to define a name for a specific IP4 host, network or range for each node in a high availability cluster.

Properties

Name	Specifies a symbolic name for the network object. (Identifier)
Address	An IP address with one instance for each node in the high availability cluster.
UserAuthGroups	Groups and user names that belong to this object. Objects that filter on credentials can only be used as source networks and destinations networks in rules. (Optional)
NoDefinedCredentials	If this property is enabled the object requires user

authentication, but has no credentials (user names or groups) defined. This means that the object only requires that a user is authenticated, but ignores any kind of group membership. (Default: No)

Comments Text describing the current object. (Optional)

3.2.1.6. IP4Group

Description

An IP4 Address Group is used for combining several IP4 Address objects for simplified management.

Properties

Name Specifies a symbolic name for the network object. (Identifier)

Members Group members.

UserAuthGroups Groups and user names that belong to this object. Objects that filter on credentials can only be used as source networks and destinations networks in rules. (Optional)

NoDefinedCredentials If this property is enabled the object requires user authentication, but has no credentials (user names or groups) defined. This means that the object only requires that a user is authenticated, but ignores any kind of group membership. (Default: No)

Comments Text describing the current object. (Optional)

3.2.1.7. IP4Address

Description

Use an IP4 Address item to define a name for a specific IP4 host, network or range.

Properties

Name Specifies a symbolic name for the network object. (Identifier)

Address IP address, e.g. "172.16.50.8", "192.168.7.0/24" or "172.16.25.10-172.16.25.50".

ActiveAddress The dynamically set address used by e.g. DHCP enabled Ethernet interfaces. (Optional)

UserAuthGroups Groups and user names that belong to this object. Objects that filter on credentials can only be used as source networks and destinations networks in rules. (Optional)

NoDefinedCredentials	If this property is enabled the object requires user authentication, but has no credentials (user names or groups) defined. This means that the object only requires that a user is authenticated, but ignores any kind of group membership. (Default: No)
Comments	Text describing the current object. (Optional)

3.2.2. EthernetAddress

The definitions here are the same as in Section 3.2.1.3, "EthernetAddress" .

3.2.3. EthernetAddressGroup

The definitions here are the same as in Section 3.2.1.4, "EthernetAddressGroup" .

3.2.4. IP4Address

The definitions here are the same as in Section 3.2.1.7, "IP4Address" .

3.2.5. IP4Group

The definitions here are the same as in Section 3.2.1.6, "IP4Group" .

3.2.6. IP4HAddress

The definitions here are the same as in Section 3.2.1.5, "IP4HAddress" .

3.2.7. IP6Address

The definitions here are the same as in Section 3.2.1.1, "IP6Address" .

3.2.8. IP6Group

The definitions here are the same as in Section 3.2.1.2, "IP6Group" .

3.3. AdvancedScheduleProfile

Description

An advanced schedule profile contains definitions of occurrences used by various policies in the system.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
Comments	Text describing the current object. (Optional)

3.3.1. AdvancedScheduleOccurrence

Description

An advanced schedule occurrence specifies an occurrence that should happen between certain times for days in month/week

Properties

StartTime	Start Time of occurrence in the format HH:MM. For example 13:30.
EndTime	End Time of occurrence in the format HH:MM. For example 14:15.
Occurrence	Specify type of occurrence. (Default: Weekly)
Weekly	Specifies days in week the schedule occurrence should be activated. Monday corresponds to 1 and Sunday 7. (Default: 1-7)
Monthly	Specifies days in month the schedule occurrence should be activated. The schedule only occurs at days that exists in the month. (Default: 1-31)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.4. ALG

This is a category that groups the following object types.

3.4.1. ALG_FTP

Description

Use an FTP Application Layer Gateway to manage FTP traffic through the system.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
AllowServerPassive	Allow server to use passive mode (unsafe for server). (Default: No)
ServerPorts	Server data ports. (Default: 1024-65535)
AllowClientActive	Allow client to use active mode (unsafe for client). (Default: No)
ClientPorts	Client data ports. (Default: 1024-65535)
AllowUnknownCommands	Allow unknown commands. (Default: No)
AllowSITEEXEC	Allow SITE EXEC. (Default: No)
MaxLineLength	Maximum line length in control channel. (Default: 256)
MaxCommandRate	Maximum number of commands per second. (Default: 20)
Allow8BitStrings	Allow 8-bit strings in control channel. (Default: Yes)
AllowResumeTransfer	Allow RESUME even in case of content scanning. (Default: No)
Antivirus	Disabled, Audit or Protect. (Default: Disabled)
ScanExclude	List of files to exclude from antivirus scanning. (Optional)
CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
ZDEnabled	Enable ZoneDefense Block. (Default: No)
ZDNetwork	Hosts within this network will be blocked at

	switches if a virus is found.
FileListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)
File	List of file types to allow or deny. (Optional)
VerifyContentMimetype	Verify that file extensions correspond to the MIME type. (Default: No)
Comments	Text describing the current object. (Optional)

3.4.2. ALG_H323

Description

Use an H.323 Application Layer Gateway to manage H.323 multimedia traffic.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
AllowTCPDataChannels	Allow TCP data channels (T.120). (Default: Yes)
MaxTCPDataChannels	Maximum number of TCP data channels per call. (Default: 10)
TranslateAddresses	Automatic or Specific. (Default: Automatic)
TranslateLogicalChannelAddresses	Translate logical channel addresses. (Default: Yes)
MaxGKRegLifeTime	Max Gatekeeper Registration Lifetime. (Default: 1800)
Comments	Text describing the current object. (Optional)

3.4.3. ALG_HTTP

Description

Use an HTTP Application Layer Gateway to filter HTTP traffic.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
AllowedProtocols	HTTP and/or HTTPS. (Default: HTTP)
RemoveCookies	Remove cookies. (Default: No)
RemoveScripts	Remove Javascript/VBScript. (Default: No)

RemoveApplets	Remove Java applets. (Default: No)
RemoveActiveX	Remove ActiveX objects (including Flash). (Default: No)
ForceSafeSearch	Force SafeSearch on Google, Bing and Yahoo! search engines. (Default: No)
VerifyUTF8URL	Verify that URLs does not contain invalid UTF8 encoding. (Default: No)
BlackURLDisplayReason	Message to show when there is an attempt to access a blacklisted site. (Optional)
HTTPBanners	HTTP ALG HTML Banners. (Default: Default)
MaxDownloadSize	The maximal allowed file size in kB. (Optional)
FileListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)
File	List of file types to allow or deny. (Optional)
VerifyContentMimetype	Verify that file extentions correspond to the MIME type. (Default: No)
Antivirus	Disabled, Audit or Protect. (Default: Disabled)
ScanExclude	List of files to exclude from antivirus scanning. (Optional)
CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
ZDEnabled	Enable ZoneDefense Block. (Default: No)
ZDNetwork	Hosts within this network will be blocked at switches if a virus is found.
WebContentFilteringMode	Disabled, Audit or Enable. (Default: Disabled)
FilteringCategories	Web content categories to block. (Optional)
NonManagedAction	Action to take for content that hasn't been classified. (Default: Allow)
AllowFilteringOverride	Allow the user to display a blocked site. (Default: No)
OverrideUpdateOnAccess	Restart the override timer on each new access to

	disallowed categories. (Default: Yes)
OverrideTimeToLive	Seconds that all disallowed categories will be allowed for the host that requested the override. (Default: 300)
AllowFilteringReclassification	Allow reclassification of sites. (Default: No)
Comments	Text describing the current object. (Optional)

3.4.3.1. ALG_HTTP_URL

Description

Blacklist URLs to deny access to complete sites, to file types by extension, or to URLs with certain words in them.

Properties

Action	Whitelist or Blacklist. (Default: Blacklist)
URL	Specifies the URL to blacklist or whitelist.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.4.4. ALG_POP3

Description

Use an POP3 Application Layer Gateway to manage POP3 traffic through the system.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
BlockUserPass	Block clients from sending USER and PASS command. (Default: No)
HideUser	Prevent server from revealing that a user name do not exist. (Default: No)
AllowUnknownCommands	Allow unknown commands. (Default: No)
FileListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)

File	List of file types to allow or deny. (Optional)
VerifyContentMimetype	Verify that file extensions correspond to the MIME type. (Default: No)
Antivirus	Disabled, Audit or Protect. (Default: Disabled)
ScanExclude	List of files to exclude from antivirus scanning. (Optional)
CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
ZDEnabled	Enable ZoneDefense Block. (Default: No)
ZDNetwork	Hosts within this network will be blocked at switches if a virus is found.
Comments	Text describing the current object. (Optional)

3.4.5. ALG_PPTP

Description

Use a PPTP Application Layer Gateway to manage PPTP traffic through the system.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
EchoTimeout	Specifies idle timeout for Echo messages in the PPTP tunnel. (Default: 0)
IdleTimeout	Specifies idle timeout for user traffic in the PPTP tunnel. (Default: 0)
Comments	Text describing the current object. (Optional)

3.4.6. ALG_SIP

Description

Use a SIP ALG to manage SIP based multimedia sessions.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
MaxSessionsPerId	Maximum number of sessions per SIP URI. (Default: 5)
MaxRegistrationTime	The maximum allowed time in seconds between registration requests. (Default: 3600)
SipSignalTmout	Timeout value for last seen SIP message (in seconds). (Default: 43200)
DataChannelTmout	Timeout value for data channel (in seconds). (Default: 120)
AllowMediaByPass	Allow clients to exchange media directly when possible. (Default: Yes)
AllowTCPDataChannels	Allow TCP data channels. (Default: Yes)
MaxTCPDataChannels	Maximum number of TCP data channels per call. (Default: 5)
Comments	Text describing the current object. (Optional)

3.4.7. ALG_SMTTP

Description

Use an SMTP Application Layer Gateway to manage SMTP traffic through the system.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
VerifySenderEmail	Check emails for mismatching SMTP command From address and email header From address. (Default: No)
VerifySenderEmailAction	...and block them. (Default: Deny)
VerifySenderEmailSpamTag	Spam Tag that is inserted into the subject. (Default: "**** SPAM ****")
VerifySenderEmailDomainOnly	Only check domain names in email From addresses. (Default: No)
MaxEmailPerMinute	Specifies the maximum amount of emails per minute from the same host. (Optional)
MaxEmailSize	Specifies the maximum allowed email size in kB. (Optional)
FileListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)
File	List of file types to allow or deny. (Optional)

VerifyContentMimetype	Verify that file extensions correspond to the MIME type. (Default: No)
Antivirus	Disabled, Audit or Protect. (Default: Disabled)
ScanExclude	List of files to exclude from antivirus scanning. (Optional)
CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
ZDEnabled	Enable ZoneDefense Block. (Default: No)
ZDNetwork	Hosts within this network will be blocked at switches if a virus is found.
DNSBL	Disable or Enable DNSBL. (Default: No)
SpamThreshold	Spam Threshold defines when an email should be considered as Spam. (Default: 10)
DropThreshold	Drop Threshold defines when an email should be considered malicious and be dropped. (Default: 20)
SpamTag	Spam Tag that is inserted into the subject for an email considered as Spam or malicious. (Default: "**** SPAM ****")
ForwardBlockedMail	Forward blocked mails to DropAddress. (Default: No)
DropAddress	Email address that emails reaching the drop threshold will be rerouted to.
AppendTXT	Use TXT records (will only be used if reaching the drop threshold). (Default: No)
CacheSize	Size of the IP Cache of checked sender IP addresses. (Default: 0)
CacheTimeout	Timeout in seconds before a cached IP address is removed. (Default: 600)
DNSBlackLists	Specifies the BlackList domain and its weighted value.
Comments	Text describing the current object. (Optional)

3.4.7.1. ALG_SMTTP_Email

Description

Used to whitelist or blacklist an email sender/recipient.

Properties

Type	Specifies if the email address is the sender or the recipient. (Default: Sender)
Action	Specifies whether to whitelist (allow) or blacklist (deny) this address. (Default: Blacklist)
Email	Specifies the recipient email to blacklist or whitelist.
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.4.8. ALG_TFTP**Description**

Use an TFTP Application Layer Gateway to manage TFTP traffic through the system.

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
AllowedCommands	Specifies allowed commands. (Default: ReadWrite)
RemoveOptions	Remove option part from request packet. (Default: No)
AllowUnknownOptions	Allow unknown options in request packet. (Default: No)
MaxBlocksize	Max value for the blksize option. (Optional)
MaxFileTransferSize	Max size for transferred file. (Optional)
BlockDirectoryTraversal	Prevent directory traversal (consecutive dots in filenames). (Default: No)
Comments	Text describing the current object. (Optional)

3.4.9. ALG_TLS**Description**

TLS Alg

Properties

Name	Specifies a symbolic name for the ALG. (Identifier)
HostCert	Specifies the host certificate.
RootCert	Specifies the root certificates. (Optional)
Comments	Text describing the current object. (Optional)

3.5. AntiVirusPolicy

Description

Add a Anti-Virus Profile that can be used by one or many IP Policies. The same Profile can be used on all protocols that support Anti-Virus scanning (HTTP, FTP, POP3 and SMTP).

Properties

Name	Specifies a symbolic name for the Profile. (Identifier)
AuditMode	Anti-Virus audit mode. (Default: No)
ScanExclude	List of files to exclude from antivirus scanning. (Optional)
CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
ZDEnabled	Enable ZoneDefense Block. (Default: No)
ZDNetwork	Hosts within this network will be blocked at switches if a virus is found.
Comments	Text describing the current object. (Optional)

3.6. AppControlSettings

Description

Settings related to the Application Control functionality.

Properties

MaxUnclassifiedPackets

Maximum number of packets in one direction on a connection before the application will be forced to unknown. (Default: 5)

MaxUnclassifiedBytes

Maximum number of bytes transfered in one direction on a connection before the application will be forced to unknown. (Default: 7500)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.7. ApplicationRuleSet

Description

An Application Rule Set contains a list of Application Rules and some settings and can be used by one or more IP rules/IP Policies to configure Application Control on the traffic matching those IP Rules/IP Policies.

Properties

Name	Specifies a symbolic name for the Profile. (Identifier)
DefaultAction	Default action if nothing in the rule list matches. (Default: Deny)
UseCustomLimits	Use custom limits for unclassified traffic in this ruleset instead of the default limits specified in the advanced settings. (Default: No)
MaxUnclassifiedPackets	Maximum number of packets in one direction on a connection before the application will be forced to unknown. (Default: 5)
MaxUnclassifiedBytes	Maximum number of bytes transferred in one direction on a connection before the application will be forced to unknown. (Default: 7500)
StrictHTTP	Handle plain http more strictly to avoid leaking generic http services when only specific http services should be allowed. (Default: Yes)
Comments	Text describing the current object. (Optional)

3.7.1. ApplicationRule

Description

An application rule specifies what action to perform on applications that matches the specified filter criteria.

Properties

Action	Action for matched application. (Default: Allow)
AppFilter	Application filter.
ApplicationContent	Extended logging and policy for application attributes. (Default: [])
UserAuthGroups	Groups and user names that belong to this object. (Optional)
ForwardChain	Specifies one or more pipes to be used for forward traffic. (Optional)

ReturnChain	Specifies one or more pipes to be used for return traffic. (Optional)
Precedence	Specifies what precedence should be assigned to the packets before sent into a pipe. (Default: FromPipe)
FixedPrecedence	Specifies the fixed precedence.
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.8. ARPND

Description

Use an ARP/Neighbor Discovery entry to publish additional IP addresses and/or MAC addresses on a specified interface.

Properties

Mode	Static, Publish or XPublish. (Default: Publish)
Interface	Indicates the interface to which the ARP entry applies; e.g. the interface the address shall be published on.
IP	The IP address to be published or statically bound to a hardware address.
MACAddress	The hardware address associated with the IP address. (Default: 00-00-00-00-00-00)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.9. ARPNDSettings

Description

Advanced ARP/Neighbor Discovery-table settings.

Properties

ARPMatchEnetSender	The Ethernet Sender address matching the hardware address in the ARP data. (Default: DropLog)
ARPQueryNoSenderIP	If the IP source address of an ARP query (NOT response!) is "0.0.0.0". (Default: DropLog)
ARPSenderIP	The IP Source address in ARP packets. (Default: Validate)
UnsolicitedARPReplies	Unsolicited ARP replies. (Default: DropLog)
ARPRequests	Specifies whether or not the ARP requests should automatically be added to the ARP table. (Default: Drop)
ARPChanges	ARP packets that would cause an entry to be changed. (Default: AcceptLog)
StaticARPChanges	ARP packets that would cause static entries to be changed. (Default: DropLog)
ARPExpire	Lifetime of an ARP entry in seconds. (Default: 900)
ARPExpireUnknown	Lifetime of an "unknown" ARP entry in seconds. (Default: 3)
ARPMulticast	ARP packets claiming to be multicast addresses; may need to be enabled for some load balancers/redundancy solutions. (Default: DropLog)
ARPBroadcast	ARP packets claiming to be broadcast addresses; should never need to be enabled. (Default: DropLog)
ARPCacheSize	Number of ARP entries in cache, total. (Default: 4096)
ARPHashSize	Number of ARP hash buckets per physical interface. (Default: 512)
ARPHashSizeVLAN	Number of ARP hash buckets per VLAN interface. (Default: 64)
ARPIPCollision	Behavior when receiving an ARP request with a sender IP colliding with the one used on the receive interface. (Default: Drop)
ARPLogResolveSuccess	Specifies whether or not to log when ARP Resolve succeeds. (Default: No)

LogResolveFailure	Specifies whether or not to log failed ARP Resolves. (Default: Yes)
NDRateLimit	Rate limit originated ND packets. (Default: 1000)
MaxAnycastDelayTime	Randomized time to delay proxied and anycast advertisements. (Default: 100)
NDMatchEnetSender	Ignore ND packets with mismatching sender- and options MAC-addresses. (Default: Yes)
NDValSenderIP	Validate the IP source address of the ND packet. (Default: Yes)
NDLogResolveSuccess	Specifies whether or not to log when ND Resolve succeeds. (Default: No)
NDChanges	Action to take when ND packets are received that would modify an existing entry. (Default: FavorOld)
StaticNDChanges	Action to take when ND packets are received that would modify a static entry. (Default: DropLog)
NDValidation	Action to take when the stateless validation of a ND packet fail. (Default: DropLog)
NDCacheSize	Number of cached IP/L2 address tuples. (Per iface). (Default: 1024)
NDMaxMulticastSolicit	Number of Neighbor Solicitations before giving up address resolution. (Default: 3)
NDMaxUnicastSolicit	Number of Neighbor Solicitations before giving up a zombie during dead peer detection. (Default: 3)
NDBaseReachableTime	Multiple of randomized time factor in seconds, resulting in the time before a ND entry becomes a zombie. (Default: 30)
NDDelayFirstProbeTime	Time in seconds for a cache entry to go from DELAY to PROBE state unless resolved. (Default: 5)
NDRetransTimer	Number of seconds between each Neighbor Solicitation during address resolution and dead peer detection. (Default: 1)
RAMaxInterval	Maximum time between sending unsolicited multicast Router Advertisement. (Default: 600s). (Default: 600)
RAMinInterval	Minimum time between sending unsolicited multicast Router Advertisement. Will be automatically adjusted if set to less than 3 seconds or greater than $.75 * \text{Max RA Interval}$. (Default: 200)
RAAutoLifetime	Auto adjust the Router Lifetime field using the following formula; $3 * \text{Max RA Interval}$. (Default: Yes)
RADefaultLifetime	The value to be placed in the Router Lifetime field of Router Advertisements sent from the SGW, in seconds. (Default: 1800s). (Default: 1800)

RAReachableTime	The value to be placed in the Reachable Time field in the Router Advertisement messages SGW. The value zero means unspecified. (Default: 0s). (Default: 0)
RARetransTimer	The value to be placed in the Retrans Timer field in the Router Advertisement messages sent by the SGW. The value zero means unspecified. (Default: 0s). (Default: 0)
RAManagedFlag	Indicates that addresses are available via DHCPv6. (Default: False). (Default: No)
RAOtherConfigFlag	Indicates that other configuration information is available via DHCPv6. (Default: False). (Default: No)
RACurHopLimit	The default value to be placed in the Cur Hop Limit field in the Router Advertisement messages sent by the SGW. The value zero means unspecified. (Default: 64). (Default: 64)
RALinkMTU	The value to be placed in MTU options sent. A value of zero indicates that no MTU options are sent. (Default: 0). (Default: 0)
RAValidLifetime	The value to be placed in the Valid Lifetime in the Prefix Information option. The value of 999999999 represents infinity. (Default: 2592000s). (Default: 2592000)
RAPreferredLifetime	The value to be placed in the Preferred Lifetime in the Prefix Information option. The value of 999999999 represents infinity. (Default: 604800s). (Default: 604800)
RAOnLinkFlag	Indicates that the advertised prefix can be used for on-link determination. (Default: True). (Default: Yes)
RAAutonomousFlag	Indicates that the advertised prefix can be used for stateless address configuration. (Default: True). (Default: Yes)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.10. AuthAgent

Description

The Authentication Agent collect user login and logout events on a network domain controller.

Properties

Name	Specifies a symbolic name for the agent.
IPAddress	The IP address of the agent.
Port	The listening port of the agent. (Default: 9999)
PSK	Selects the Pre-shared key to use with this agent. (Default: auth_agent_psk)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.11. AuthenticationSettings

Description

Settings related to Authentication and Accounting.

Properties

LogoutAccUsersAtShutdown	Logout authenticated accounting users and send AccountingStop packets prior to shutdown. (Default: Yes)
AllowAuthIfNoAccountingResponse	Allow an authenticated user to still have access even if no response is received by the Accounting Server. (Default: Yes)
LogALGUser	Log authenticated user together with URL in ALG log messages. (Default: Yes)
LogConnUser	Include authenticated user name in CONN logs. (Default: Yes)
MaxRADIUSContexts	Maximum number of RADIUS communication contexts. (Default: 1024)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.12. BlacklistWhiteHost

Description

Hosts and networks added to this whitelist can never be blacklisted by IDP or Threshold Rules.

Properties

Addresses	Specifies the addresses that will be whitelisted.
Service	Specifies the service that will be whitelisted.
Schedule	The schedule when the whitelist should be active. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.13. BNE2EthernetPCIDriver

Description

Broadcom NE2 Gigabit Ethernet.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.14. BroadcomEthernetPCIDriver

Description

Broadcom NE Gigabit Ethernet.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.15. Certificate

Description

An X. 509 certificate is used to authenticate a VPN client or gateway when establishing an IPsec tunnel.

Properties

Name	Specifies a symbolic name for the certificate. (Identifier)
Type	Local, Remote or Request.
CertificateData	Certificate data.
PrivateKey	Private key.
NoCRLs	Disable CRLs (Certificate Revocation Lists). (Default: No)
PKAType	Encryption algorithm of the public key. (Default: Unknown)
Comments	Text describing the current object. (Optional)

3.16. COMPortDevice

Description

A serial communication port, that is used for accessing the CLI.

Properties

Port	Port. (Identifier)
BitsPerSecond	Bits per second. (Default: 9600)
DataBits	Data bits. (Default: 8)
Parity	Parity. (Default: None)
StopBits	Stop bits. (Default: 1)
FlowControl	Flow control. (Default: None)
Comments	Text describing the current object. (Optional)

3.17. ConfigModePool

Description

An IKE Config Mode Pool will dynamically assign the IP address, DNS server, WINS server etc. to the VPN client connecting to this gateway.

Properties

IPPoolType	Specifies whether a predefined IP Pool or a static set of IP addresses should be used as IP address source.
IPPool	Specifies the IP pool to use for assigning IP addresses to VPN clients.
IPPoolAddress	Specifies the set of IP addresses to use for assigning IP addresses to VPN clients.
IPPoolNetmask	Specifies the netmask to assign to VPN clients.
DNS	Specifies the IP address of a DNS server that a VPN client should be able to connect to. (Optional)
NBNSIP	Specifies the IP address of a NBNS/WINS server that a VPN client should be able to connect to. (Optional)
DHCP	Specifies the IP address of a DHCP that that a VPN client should be able to connect to. (Optional)
Subnets	Specifies additional subnets behind this gateway. (Optional)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.18. ConnTimeoutSettings

Description

Timeout settings for various protocols.

Properties

ConnLife_TCP_SYN	Connection idle lifetime for TCP connections being formed. (Default: 60)
ConnLife_TCP	Connection idle lifetime for TCP. (Default: 262144)
ConnLife_TCP_FIN	Connection idle lifetime for TCP connections being closed. (Default: 80)
ConnLife_UDP	Connection idle lifetime for UDP. (Default: 130)
AllowBothSidesToKeepConnAlive_UDP	Allow both sides to keep a UDP connection alive. (Default: No)
ConnLife_Ping	Connection timeout for Ping. (Default: 8)
ConnLife_Other	Idle lifetime for other protocols. (Default: 130)
ConnLife_IGMP	Connection idle lifetime for IGMP. (Default: 12)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.19. DateTime

Description

Set the date, time and time zone information for this system.

Properties

TimeZone	Specifies the time zone. (Default: GMT)
DSTEnabled	Enable daylight saving time. (Default: Yes)
DSTOffset	Daylight saving time offset in minutes. (Default: 60)
DSTStartMonth	What month daylight saving time starts. (Default: March)
DSTStartDay	What day of month daylight saving time starts. (Default: 1)
DSTEndMonth	What month daylight saving time ends. (Default: October)
DSTEndDay	What day of month daylight saving time ends. (Default: 1)
TimeSyncEnable	Enable time synchronization. (Default: No)
TimeSyncServerType	Type of server for time synchronization, UDPTIME or SNTP (Simple Network Time Protocol). (Default: SNTP)
TimeSyncServer1	DNS hostname or IP Address of Timeserver 1.
TimeSyncServer2	DNS hostname or IP Address of Timeserver 2. (Optional)
TimeSyncServer3	DNS hostname or IP Address of Timeserver 3. (Optional)
TimeSyncInterval	Seconds between each resynchronization. (Default: 86400)
TimeSyncMaxAdjust	Maximum time drift in seconds that a server is allowed to adjust. (Default: 600)
TimeSyncGroupIntervalSize	Interval according to which server responses will be grouped. (Default: 10)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.20. DefaultInterface

Description

A special interface used to represent internal mechanisms in the system as well as an abstract "any" interface.

Properties

Name Specifies a symbolic name for the interface. (Identifier)

Comments Text describing the current object. (Optional)

3.21. Device

Description

Global parameters for this device.

Properties

Name	Name of the device. (Default: Device)
LocalCfgVersion	Local version number of the configuration. (Default: 1)
RemoteCfgVersion	Remote version number of the configuration. (Default: 0)
ConfigUser	Name of the user who committed the current configuration. (Default: BaseConfiguration)
ConfigSession	Session type used when the current configuration was committed. (Default: BaseConfiguration)
ConfigIP	IP address of the user who committed the current configuration. (Optional)
ConfigDate	Date when the current configuration was committed. (Optional)
HWModel	System hardware model. (Default: SOFTWARE)
DeviceID	Device identification string. (Optional)
RegistrationKey	System registration key. (Optional)
ProductionDate	Device production date. (Optional)
HWSerial	Device hardware serial number. (Optional)
ServiceTag	Service Tag. (Optional)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.22. DHCPRelay

Description

Use a DHCP Relay to dynamically alter the routing table according to relayed DHCP leases.

Properties

Name	Specifies a symbolic name for the relay rule. (Identifier)
Action	Ignore, Relay or BootpFwd. (Default: Ignore)
SourceInterface	The source interface of the DHCP packet.
TargetDHCPserver	Specifies the IP of the server to send the relayed DHCP packets to.
TargetDHCPserver2	Optional secondary server. (Optional)
TargetDHCPserver3	Optional tertiary server. (Optional)
IPOfferFilter	Specifies the span of IP addresses that are allowed to be relayed from the DHCP server. (Default: 1)
AddRoute	Enable dynamic adding of routes as leases are added and removed. (Default: No)
AddRouteLocalIP	The IP Address specified here will automatically be published on the interfaces where a route is added. (Optional)
AddRouteGatewayIP	The IP used as gateway to reach hosts on this route. (Optional)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
MaxRelaysPerInterface	Specifies how many relays are allowed per interface, that means, how many DHCP clients are allowed to be relayed through each interface. (Optional)
AgentIP	Define what IP the relay should use as gateway IP when passing the requests to the DHCP server. (Default: Recv)
AllowNULLOffers	Accept server responses offering IP address "0.0.0.0" (no IP address offered). (Default: No)
ProxyARPAAllInterfaces	Always select all interfaces, including new ones, for publishing routes needed for the relay via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interface/interfaces on which the security gateway should publish routes needed for the relay via Proxy ARP. (Optional)
LogEnabled	Enable logging. (Default: Yes)

LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

3.23. DHCPRelaySettings

Description

Advanced DHCP relay settings.

Properties

MaxTransactions	Maximum number of concurrent BOOTP/DHCP transactions. (Default: 32)
TransactionTimeout	Timeout for each transaction (in seconds). (Default: 10)
MaxPPMPerIface	Maximum packets per minute that are relayed from clients to the server, per interface. (Default: 500)
MaxHops	Requests/responses that have traversed more than this many relays will not be relayed. (Default: 5)
MaxLeaseTime	Maximum lease time (seconds) allowed from the DHCP server (too high times will be lowered silently). (Default: 10000)
MaxAutoRoutes	Maximum number of DHCP client IPs automatically added to the routing table. (Default: 256)
AutoSaveRelayPolicy	Policy for saving the relay list to disk. (Default: ReconfShut)
AutoSaveRelayInterval	Seconds between auto saving the relay list to disk. (Default: 86400)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.24. DHCP Server

Description

A DHCP Server determines a set of IP addresses and host configuration parameters to hand out to DHCP clients attached to a given interface.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the DHCP Server rule. (Identifier)
Interface	The source interface to listen for DHCP requests on. This can be a single interface or a group of interfaces.
RelayerFilter	A range, group or network that will allow specific DHCP Relayers access to the DHCP Server. (Default: 0/0)
IPAddressPool	A range, group or network that the DHCP Server will use as IP address pool to give out DHCP leases from.
Netmask	Netmask sent to the DHCP Client. (Default: 255)
DefaultGateway	Specifies what IP should be sent to the client for use as default gateway. If unspecified or if 0.0.0.0 is specified, the IP given to the client will be sent as gateway. (Optional)
Domain	Domain name used for DNS resolution. (Optional)
LeaseTime	The time, in seconds, that a DHCP lease should be provided to a host after this the client have to renew the lease. (Default: 86400)
DNS1	IP of the primary DNS server. (Optional)
DNS2	IP of the secondary DNS server. (Optional)
NBNS1	IP of the primary Windows Internet Name Service (WINS) server that is used in Microsoft environments which uses the NetBIOS Name Servers (NBNS) to assign IP addresses to NetBIOS names. (Optional)
NBNS2	IP of the primary Windows Internet Name Service (WINS) server that is used in Microsoft environments which uses the NetBIOS Name Servers (NBNS) to assign IP addresses to NetBIOS names. (Optional)
LeasesRequireAuth	Enable distribution of leases only after clients have been authenticated. (Default: No)
NextServer	IP address of next server in the boot process.

	(Optional)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

3.24.1. DHCPStaticHost

Description

Static DHCP Server host entry

Properties

Host	IP Address of the host.
StaticHostType	Identifier for host. (Default: MACAddress)
MACAddress	The hardware address of the host.
ClientIdentType	Type of client identifier specified. (Default: Ascii)
ClientIdent	The client identifier for the host.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.24.2. DHCPServerCustomOption

Description

Extend the DHCP Server functionality by adding custom options that will be handed out to the DHCP clients.

Properties

Code	The DHCP option code.
Type	What type the option is, i.e. STRING, IP4 and so on. (Default: UINT8)
Param	The parameter sent with the code, this can be one parameter or a comma separated list.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.25. DHCP Server Settings

Description

Advanced DHCP server settings.

Properties

AutoSaveLeasePolicy	Policy for saving the lease database to disk. (Default: ReconfShut)
AutoSaveLeaseInterval	Seconds between auto saving the lease database to disk. (Default: 86400)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.26. DHCPv6Server

Description

A DHCPv6 Server determines a set of IPv6 addresses and host configuration parameters to hand out to DHCPv6 clients attached to a given interface.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the DHCPv6 Server rule. (Identifier)
Interface	The source interface to listen for DHCPv6 requests on. This can be a single interface or a group of interfaces.
IPv6AddressPool	A range, group or network that the DHCP Server will use as IPv6 address pool to give out DHCPv6 leases from.
Domain	Domain name used for DNS resolution. (Optional)
ValidLeaseTime	The length of time in seconds that an address remains valid for sending and receiving packets. When expired, the host is not allowed to use the provided address any more and should acquire a new one. (Default: 86400)
PreferredLeaseTime	The length of time in seconds that an address should be preferred to be used in new communications. When expired, unless renewed, the address becomes deprecated and should no longer be used as a source address in new communications. (Default: 66400)
DNS1	IPv6 of the primary DNS server. (Optional)
DNS2	IPv6 of the secondary DNS server. (Optional)
SendUnicastOption	Enable sending of Unicast option to DHCPv6 client. (Default: No)
ClearUniversalLocalBit	Clear the universal/local bit in the IPv6 address pool in case of /64 networks. (Default: No)
RapidCommit	Enable respond with committed address assignments and other resources on Solicit request. (Default: No)
PreferenceConfigured	Enable Preference option sending in Advertise message. (Default: No)
PreferenceValue	Preference Option value. (Default: 0)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent

	to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

3.26.1. DHCPv6ServerPoolStaticHost

Description

Static DHCPv6 Server host entry

Properties

Host	IPv6 Address of the host.
MACAddress	The hardware address of the host.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.27. DHCPv6ServerSettings

Description

Advanced DHCPv6 server settings.

Properties

AutoSaveLeasePolicy	Policy for saving the lease database to disk. (Default: ReconfShut)
AutoSaveLeaseInterval	Seconds between auto saving the lease database to disk. (Default: 86400)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.28. DiagnosticsSettings

Description

Control how anonymous usage statistics are automatically shared with Clavister to improve the quality of the product and the services. Sensitive information e.g. VPN keys or certificates are not shared. All communication is encrypted and no information is shared with 3rd parties.

Properties

EnableDiagnostics	Allow anonymous diagnostics reports to be sent to Clavister. (Default: Yes)
IncludeUsageStatistics	Include usage statistics e.g. CPU load, connection count and memory usage to manufacturer. The information will improve the quality of future products and releases. (Default: Yes)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.29. DNS

Description

Configure the DNS (Domain Name System) client settings.

Properties

DNSServer1	IP of the primary DNS Server. (Optional)
DNSServer2	IP of the secondary DNS Server. (Optional)
DNSServer3	IP of the tertiary DNS Server. (Optional)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.30. DynamicRoutingRule

Description

A Dynamic Routing Policy rule creates a filter to catch statically configured or OSPF learned routes. The matched routes can be controlled by the action rules to be either exported to OSPF processes or to be added to one or more routing tables.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
From	OSPF or Routing table. (Default: OSPF)
OSPFProcess	Specifies from which OSPF process the route should be imported from into either a routing table or another OSPF process.
RoutingTable	Specifies from which routing table a route should be imported into the OSPF AS or copied into another routing table.
DestinationInterface	The interface that the policy has to match. (Optional)
DestinationNetworkExactly	Specifies if the route needs to match a specific network exactly. (Optional)
DestinationNetworkIn	Specifies if the route just needs to be within a specific network. (Optional)
NextHop	The next hop (router) on the route that this policy has to match. (Optional)
MetricRange	Specifies an interval that the metric of the routes needs to be within. (Optional)
RouterID	Specifies if the policy should filter on router ID. (Optional)
OSPFRouteType	Specifies if the policy should filter on OSPF router type. (Optional)
OSPFTagRange	Specifies an interval that the tag of the routers need to be within. (Optional)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed

last in the list and the `Index` will be equal to the length of the list.

3.30.1. DynamicRoutingRuleExportOSPF

Description

An OSPF action is used to manipulate and export new or changed routes to an OSPF Router Process.

Properties

ExportToProcess	Specifies to which OSPF Process the route change should be exported.
SetTag	Specifies a tag for this route. This tag can be used in other routers for filtering. (Optional)
SetRouteType	The external route type. (Optional)
OffsetMetric	Increases the metric of the imported route by this value. (Optional)
LimitMetricRange	Limits the metrics for these routes to a minimum and maximum value, if a route has a higher or lower value then specified it will be set to the specified value. (Optional)
SetForward	IP to route over. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.30.2. DynamicRoutingRuleAddRoute

Description

A routing action is used to manipulate and insert new or changed routes to one or more local routing tables.

Properties

Destination	Specifies to which routing table the route changes to the OSPF Process should be exported.
OverrideStatic	Allow override of static routes. (Default: No)
OverwriteDefault	Allow overwrite of default route. (Default: No)

OffsetMetric	Increases the metric by this value. (Optional)
OffsetMetricType2	Increases the for Type2 routers metric by this value. (Optional)
LimitMetricRange	Limits the metrics for these routes to a minimum and maximum value, if a route has a higher or lower value then specified it will be set to the specified value. (Optional)
ProxyARPAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.31. DynDnsClientCjbNet

Description

Configure the parameters used to connect to the Cjb.net DynDNS service.

Properties

Username	Username.
Password	The password for the specified username. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.32. DynDnsClientDyndnsOrg

Description

Configure the parameters used to connect to the dyndns.org DynDNS service.

Properties

DNSName	The DNS name excluding the .dyndns.org suffix.
Username	Username.
Password	The password for the specified username. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.33. DynDnsClientDynsCx

Description

Configure the parameters used to connect to the dyns.cx DynDNS service.

Properties

DNSName	The DNS name excluding the .dyns.cx suffix.
Username	Username.
Password	The password for the specified username. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.34. DynDnsClientPeanutHull

Description

Configure the parameters used to connect to the Peanut Hull DynDNS service.

Properties

DNSNames	Specifies the DNS names separated by ";".
Username	Username.
Password	The password for the specified username. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.35. E1000EthernetPCIDriver

Description

Intel (E1000) Gigabit Ethernet Adaptor.

Properties

RxRingsize	Rx ringsize. (Default: 64)
TxRingsize	Rx ringsize. (Default: 256)
EnableMonitoring	Enable monitoring. (Default: No)
BelowCPULoad	Below CPU load. (Default: 80)
BelowInterfaceLoad	Below interface load. (Default: 70)
MinInterval	Minimum interval. (Default: 30)
RxErrorPercentage	Rx error percentage. (Default: 20)
TxErrorPercentage	Tx error percentage. (Default: 7)
ErrorTime	Error time. (Default: 10)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.36. E100EthernetPCIDriver

Description

Intel (E100) Fast Ethernet Adaptor.

Properties

RxRingsize Rx ringsize. (Default: 32)

TxRingsize Tx ringsize. (Default: 128)

Comments Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.37. Ethernet

Description

An Ethernet interface represents a logical endpoint for Ethernet traffic.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
EthernetDevice	Hardware settings for the Ethernet interface.
VlanQoSInherit	Set whether VLANs using the interface should inherit the IP QoS bits. (Default: No)
ReceiveMulticastTraffic	Sets the multicast receive mode of the interface. (Default: Auto)
LACPPortPriority	Port priority value to be sent in LACP messages. (Default: 1)
IP	The IP address of the interface.
Network	The network of the interface.
DefaultGateway	The default gateway of the interface. (Optional)
Broadcast	The broadcast address of the connected network. (Optional)
EnableIPv6	Enable processing of IPv6 traffic on this interface. (Default: No)
IPv6IP	The IP address of the interface.
IPv6Network	The network of the interface.
IPv6DefaultGateway	The default gateway of the interface. (Optional)
PrivateIP	The private IP address of this high availability node. (Optional)
NOCHB	This will disable sending Cluster Heartbeats from this interface (used by HA to detect if a node is online and working). (Optional)
MTU	Specifies the size (in bytes) of the largest packet that can be passed onward. Must be 1294 or larger when IPv6 is enabled. (Default: 1500)
Metric	Specifies the metric for the auto-created route. (Default: 100)
DHCPEnabled	Enable DHCP client on this interface. (Default: No)
DHCPHostName	Optional DHCP Host Name. Leave blank to use default name. (Optional)
AutoSwitchRoute	Enable transparent mode, which means that a

	switch route is added automatically for this interface. (Default: No)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given network. (Default: Yes)
AutoDefaultGatewayRoute	Automatically add a default route for this interface using the given default gateway. (Default: Yes)
DHCPDNS1	IP of the primary DNS server. (Optional)
DHCPDNS2	IP of the secondary DNS server. (Optional)
DHCPPreferredIP	Set a preferred IP address which will be included in the request to the DHCP server. (Optional)
DHCPAllowStaticRoutes	Allow the use of static routes send from the DHCP server. (Default: No)
DHCPPreferredLeaseTime	Set a preferred lease time which will be included in the request to the DHCP server. (Optional)
DHCPLeaseFilter	Allowed IP address range(s) for the DHCP lease. (Optional)
DHCPServerFilter	IP address range(s) for the DHCP servers from which leases are accepted. (Optional)
DHCPDisallowIPConflicts	Do not allow IP collisions with static routes. (Default: Yes)
DHCPDisallowNetConflicts	Do not allow network collisions with static routes. (Default: Yes)
EnableRouterAdvertisement	Enable Router Advertisement for this interface. (Default: No)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.38. EthernetDevice

Description

Hardware settings for an Ethernet interface.

Properties

Name	Specifies a symbolic name for the device. (Identifier)
EthernetDriver	The Ethernet PCI driver that should be used by the interface.
PCIBus	PCI bus number where the Ethernet adapter is installed.
PCISlot	PCI slot number used by the Ethernet adapter.
PCIPort	Some Ethernet adapters have multiple ports that share the same bus and slot number. This parameter specifies what port to be used.
Media	Specifies if the link speed should be auto-negotiated or locked to a static speed. (Default: Auto)
Duplex	Specifies if the duplex should be auto-negotiated or locked to full or half duplex. (Default: Auto)
MACAddress	The hardware address for the interface. (Optional)
Comments	Text describing the current object. (Optional)

3.39. EthernetSettings

Description

Settings for Ethernet interface.

Properties

DHCP_MinimumLeaseTime	Minimum lease time (seconds) accepted from the DHCP server. (Default: 60)
DHCP_ValidateBcast	Require that the assigned broadcast address is the highest address in the assigned network. (Default: Yes)
DHCP_AllowGlobalBcast	Allow DHCP server to assign 255.255.255.255 as broadcast (Non-standard). (Default: No)
DHCP_UseLinkLocalIP	Use a 169.254.*.* IP while waiting for a lease (instead of 0.0.0.0). (Default: No)
DHCP_DisableArpOnOffer	Disable arp resolve on offers (normally used to verify that an IP is not occupied). (Default: No)
Ringsize_e1000_rx	Size of e1000 receive ring (per interface). (Default: 128)
Ringsize_e1000_tx	Size of e1000 send ring (per interface). (Default: 256)
Ringsize_ixgbe_rx	Size of ixgbe receive ring (per interface). (Default: 128)
Ringsize_ixgbe_tx	Size of ixgbe send ring (per interface). (Default: 256)
Ringsize_e100_rx	Size of e100 receive ring (per interface). (Default: 32)
Ringsize_e100_tx	Size of e100 send ring (per interface). (Default: 128)
Ringsize_yukonii_rx	Size of Yukon-II receive ring (per interface). (Default: 128)
Ringsize_yukonii_tx	Size of Yukon-II send ring (per interface). (Default: 128)
Ringsize_yukon_rx	Size of Yukon receive ring (per interface). (Default: 256)
Ringsize_yukon_tx	Size of Yukon send ring (per interface). (Default: 256)
Ringsize_bne2_rx	Size of bne2 receive ring (per interface). (Default: 1024)
Ringsize_bne2_tx	Size of bne2 send ring (per interface). (Default: 512)
Ringsize_r8169_rx	Size of r8169 receive ring (per interface). (Default: 256)

Ringsize_r8169_tx	Size of r8169 send ring (per interface). (Default: 256)
Ringsize_pcnet32_rx	Size of pcnet32 receive ring (per interface). (Default: 256)
Ringsize_pcnet32_tx	Size of pcnet32 transmit ring (per interface). (Default: 256)
IfaceMon_e1000	Enable interface monitor for e1000 interfaces. (Default: Yes)
IfaceMon_BelowCPUload	Temporarily disable interface monitor if CPU load goes above this percentage. (Default: 80)
IfaceMon_BelowIfaceLoad	Temporarily disable interface monitor on an interface if network load on the interface goes above this percentage. (Default: 70)
IfaceMon_MinInterval	Minimum interval between two resets of the same interface. (Default: 30)
IfaceMon_RxErrorPerc	At what percentage of errors to received packets to declare a problem. (Default: 20)
IfaceMon_TxErrorPerc	At what percentage of errors to sent packets to declare a problem. (Default: 7)
IfaceMon_ErrorTime	How long a problem must persist before an interface is reset. (Default: 10)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.40. EventReceiverSNMP2c

Description

A SNMP2c event receiver is used to receive SNMP events from the system.

Properties

Name	Specifies a symbolic name for the log receiver. (Identifier)
IPAddress	Destination IP address.
Port	Destination port. (Default: 162)
Community	Community string. (Default: public)
RepeatCount	Repetition counter. (Default: 0)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Optional; Default: Emergency,Alert,Critical,Error,Warning,Notice,Info)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.40.1. LogReceiverMessageException

Description

A log message exception is used to override the severity filter in the log receiver.

Properties

LogCategory	The Category of the log message.
LogID	The ID number of the log message, a empty value selects all messages of this category. (Optional)
LogType	EXCLUDE or INCLUDE. (Default: EXCLUDE)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.41. FileControlPolicy

Description

Add a File Control Profile that can be used by one or many IP Policies. The same Profile can be used on all protocols that support File Control scanning (HTTP, FTP, POP3 and SMTP).

Properties

Name	Specifies a symbolic name for the Profile. (Identifier)
FileListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)
File	List of file types to allow or deny. (Optional)
VerifyContentMimetype	Verify that file extensions correspond to the MIME type. (Default: No)
Comments	Text describing the current object. (Optional)

3.42. FragSettings

Description

Settings related to fragmented packets.

Properties

PseudoReass_MaxConcurrent	Maximum number of concurrent fragment reassemblies. Set to 0 to drop all fragments. (Default: 1024)
IllegalFrag	Illegally constructed fragments; partial overlaps, bad sizes, etc. (Default: DropLog)
DuplicateFragData	On receipt of duplicate fragments, verify matching data... (Default: Check8)
FragReassemblyFail	Failed packet reassembly attempts - due to timeouts or packet losses. (Default: LogSuspectSubseq)
DroppedFrag	Fragments of packets dropped due to rule base. (Default: LogSuspect)
DuplicateFrag	Duplicate fragments received. (Default: LogSuspect)
FragmentedICMP	Fragmented ICMP messages other than Ping; normally invalid. (Default: DropLog)
MinimumFragLength	Minimum allowed length of non-last fragments. (Default: 8)
ReassTimeout	Timeout of a reassembly, since previous received fragment. (Default: 65)
ReassTimeLimit	Maximum lifetime of a reassembly, since first received fragment. (Default: 90)
ReassDoneLinger	How long to remember a completed reassembly (watching for old dups). (Default: 20)
ReassIllegalLinger	How long to remember an illegal reassembly (watching for more fragments). (Default: 60)
IP6IllegalFrag	Illegally constructed fragments; partial overlaps, bad sizes, etc. (Default: DropLog)
IP6DuplicateFragData	On receipt of duplicate fragments, verify matching data... (Default: Check8)
IP6FragReassemblyFail	Failed packet reassembly attempts - due to timeouts or packet losses. (Default: LogSuspectSubseq)
IP6DroppedFrag	Fragments of packets dropped due to rule base. (Default: LogSuspect)
IP6DuplicateFrag	Duplicate fragments received. (Default:

	LogSuspect)
IP6RejectBadFragLength	Send Parameter Problem error upon reception of fragments with bad data length. (Default: No)
IP6IgnoreStubFrag	Ignore fragments with M flag cleared and fragment offset zero. (Default: No)
IP6MinimumFragLength	Minimum allowed length of non-last fragments. (Default: 8)
IP6ReassTimeout	Timeout of a reassembly, since previous received fragment. (Default: 65)
IP6ReassTimeLimit	Maximum lifetime of a reassembly, since first received fragment. (Default: 90)
IP6ReassDoneLinger	How long to remember a completed reassembly (watching for old dups). (Default: 20)
IP6ReassIllegalLinger	How long to remember an illegal reassembly (watching for more fragments). (Default: 60)
IP6SendErrorOnTimeout	Send ICMPv6 error when a fragment reassembly time out. (Default: No)

**Note**

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.43. GRE Tunnel

Description

A GRE interface is a Generic Routing Encapsulation (no encryption, no authentication, only encapsulation) tunnel over an existing IP network.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	Specifies the IP address of the GRE interface.
Network	Specifies the network address of the GRE interface.
RemoteEndpoint	Specifies the IP address of the remote endpoint.
EncapsulationChecksum	Add an extra level of checksum above the one provided by the IPv4 layer. (Default: No)
OriginatorIPType	Specifies what IP address to use as source IP in e.g. NAT. (Default: LocalInterface)
OriginatorIP	Manually specified originator IP address to use as source IP in e.g. NAT.
Metric	Specifies the metric for the auto-created route. (Default: 90)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given remote network. (Default: Yes)
OuterPBRTTable	The outer PBR Table to use. (Default: main)
UseSessionKey	Specify whether or not to use a session key. (Default: No)
SessionKey	Session key. (Default: 0)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.44. HighAvailability

Description

Configure the High Availability cluster parameters for this system.

Properties

Enabled	Enable high availability. (Default: No)
Sync	Specifies if cluster members are to synchronization configuration data. (Default: Yes)
ClusterID	A (locally) unique cluster ID to use in identifying this group of HA security gateways. (Default: 0)
Synciface	Specifies the interface used for state synchronization.
NodeID	Master or Slave. (Default: Master)
HASyncBufSize	How much sync data, in KB, to buffer while waiting for acknowledgments from the cluster peer. (Default: 1024)
HASyncMaxPktBurst	The maximum number of state sync packets to send in a burst. (Default: 20)
HAInitialSilence	The number of seconds to stay silent on startup or after reconfiguration. (Default: 5)
UseUniqueSharedMac	Use a unique shared mac address for each interface. (Default: Yes)
HADeactivateBeforeReconf	Deactivate(hand over) before Reconfiguration if Active. (Default: Yes)
ReconfFailoverTime	Number of non-responsive seconds before failover at HA reconf (0=immediate failover). (Default: 0)
HAFailoverTime	Number of milliseconds before failover when active HA node becomes non-responsive. (Default: 750)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.45. HTTPALGBanners

Description

HTTP banner files specifies the look and feel of HTTP ALG restriction web pages.

Properties

Name	Specifies a symbolic name for the HTTP Banner Files. (Identifier)
CompressionForbidden	HTML for the CompressionForbidden.html web page.
ContentForbidden	HTML for the ContentForbidden.html web page.
URLForbidden	HTML for the URLForbidden.html web page.
RestrictedSiteNotice	HTML for the RestrictedSiteNotice.html web page.
ReclassifyURL	HTML for the ReclassifyURL.html web page.
Comments	Text describing the current object. (Optional)

3.46. HTTPAuthBanners

Description

HTTP banner files specifies the look and feel of HTML authentication web pages.

Properties

Name	Specifies a symbolic name for the HTTP Banner Files. (Identifier)
FormLogin	HTML for the FormLogin.html web page.
LoginSuccess	HTML for the LoginSuccess.html web page.
LoginFailure	HTML for the LoginFailure.html web page.
LoginAlreadyDone	HTML for the LoginAlreadyDone.html web page.
LoginChallenge	HTML for the LoginChallenge.html web page.
LoginChallengeTimeout	HTML for the LoginChallenge.html Timeout' web page.
LogoutSuccess	HTML for the LogoutSuccess.html web page.
LogoutSuccessBasicAuth	HTML for the LogoutSuccessBasicAuth.html web page.
LogoutFailure	HTML for the LogoutFailure.html web page.
FileNotFound	HTML for the FileNotFound.html web page.
Comments	Text describing the current object. (Optional)

3.47. HTTPPoster

Description

Use the HTTP poster for dynamic DNS or automatic logon to services using web-based authentication.

Properties

URL	The URL that will be posted when the security gateway is loaded.
RepostDelay	Delay in seconds until the URL is refetched. (Default: 1200)
AlwaysRepost	Repost on each reconfiguration. (Default: No)
PostValues	HTTP POST the values. (Default: No)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.48. HWM

Description

Hardware Monitoring allows monitoring of hardware sensors.

Properties

Name	Specifies a symbolic name for the object.
Type	Type of monitoring.
Sensor	Sensor index.
MinLimit	Lower limit. (Optional)
MaxLimit	Upper limit. (Optional)
EnableMonitoring	Enable/disable monitoring. (Default: No)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.49. HWMSettings

Description

General settings for Hardware Monitoring

Properties

EnableSensors	Enable/disable all HWM functionality. (Default: No)
SensorPollInterval	Sensor polling interval. (Default: 500)
MemoryPollInterval	Memory polling interval in minutes. (Default: 15)
MemoryUsePercent	Should mem monitor use percentage as unit for monitoring, else it is megabyte. (Default: Yes)
MemoryLogRepetition	Should a log message be sent for each poll result that is in the Alert, Critical or Warning level, or should a log message only be sent when a new level is reached. (Default: No)
MemoryAlertLevel	Alert log message if free memory is below this value, disable by using 0. (Default: 0)
MemoryCriticalLevel	Critical log message if free memory is below this value, disable by using 0. (Default: 0)
MemoryWarningLevel	Warning log message if free memory is below this value, disable by using 0. (Default: 0)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.50. ICMPSettings

Description

Settings related to the ICMP protocol.

Properties

ICMPSendPerSecLimit	Maximum number of ICMP responses that will be sent each second. (Default: 500)
SilentlyDropStateICMPErrors	Silently drop ICMP errors regarding statefully tracked open connections. (Default: Yes)
ICMP6MaxOptND	Total number of options allowed per ICMP6 ND header. (Default: 32)
ICMP6NDOnMaxOptND	Validate the number of options per extension header when it goes beyond ICMP6MaxOptND. (Default: DropLog)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.51. IDList

Description

An ID list contains IDs, which are used within the authentication process when establishing an IPsec tunnel.

Properties

Name	Specifies a symbolic name for the ID list. (Identifier)
Comments	Text describing the current object. (Optional)

3.51.1. ID

Description

An ID is used to define parameters that are matched against the subject field in an X.509 certificate when establishing an IPsec tunnel.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
Type	IP, DNS, E-Mail or Distinguished name.
IP	IP address.
Hostname	Host name.
CommonName	Common name of the owner of the certificate. (Optional)
OrganizationName	Organization name of the owner of the certificate. (Optional)
OrganizationalUnit	Organizational unit of the owner of the certificate. (Optional)
Country	Specifies the country. (Optional)
LocalityName	Locality. (Optional)
EEmailAddress	E-mail address. (Optional)
DNTuples	Enter the most common DN types above, or as a comma separated list of types below. E.g. 'SN=12345, S=Smith' for serial number and surname. (Optional)
Comments	Text describing the current object. (Optional)

3.52. IDPRule

Description

An IDP Rule defines a filter for matching specific network traffic. When the filter criterion is met, the IDP Rule Actions are evaluated and possible actions taken.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
InsertionEvasion	Protect against insertion/evasion attacks. (Default: Yes)
URIIllegalUTF8	Specifies what action to take if invalid UTF-8 characters are seen in a HTTP URI. (Default: Log)
URIIllegalHex	Specifies what action to take when invalid hexencoding (%xx) is seen in a HTTP URI. (Default: DropLog)
URIDoubleEncode	Specifies what action to take when seeing double encoded characters in a HTTP URI. (Default: Ignore)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.52.1. IDPRuleAction

Description

An IDP Rule Action specifies what signatures to search for in the network traffic, and what action to take if those signatures are found.

Properties

Action	Specifies what action to take if the given signature is found. (Default: Protect)
Signatures	Specifies what signature(s) to search for in the network traffic. (Optional)
BlackList	Activate BlackList. (Default: No)
BlackListTimeToBlock	The number of seconds that the dynamic black list should remain. (Optional)
BlackListBlockOnlyService	Only block the service that triggered the blacklisting. (Default: No)
BlackListIgnoreEstablished	Do not drop existing connection. (Default: No)
PipeLimit	Specifies the bandwidth limit in kbps for hosts triggered by this action.
PipeNetwork	Traffic shaping will only apply to hosts that are within this network. (Default: 0/0)
PipeNewConnections	Enable piping of new connections from and to the same host. (Default: No)
PipeTimeWindow	Throttling of new connections to and from the triggering host will stop after the configured amount of time. (Default: 10)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.53. IGMRule

Description

An IGMP rule specifies how to handle inbound IGMP reports and outbound IGMP queries.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
Type	The type of IGMP messages the rule applies to. (Default: Report)
Action	Drop, Snoop, Proxy or PIM. (Default: Drop)
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet. (Default: core)
MulticastGroup	Specifies the multicast group to be compared to the received packet.
MulticastSource	Specifies the multicast source to be compared to the received packet.
RelayInterface	Specifies the interface via which to relay IGMP messages.
TranslateMGroup	Translate the multicast group for packets matching this rule. (Default: No)
GrpAllToOne	Rewrite all multicast groups to a single IP. (Default: No)
NewGrpIP	Translate the multicast group to this address.
TranslateMSource	Translate the multicast source for packets matching this rule. (Default: No)
SrcAllToOne	Rewrite all multicast sources to a single IP. (Default: No)
NewSrcIP	Translate the multicast source to this address.
Filter	Pass IGMP data not matching this rule to the next rule. (Default: Yes)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.54. IGMPSetting

Description

IGMP parameters can be tuned for one, or a group of interfaces in order to match the characteristics of a network.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
Interface	The interfaces that these settings should apply to.
RobustnessVariable	IGMP is robust to (Robustness Variable - 1) packet losses. (Default: 2)
MaxRequestsPerSecond	Maximum number of IGMP requests to process each second and interface. (Default: 100)
RouterVersion	Multiple IGMP querying routers on a network must use the same IGMP version. (Default: IGMPv3)
LowestCompatibleVersion	The lowest IGMP version to allow on incoming requests. (Default: IGMPv1)
QueryInterval	The interval between general queries sent by the security gateway. (Default: 125000)
QueryResponseInterval	The maximum time until a host (client) has to send an answer to a query. (Default: 10000)
LastMemberQueryInterval	The maximum time until a host (client) has to send an answer to a group and group-and-source specific query. (Default: 10000)
LastMemberQueryCount	The number of group and group-and-source specific queries sent until the security gateway decides there are no more subscribers to a specific multicast group. (Default: 2)
StartupQueryInterval	The general query interval to use during the startup phase. (Default: 30000)
StartupQueryCount	The number of startup queries to send during the startup phase. (Default: 2)
UnsolicitedReportInterval	The time between repetitions of a host's initial membership reports to a group. (Default: 1000)
ReactToOwnQueries	Should the system respond to Member Report Queries originating from itself. (Default: No)
Comments	Text describing the current object. (Optional)

3.55. IKEAlgorithms

Description

Configure algorithms which are used in the IKE phase of an IPsec session.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
DESEnabled	Enable DES encryption algorithm. (Default: No)
DES3Enabled	Enable 3DES encryption algorithm. (Default: No)
AESEnabled	Enable AES encryption algorithm. (Default: No)
BlowfishEnabled	Enable Blowfish encryption algorithm. (Default: No)
TwofishEnabled	Enable Twofish encryption algorithm. (Default: No)
CAST128Enabled	Enable CAST128 encryption algorithm. (Default: No)
BlowfishMinKeySize	Specifies the minimum Blowfish key size in bits. (Default: 128)
BlowfishKeySize	Specifies the Blowfish preferred key size in bits. (Default: 128)
BlowfishMaxKeySize	Specifies the maximum Blowfish key size in bits. (Default: 448)
TwofishMinKeySize	Specifies the minimum Twofish key size in bits. (Default: 128)
TwofishKeySize	Specifies the Twofish preferred key size in bits. (Default: 128)
TwofishMaxKeySize	Specifies the maximum Twofish key size in bits. (Default: 256)
AESMinKeySize	Specifies the minimum AES key size in bits. (Default: 128)
AESKeySize	Specifies the preferred AES key size in bits. (Default: 128)
AESMaxKeySize	Specifies the maximum AES key size in bits. (Default: 256)
MD5Enabled	Enable MD5 integrity algorithm. (Default: No)
SHA1Enabled	Enable SHA1 integrity algorithm. (Default: No)
XCBCEnabled	Enable XCBC-AES integrity algorithm. (Default: No)
SHA256Enabled	Enable SHA256 integrity algorithm. (Default: No)

SHA512Enabled	Enable SHA512 integrity algorithm. (Default: No)
Comments	Text describing the current object. (Optional)

3.56. InterfaceGroup

Description

Use an interface group to combine several interfaces for a simplified security policy.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
Equivalent	Specifies if the interfaces should be considered security equivalent, that means that if enabled the interface group can be used as a destination interface in rules where connections might need to be moved between the two interfaces. (Default: No)
Members	Specifies the interfaces that are included in the interface group.
Comments	Text describing the current object. (Optional)

3.57. IP6in4Tunnel

Description

A 6in4 tunnel (no encryption, no authentication, only encapsulation) allows tunneling of IPv6 packets over an existing IPv4 network.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	Specifies the IPv6 address of the 6in4 tunnel interface.
Network	Specifies the remote IPv6 network of the 6in4 interface.
RemoteEndpoint	Specifies the IPv4 address of the remote endpoint.
OriginatorIPType	Specifies what IPv4 address to use as source IP for the encapsulated IPv6 packets. (Default: LocalInterface)
OriginatorIP	Manually specified IPv4 address to use as source IP for the encapsulated IPv6 packets.
Metric	Specifies the metric for the auto-created route. (Default: 90)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given remote network. (Default: Yes)
MTU	Maximum Transmission Unit. (Default: 1280)
OuterPBRTTable	The outer PBR Table to use when communicating with the remote endpoint. (Default: main)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.58. IPPolicy

Description

An IP Policy specifies what action to perform on network traffic that matches the specified filter criteria.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the policy.
Action	Allow or Deny. (Default: Allow)
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
SourceAddressTranslation	Action to take on source address. (Default: Auto)
NATSourceAddressAction	Specify method to determine which sender address to use. (Default: OutgoingInterfaceIP)
SATSourceAddressAction	Specify method to determine which sender address to use.
SourceNewIP	Specifies which sender address will be used.
SourceBaseIP	Specifies base address for sender address.
SourceNATPool	Specifies NAT Pool to fetch sender address to be used.
SourcePortAction	Specify method to determine which port action to use. (Default: None)
SourceNewSinglePort	Translate to this port. (Optional)
SourceBasePort	Transpose using as base this port. (Optional)
DestAddressTranslation	Action to take on destination address. (Default: None)
DestAddressAction	Specify method to determine which destination

	address to use.
DestNewIP	Specifies which destination address will be used.
DestBaseIP	Specifies base address for destination address.
DestPortAction	Specify method to determine which port action to use. (Default: None)
DestNewSinglePort	Translate to this port. (Optional)
DestBasePort	Transpose using as base this port. (Optional)
AntiVirus	Anti-Virus scanning. (Default: No)
AV_Mode	Anti-Virus mode. (Default: UsePolicy)
AV_Policy	Selects preconfigured Anti-Virus Profile.
AV_AuditMode	Anti-Virus audit mode. (Default: No)
AV_ScanExclude	List of files to exclude from antivirus scanning. (Optional)
AV_CompressionRatio	A compression ratio higher than this value will trigger the action in Compression Ratio Action, a value of zero will disable all compression checks. (Default: 20)
AV_CompressionRatioAction	The action to take when high compression threshold is violated, all actions are logged. (Default: Drop)
AV_AllowEncryptedZip	Allow encrypted zip files, even though the contents can not be scanned. (Default: No)
AV_ZDEnabled	Enable ZoneDefense Block. (Default: No)
AV_ZDNetwork	Hosts within this network will be blocked at switches if a virus is found.
WebContentFiltering	Web Content Filtering. (Default: No)
WCF_Mode	Web Content Filtering mode. (Default: UsePolicy)
WCF_Policy	Selects preconfigured Web Content Filtering Profile.
WCF_AuditMode	Web Content Filtering audit mode. (Default: No)
WCF_FilteringCategories	Web content categories to block. (Optional)
WCF_NonManagedAction	Action to take for content that hasn't been classified. (Default: Allow)
WCF_AllowOverride	Allow the user to display a blocked site. (Default: No)
WCF_OverrideUpdateOnAccess	Restart the override timer on each new access to disallowed categories. (Default: Yes)
WCF_OverrideTimeToLive	Seconds that all disallowed categories will be allowed for the host that requested the override.

	(Default: 300)
WCF_AllowReclassification	Allow reclassification of sites. (Default: No)
URLFilter	URL Filter. (Default: No)
WC_Policy	Selects preconfigured URL Filter Profile.
FileControl	File Control. (Default: No)
FC_Mode	File Control mode. (Default: UsePolicy)
FC_Policy	Selects preconfigured File Control Profile.
FC_ListType	Specifies if the file list contains files to allow or deny. (Default: Block)
FC_FailModeBehavior	Standard behaviour on error: Allow or Deny. (Default: Deny)
FC_FileExtension	List of file types to allow or deny. (Optional)
FC_VerifyContentMimetype	Verify that file extensions correspond to the MIME type. (Default: No)
AppControl	Application Control. (Default: No)
AC_Mode	Application Control mode. (Default: UsePolicy)
AC_RuleSet	Selects preconfigured Application Rule.
AC_AppAction	Allow or Deny selected applications. (Default: Allow)
AC_Applications	List of applications to match.
Reject	Drop the packet and respond with an ICMP error or TCP reset. (Default: No)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.59. IPPool

Description

An IP Pool is a dynamic object which consists of IP leases that are fetched from a DHCP Server. The IP Pool is used as an address source by subsystems that may need to distribute addresses, e.g. by IPsec in Configuration mode.

Properties

Name	Specifies a symbolic name for the IP Pool. (Identifier)
DHCPServerType	Should server address be specified or should broadcast on a interface be used. (Default: Interface)
ServerIP	DHCP Server Address.
ServerFilter	Specifies which DHCP server that leases should be accepted from. (Optional)
Interface	Specifies the interface which has the DHCP server that leases are accepted from.
IPFilter	Specifies which IP addresses that are accepted from the DHCP server. (Optional)
RoutingTable	The routing table to use in communication with the DHCP server. (Default: main)
ReceiveInterface	Which interface to use when communicating with the DHCP server. (Optional)
PrefetchLeases	Specifies the number of leases an IP Pool will keep prefetched. (Default: 3)
MaxFree	Maximum number of free address that the IP pool will keep, others will be returned back to DCHP server. (Optional)
MaxClients	Maximum number clients that the IP pool is allowed to contain. (Optional)
MacRangeStart	Specifies the lower boundary of MAC addresses that DCHP Clients will use in communication with a server. (Optional)
MacRangeEnd	Specifies the upper boundary of MAC addresses that DCHP Clients will use in communication with a server. (Optional)
SenderIP	The local IP that should be used when communication with the DHCP server. (Optional)
AscendingFreeList	Enabling this will result in the IPs being fetched in a predictable manner from the free list. (Default: No)
Comments	Text describing the current object. (Optional)

3.60. IPRule

Description

An IP rule specifies what action to perform on network traffic that matches the specified filter criteria.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
Action	Reject, Drop, FwdFast, Allow, NAT, SAT ,SLB_SAT, GOTO or RETURN.
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
NATAction	Specify sender address or Use interface address. (Default: UseInterfaceAddress)
NATSenderAddress	Specifies which sender address will be used.
NATPool	Specifies the NATPool object to use.
SATTranslate	Specifies whether to translate source IP or destination IP. (Default: DestinationIP)
SATTranslateToIP	Translate to this IP address.
SATTranslateToPort	Translate to this port. (Optional)
SATAIIToOne	Rewrite all destination IPs to a single IP. (Default: No)
SLBAddresses	The IP addresses of the servers in the server farm.
SLBStickiness	Specifies stickiness mode. (Default: None)
SLBIdeTimeOut	New connections that arrive within the idle timeout are assigned to the same real server as previous connections from that address. The timeout is refreshed after each new connection.

	(Default: 30)
SLBMaxSlots	Specifies maximum number of slots for IP and network stickiness. (Default: 2048)
SLBNetSize	Specifies network size for network stickiness. (Default: 24)
SLBNewPort	Rewrite destination port to this port. (Optional)
SLBMonitorRoutingTable	Routing table used for server monitoring. (Default: main)
SLBMonitorPing	Enable monitoring using ICMP Ping packets. (Default: No)
SLBPingPollingInterval	Delay in milliseconds between each ping interval. (Default: 5000)
SLBPingSamples	Specifies the number of attempts to use for statistical calculations. (Default: 10)
SLBPingMaxPollFails	Specifies the maximum number of failed ping attempts until host is considered to be unreachable. (Default: 2)
SLBPingMaxAverageLatency	Specifies the max average latency for the sample attempts. (Default: 800)
SLBMonitorTCP	Enable monitoring using TCP handshakes. (Default: No)
SLBTCPPorts	Specifies the ports that will be monitored.
SLBTCPPollingInterval	Delay in milliseconds between each TCP handshake. (Default: 10000)
SLBTCPSamples	Specifies the number of attempts to use for statistical calculations. (Default: 10)
SLBTCPMaxPollFails	Specifies the maximum number of failed TCP attempts until host is considered to be unreachable. (Default: 2)
SLBTCPMaxAverageLatency	Specifies the max average latency for the sample attempts. (Default: 800)
SLBMonitorHTTP	Enable monitoring using HTTP requests. (Default: No)
SLBHTTPPorts	Specifies the ports that will be monitored. (Default: 80)
SLBHTTTPollingInterval	Delay in milliseconds between each monitor interval. (Default: 10000)
SLBHTTTPSamples	Specifies the number of attempts to use for statistical calculations. (Default: 10)
SLBHTTTPMaxPollFails	Specifies the maximum number of failed HTTP attempts until host is considered to be unreachable. (Default: 2)

SLBHTTPMaxAverageLatency	Specifies the max average latency for the sample attempts. (Default: 800)
SLBHTTPURLType	Defines how the request URL should be interpreted. (Default: FQDN)
SLBHTTPRequestURL	Specifies the HTTP URL to monitor.
SLBHTTPExpectedResponse	Expected HTTP response. (Optional)
SLBDistribution	Specifies the algorithm used for the load distribution tasks. (Default: RoundRobin)
SLBWindowTime	Specifies the window time used for counting the number of seconds back in time to summarize the number of new connections for connection-rate algorithm. (Default: 10)
RequireIGMP	Multicast traffic must have been requested using IGMP before it is forwarded. (Default: Yes)
MultiplexArgument	Specifies how the traffic should be forwarded and translated.
MultiplexAllToOne	Rewrite all destination IPs to a single IP. (Default: No)
RuleSet	Assuming action is Goto, where to redirect rule lookup.
AppControl	Application Control. (Default: No)
AC_Mode	Application Control mode. (Default: UsePolicy)
AC_RuleSet	Selects preconfigured Application Rule.
AC_AppAction	Allow or Deny selected applications. (Default: Allow)
AC_Applications	List of applications to match.
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.61. IPRuleFolder

Description

An IP Rule Folder can be used to group IP Rules into logical groups for better overview and simplified management.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies the name of the folder.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.61.1. IPPolicy

The definitions here are the same as in Section 3.58, "IPPolicy".

3.61.2. IPRule

The definitions here are the same as in Section 3.60, "IPRule".

3.62. IPRuleSet

Description

An IP Rule Set is a self-contained set of IP Rules. Default action is Drop.

Properties

Name	A name to uniquely identify this IPRuleSet. (Identifier)
Comments	Text describing the current object. (Optional)

3.62.1. IPPolicy

The definitions here are the same as in Section 3.58, "IPPolicy" .

3.62.2. IPRule

The definitions here are the same as in Section 3.60, "IPRule" .

3.62.3. IPRuleFolder

The definitions here are the same as in Section 3.61, "IPRuleFolder" .

3.63. IPsecAlgorithms

Description

Configure algorithms which are used in the IPsec phase of an IPsec session.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
NULLEnabled	Enable plaintext. (Default: No)
DESEnabled	Enable DES encryption algorithm. (Default: No)
DES3Enabled	Enable 3DES encryption algorithm. (Default: No)
AESEnabled	Enable AES encryption algorithm. (Default: No)
BlowfishEnabled	Enable Blowfish encryption algorithm. (Default: No)
TwofishEnabled	Enable Twofish encryption algorithm. (Default: No)
CAST128Enabled	Enable CAST128 encryption algorithm. (Default: No)
BlowfishMinKeySize	Specifies the minimum Blowfish key size in bits. (Default: 128)
BlowfishKeySize	Specifies the Blowfish preferred key size in bits. (Default: 128)
BlowfishMaxKeySize	Specifies the maximum Blowfish key size in bits. (Default: 448)
TwofishMinKeySize	Specifies the minimum Twofish key size in bits. (Default: 128)
TwofishKeySize	Specifies the Twofish preferred key size in bits. (Default: 128)
TwofishMaxKeySize	Specifies the maximum Twofish key size in bits. (Default: 256)
AESMinKeySize	Specifies the minimum AES key size in bits. (Default: 128)
AESKeySize	Specifies the preferred AES key size in bits. (Default: 128)
AESMaxKeySize	Specifies the maximum AES key size in bits. (Default: 256)
MD5Enabled	Enable MD5 integrity algorithm. (Default: No)
SHA1Enabled	Enable SHA1 integrity algorithm. (Default: No)
SHA256Enabled	Enable SHA256 integrity algorithm. (Default: No)

SHA512Enabled	Enable SHA512 integrity algorithm. (Default: No)
XCBCEnabled	Enable XCBC-AES integrity algorithm. (Default: No)
Comments	Text describing the current object. (Optional)

3.64. IPsecTunnel

Description

An IPsec tunnel item is used to define IPsec endpoint and will appear as a logical interface in the system.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the interface. (Identifier)
LocalNetwork	The network on "this side" of the IPsec tunnel. The IPsec tunnel will be established between this network and the remote network.
RemoteNetwork	The network connected to the remote gateway. The IPsec tunnel will be established between the local network and this network.
RemoteEndpoint	Specifies the IP address of the remote endpoint. This is the address the security gateway will establish the IPsec tunnel to. It also dictates from where inbound IPsec tunnels are allowed. (Optional)
IKEConfigModePool	Selects IKE Config Mode Pool to use for the tunnel. (Optional)
IKEAlgorithms	Specifies the IKE Proposal list used with the tunnel. (Default: High)
IPsecAlgorithms	Specifies the IPsec Proposal list used with the tunnel. (Default: High)
IKELifeTimeSeconds	The lifetime of the IKE connection in seconds. Whenever it expires, a new phase-1 exchange will be performed. (Default: 28800)
IPsecLifeTimeSeconds	The lifetime of the IPsec connection in seconds. Whenever it's exceeded, a re-key will be initiated, providing new IPsec encryption and authentication session keys. (Default: 3600)
IPsecLifeTimeKilobytes	The lifetime of the IPsec connection in kilobytes. (Default: 0)
EncapsulationMode	Specifies if the IPsec tunnel should use Tunnel or Transport mode. (Default: Tunnel)
AuthMethod	Certificate or Pre-shared key. (Default: PSK)
PSK	Selects the Pre-shared key to use with this IPsec Tunnel.
LocalIDType	Selects the type of Local ID to use. (Default: Auto)

LocalIDValue	Specify the local identity of the tunnel ID.
GatewayCertificate	Selects the certificate the security gateway uses to authenticate itself to the other IPsec peer.
RootCertificates	Selects one or more root certificates to use with this IPsec Tunnel.
IDList	Selects the identification list to use with this IPsec Tunnel. An identification list is a list of the identities that are allowed to establish a IPsec tunnel. (Optional)
XAuth	Required for inbound or Pass to peer gateway. (Default: Off)
XAuthUsername	Specifies the username to pass to the remote gateway via IKE XAuth.
XAuthPassword	Specifies the password to pass to the remote gateway via IKE XAuth.
AddRouteToRemoteNet	Dynamically add route to the remote networks when a tunnel is established. (Default: No)
PlaintextMTU	Specifies the size in bytes at which to fragment plaintext packets (rather than fragmenting IPsec). (Default: 1420)
OriginatorIPType	Specifies what IP address to use as source IP in e.g. NAT. (Default: LocalInterface)
OriginatorIP	Manually specified originator IP address to use as source IP in e.g. NAT.
OriginatorHAIP	Manually specified private originator IP address for use in HA. (Optional)
IKEMode	Specifies which IKE mode to use: main or aggressive. (Default: Main)
DHGroup	Specifies the Diffie-Hellman group to use when doing key exchanges in IKE. (Default: 2)
PFS DHGroup	Specifies which Diffie-Hellman group to use with PFS. (Default: None,1,2,5)
SetupSAPer	Setup security association per network, host or port. (Default: Net)
DeadPeerDetection	Enable Dead Peer Detection. (Default: Yes)
NATTraversal	Enable or disable NAT traversal. (Default: OnIfNeeded)
AutoEstablish	Negotiate tunnel directly after reconfiguration. (Default: No)
Metric	Specifies the metric for the auto-created route. (Default: 90)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using

	the given remote network. (Default: Yes)
LocalEndpoint	Specifies on which local address this tunnel should accept incoming IKE/IPsec traffic. (Optional)
SourceInterface	Specifies which interface this tunnel should use for IKE/IPsec traffic. (Default: any)
OuterPBRTTable	Specifies which routing table this tunnel should use for IKE/IPsec traffic. (Default: main)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.65. IPsecTunnelSettings

Description

Settings for the IPsec tunnel interfaces used for establishing IPsec VPN connections to and from this system.

Properties

IPsecMaxTunnels	Amount of IPsec tunnels allowed (0 = automatic). (Default: 0)
IPsecMaxRules	Amount of IPsec rules allowed (0 = automatic). (Default: 0)
IKESendInitialContact	Send 'initial contact' messages. (Default: Yes)
IKESendCRLs	Send CRLs in the IKE exchange. (Default: Yes)
IKECRLValidityTime	Maximum number of seconds a CRL is considered valid (0=obey the 'next update' field in the CRL). (Default: 86400)
IKEMaxCAPath	Maximum number of CA certificates in a certificate path. (Default: 15)
IPsecCertCacheMaxCerts	Maximum number of entries in the certificate cache. (Default: 1024)
IPsecBeforeRules	Pass IKE & IPsec (ESP/AH) traffic sent to the security gateway directly to the IPsec engine without consulting the ruleset. (Default: Yes)
IPsecGWNameCacheTime	Amount of time to keep an IPsec tunnel open when the remote DNS name fails to resolve. (Default: 14400)
DPDMetric	Metric 10s of seconds with no traffic or other evidence of life in tunnel before SA is removed. (Default: 3)
FlowMetric	Minimum number of seconds without data traffic in a flow to activate IKE DPD liveness checks from the corresponding IKE SA. (Default: 15)
IPsecDPDNoWaitWorryTime	Do not wait for 10 times the value of DPD Metric after the value of Flow Metric has expired without aliveness sign before activating IKE DPD. (Default: No)
DPDKeepTime	Number 10s of seconds a SA will remain in dead cache after a delete. DPD will not trigger if peer already is cached as dead. (Default: 2)
DPDExpireTime	Number of seconds that DPD-R-U-THERE messages will be sent. (Default: 15)
IPsecHardwareAcceleration	IPsec hardware acceleration. (Default: Inline)

IPsecDisablePKAccel	Disable hardware acceleration for public-key operations. (Default: No)
AESNIEnable	Enable AES-NI acceleration for processors that support it. (Default: Yes)
IPsecESPDetectNATChange	Use inbound ESP packets to detect that NAT mappings have changed. (Default: Yes)

**Note**

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.66. IPSettings

Description

Settings related to the IP protocol.

Properties

EnableIPv6	Enable processing of IPv6 traffic. (Default: No)
IP6LogOnForwardHopLimit0	Log any attempts of forwarding IPv6 packets with HopLimit=0 destined for outside the security gateway; this should never happen! (Default: DropLog)
IP6AnycastSrc	Drop Log packets with anycast source address. (Default: DropLog)
HopLimitMin	The minimum IP Hop-Limit value accepted on receipt. (Default: 3)
HopLimitOnLow	What action to take on too low unicast Hop-Limit values. (Default: DropLog)
HopLimitMinMulticast	The minimum IP multicast Hop-Limit value accepted on receipt. (Default: 3)
HopLimitOnLowMulticast	What action to take on too low multicast Hop-Limit values. (Default: DropLog)
DefaultHopLimit	The default IP Hop-Limit of packets originated by the security gateway (32-255). (Default: 255)
IP6FI	Validate IPV6 Flow label header field. (Default: Ignore)
IP6TC	Validate IPV6 Traffic class header field. (Default: Ignore)
IP6MaxExtHdr	Maximum allowed size of all IP6 extension headers. (Default: 256)
IP6OnMaxExtHdr	Validate the extension header length when it goes beyond IP6MaxExtHdr. (Default: DropLog)
RejectUnorderedExtHdr	Send an ICMPv6 error when encountering extension headers out of order. (Default: No)
IP6MaxOptHdr	Total number of options allowed per IP6 extension header. (Default: 8)
IP6OnMaxOptHdr	Validate the number of options per extension header when it goes beyond IP6MaxOptHdr. (Default: DropLog)
IP6ValidateSyntax	Validate ipv6 syntax violation. (Default: ValidateLogBad)
IP6OPT_PADN	Validate when ipv6 padn option data fields are non-zero. (Default: StripLog)

IP6OPT_JUMBO	Validate jumbogram packets. (Default: ValidateLog)
IP6OPT_RA	Validate Router Alert packets. (Default: Ignore)
IP6OPT_HA	Validate Home Address option packets. (Default: Ignore)
IP6OPT_OTH	Validate unknown option types. (Default: RFC2460Log)
IP6_RH0	Validate routing header type 0 option. (Default: RFC5095NoSupportLog)
IP6_RH2	Validate routing header type 2 option. (Default: RFC2460NoSupportLog)
IP6_RHOther	Validate routing header other than type 0 or 2 option. (Default: RFC2460NoSupportLog)
IP6OnLocalUnrecognizedHdr	How to handle packets destined to the SGW with unrecognized IPV6 headers. (Default: DropLog)
LogCheckSumErrors	Log IP packets with bad checksums. (Default: Yes)
LogNonIPV4IPV6	Log occurrences of non-IPV4/IPV6 packets. (Default: Yes)
LogReceivedTTL0	Log received packets with TTL=0; this should never happen! (Default: Yes)
LogOnForwardTTL0	Log any attempts of forwarding IPv4 packets with TTL=0 destined for outside the security gateway; this should never happen! (Default: DropLog)
Log0000Src	Log invalid 0.0.0.0 source address. (Default: Drop)
Block0Net	Block 0.* source addresses. (Default: DropLog)
Block127Net	Block 127.* source addresses. (Default: DropLog)
BlockMulticastSrc	Block multicast source addresses (224.0.0.0--239.255.255.255). (Default: DropLog)
TTLMin	The minimum IP Time-To-Live value accepted on receipt. (Default: 3)
TTLOnLow	What action to take on too low unicast TTL values. (Default: DropLog)
TTLMinMulticast	The minimum IP multicast Time-To-Live value accepted on receipt. (Default: 3)
TTLOnLowMulticast	What action to take on too low multicast TTL values. (Default: DropLog)
DefaultTTL	The default IP Time-To-Live of packets originated by the security gateway (32-255). (Default: 255)
LayerSizeConsistency	TCP/UDP/ICMP/etc layer data and header sizes matching lower layer size information. (Default: ValidateLogBad)

SecuRemoteUDPEncapCompat	Allow IP data to contain eight bytes more than the UDP total length field specifies -- Checkpoint SecuRemote violates NAT-T drafts. (Default: No)
IPOptionSizes	Validity of IP header option sizes. (Default: ValidateLogBad)
IPOPT_SR	How to handle IP packets with contained source or return routes. (Default: DropLog)
IPOPT_TS	How to handle IP packets with contained Timestamps. (Default: DropLog)
IPOPT_RTRALT	How to handle IP packets with contained route alert. (Default: ValidateLogBad)
IPOPT_OTHER	How to handle IP options not specified above. (Default: DropLog)
DirectedBroadcasts	How to handle directed broadcasts being passed from one interface to another. (Default: DropLog)
IPRF	How to handle the IP Reserved Flag, if set; it should never be. (Default: DropLog)
StripDFOnSmall	Strip the "DontFragment" flag for packets of this size or smaller. (Default: 65535)
MulticastIPEnetOnMismatch	What action to take when ethernet and IP multicast addresses do not match. (Default: DropLog)
TTLMinBroadcast	The shortest IP broadcast Time-To-Live value accepted on receipt. (Default: 1)
TTLonLowBroadcast	What action to take on too low broadcast TTL values. (Default: DropLog)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.67. ixgbeEthernetPCIDriver

Description

Intel (IXGBE) 10 Gigabit Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.68. IXP4NPEEthernetDriver

Description

Intel (IXP4xxNPE) Fast Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.69. L2TPClient

Description

A PPTP/L2TP client interface is a PPP (Point-to-Point Protocol) tunnel over an existing IP network. Its IP address and DNS servers are dynamically assigned.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	The host name to store the assigned IP address in, if this network object exists and have a value other than 0.0.0.0 the PPTP/L2TP client will try to get that one from the PPTP/L2TP server as preferred IP. (Optional)
Network	The network from which traffic should be routed into the tunnel.
RemoteEndpoint	The IP address of the L2TP/PPTP server.
TunnelProtocol	Specifies if PPTP or L2TP should be used for this tunnel. (Default: PPTP)
OriginatorIPType	Specifies what IP address to use as source IP in e.g. NAT. (Default: LocalInterface)
OriginatorIP	Manually specified originator IP address to use as source IP in e.g. NAT.
DNS1	IP of the primary DNS server. (Optional)
DNS2	IP of the secondary DNS server. (Optional)
Username	Specifies the username to use for this PPTP/L2TP interface.
Password	The password to use for this PPTP/L2TP interface.
PPPAuthNoAuth	Allow no authentication for this tunnel. (Default: No)
PPPAuthPAP	Use PAP authentication protocol for this tunnel. User name and password are sent in plaintext. (Default: Yes)
PPPAuthCHAP	Use CHAP authentication protocol for this tunnel. (Default: Yes)
PPPAuthMSCHAP	Use MS-CHAP authentication protocol for this tunnel. (Default: Yes)
PPPAuthMSCHAPv2	Use MS-CHAP v2 authentication protocol for this tunnel. (Default: Yes)
MPPENone	Allow authentication without Microsoft Point-to-Point Encryption (MPPE). (Default: Yes)

MPPER440	Use an RC4 40 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
MPPER456	Use an RC4 56 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
MPPER4128	Use an RC4 128 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
DialOnDemand	Enable Dial-on-demand which means that the L2TP/PPTP tunnel will not be setup until traffic is sent on the interface. (Default: No)
ActivitySensing	Specifies if the dial-on-demand should trigger on inbound or outbound traffic or both. (Default: BiDirectional)
IdleTimeout	Idle timeout in seconds for dial-on-demand. (Default: 3600)
Metric	Specifies the metric for the auto-created route. (Default: 90)
MTU	Specifies the size (in bytes) of the largest packet that can be passed onward. (Default: 1456)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given remote network. (Default: Yes)
MPPEAllowStateful	Allow usage of Stateful MPPE (less secure, use only for compatibility). (Default: No)
IPsecInterface	Use this IPsec interface to encrypt the traffic to the L2TP server. (L2TP/IPsec). (Optional)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.70. L2TPServer

Description

A PPTP/L2TP server interface terminates PPP (Point to Point Protocol) tunnels set up over existing IP networks.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	The IP address of the PPTP/L2TP server interface.
TunnelProtocol	Specifies if PPTP or L2TP should be used for this tunnel. (Default: PPTP)
Interface	The interface that the PPTP/L2TP Server should be listening on.
ServerIP	Specifies the IP that the PPTP/L2TP server should listen on, this can be an IP of a interface, or for example an ARP published IP.
UseUserAuth	Enable the use of user authentication rules on this server. (Default: Yes)
MPPENone	Allow no authentication for this tunnel. (Default: Yes)
MPPER440	Use an RC4 40 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
MPPER456	Use an RC4 56 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
MPPER4128	Use an RC4 128 bit MPPE session key with MS-CHAP or MS-CHAP v2 authentication protocol. (Default: Yes)
IPPool	A range, group or network that the PPTP/L2TP server will use as IP address pool to give out IP addresses to the clients from.
DNS1	IP of the primary DNS server. (Optional)
DNS2	IP of the secondary DNS server. (Optional)
NBNS1	IP of the primary Windows Internet Name Service (WINS) server that is used in Microsoft environments which uses the NetBIOS Name Servers (NBNS) to assign IP addresses to NetBIOS names. (Optional)
NBNS2	IP of the primary Windows Internet Name Service (WINS) server that is used in Microsoft environments which uses the NetBIOS Name

	Servers (NBNS) to assign IP addresses to NetBIOS names. (Optional)
AllowedRoutes	Restricts networks for which routes may automatically be added. (Default: all-nets)
MPPEAllowStateful	Allow usage of Stateful MPPE (less secure, use only for compatibility). (Default: No)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
ProxyARPAAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

3.71. L2TPServerSettings

Description

PPTP/L2TP server settings.

Properties

L2TPBeforeRules

Pass L2TP connections sent to the security gateway directly to the L2TP engine without consulting the ruleset. (Default: Yes)

PPTPBeforeRules

Pass PPTP connections sent to the security gateway directly to the PPTP engine without consulting the ruleset. (Default: Yes)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.72. L2TPv3Client

Description

A L2TPv3 client interface terminates L2 (Ethernet and VLAN) tunnels set up over existing IP networks.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	The IP address of the L2TPv3 Client interface.
LocalNetwork	The network on "this side" of the L2TPv3 tunnel.
PseudowireType	Specifies if L2TPv3 should tunnel Ethernet or IEEE 802.1Q (VLAN) tagged Ethernet frames. (Default: Ethernet)
Protocol	Specifies if L2TPv3 should tunnel over IP or UDP. (Default: UDP)
RemoteEndpoint	The IP address of the L2TPv3 server.
OriginatorIPType	Specifies what IP address to use as source IP in e.g. NAT. (Default: LocalInterface)
OriginatorIP	Manually specified originator IP address to use as source IP in e.g. NAT.
IPsecInterface	Use this IPsec interface to encrypt the traffic to the L2TPv3 server. (L2TP/IPsec). (Optional)
AutoRouteMetric	Specifies the metric for the auto-created route used by the L2TPv3 Client. (Default: 100)
HostName	The host name for this L2TPv3 Client. (Used in the Host Name AVP). (Optional)
RouterID	Router ID. (Used in the Router ID AVP). (Optional)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
ProxyARPAAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

3.73. L2TPv3Server

Description

A L2TPv3 server interface terminates L2 (Ethernet and VLAN) tunnels set up over existing IP networks.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
IP	The IP address of the L2TPv3 Server interface.
LocalNetwork	The network on "this side" of the L2TPv3 tunnel.
Protocol	Specifies if L2TPv3 should tunnel over IP or UDP. (Default: UDP)
Interface	The interface that the L2TPv3 Server should be listening on.
ServerIP	Specifies the IP that the L2TPv3 Server should listen on, this can be an IP of a interface, or for example an ARP published IP.
AutoRouteMetric	Specifies the metric for the auto-created route used by the L2TPv3 Server. (Default: 100)
HostName	The host name for this L2TPv3 Server. (Used in the Host Name AVP). (Optional)
RouterID	Router ID. (Used in the Router ID AVP). (Optional)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
ProxyARPAAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

3.74. LDAPDatabase

Description

External LDAP server used to verify user names and passwords.

Properties

Name	Specifies a symbolic name for the server. (Identifier)
IP	The IP address of the server.
Port	The TCP port of the server. (Default: 389)
Timeout	The timeout, in milliseconds, used when processing requests. (Default: 5)
NameAttr	Specifies a name attribute in LDAP database. (Default: uid)
PassAttr	Specifies a password attribute in LDAP database. (Optional)
GroupsAttr	Specifies the group membership attribute used in the LDAP database. (Default: memberOf)
GetGroups	Retrieve group membership for users. (Default: Yes)
DomainName	The domain name of the server. (Optional)
CombinedUsername	Combine Name Attribute with given username, Optional Attribute and Base Object in LDAP bind request. (Default: No)
OptionalAttribute	Optional attribute to be used in bind request together with given username and Base Object. (Optional)
BaseObject	Specifies a base object to search. (Optional)
UserName	Specifies a user name. (Optional)
Password	Specifies a user password. (Optional)
Type	Add domain name to username. (Default: 0)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.75. LDAPServer

Description

An LDAP server is used as a central repository of certificates and CRLs that the security gateway can download when necessary.

Properties

Host	Specifies the IP address or hostname of the LDAP server.
Username	Specifies the username to use when accessing the LDAP server. (Optional)
Password	Specifies the password to use when accessing the LDAP server. (Optional)
Port	Specifies the LDAP service port number. (Default: 389)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.76. LengthLimSettings

Description

Length limitations for various protocols.

Properties

MaxTCPLen	TCP; Sometimes has to be increased if tunneling protocols are used. (Default: 1480)
MaxUDPLen	UDP; Many interactive applications use large UDP packets, may otherwise be decreased to 1480. (Default: 60000)
MaxICMPLen	ICMP; May be decreased to 1480 if desired. (Default: 10000)
MaxICMPv6Len	ICMPv6; May be decreased to 1280 if desired. (Default: 10000)
MaxGRELen	Encapsulated (tunneled transport), used by PPTP. (Default: 2000)
MaxESPLen	IPsec ESP; Encrypted communication. (Default: 2000)
MaxAHLen	IPsec AH; Authenticated communication. (Default: 2000)
MaxSKIPLen	SKIP; Simple Key management for IP, VPN protocol. (Default: 2000)
MaxOSPFLen	OSPF; Open Shortest Path First, routing protocol. (Default: 1480)
MaxIPIPLen	IPIP/FWZ; Encapsulated (tunneled) transport, used by VPN-1. (Default: 2000)
MaxIPCompLen	IPsec IPComp; Compressed communication. (Default: 2000)
MaxL2TPLen	L2TP; Layer 2 Tunneling Protocol. (Default: 2000)
MaxOtherSubIPLen	Others; sometimes has to be increased if unknown tunneling protocols are used. (Default: 1480)
LogOversizedPackets	Log occurrences of oversized packets. (Default: Yes)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.77. LinkAggregation

Description

A Link Aggregation interface combines multiple Ethernet interfaces into a single logical endpoint.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
Members	A set of Ethernet interfaces to aggregate. (Optional)
DistributionAlgorithm	Specifies how outgoing traffic will be distributed among the active links. (Default: Combination)
Mode	Specifies the method used to aggregate links. (Default: Static)
LACPActivity	Specifies if the system should actively attempt to initiate LACP negotiations or wait for a partner system to do so. (Default: Active)
LACPTimeout	Specifies how soon the system will reselect active links if a link is broken. (Default: Long)
LACPSystemPriority	System priority value to be sent in LACP messages. (Default: 1)
MACAddress	The hardware address for the interface. (Optional)
IP	The IP address of the interface.
Network	The network of the interface.
DefaultGateway	The default gateway of the interface. (Optional)
Broadcast	The broadcast address of the connected network. (Optional)
EnableIPv6	Enable processing of IPv6 traffic on this interface. (Default: No)
IPv6IP	The IP address of the interface.
IPv6Network	The network of the interface.
IPv6DefaultGateway	The default gateway of the interface. (Optional)
PrivateIP	The private IP address of this high availability node. (Optional)
NOCHB	This will disable sending Cluster Heartbeats from this interface (used by HA to detect if a node is online and working). (Optional)
MTU	Specifies the size (in bytes) of the largest packet that can be passed onward. Must be 1294 or larger

	when IPv6 is enabled. (Default: 1500)
Metric	Specifies the metric for the auto-created route. (Default: 100)
DHCPEnabled	Enable DHCP client on this interface. (Default: No)
DHCPHostName	Optional DHCP Host Name. Leave blank to use default name. (Optional)
AutoSwitchRoute	Enable transparent mode, which means that a switch route is added automatically for this interface. (Default: No)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given network. (Default: Yes)
AutoDefaultGatewayRoute	Automatically add a default route for this interface using the given default gateway. (Default: Yes)
DHCPDNS1	IP of the primary DNS server. (Optional)
DHCPDNS2	IP of the secondary DNS server. (Optional)
DHCPPreferredIP	Set a preferred IP address which will be included in the request to the DHCP server. (Optional)
DHCPAllowStaticRoutes	Allow the use of static routes send from the DHCP server. (Default: No)
DHCPPreferredLeaseTime	Set a preferred lease time which will be included in the request to the DHCP server. (Optional)
DHCPLeaseFilter	Allowed IP address range(s) for the DHCP lease. (Optional)
DHCPServerFilter	IP address range(s) for the DHCP servers from which leases are accepted. (Optional)
DHCPDisallowIPConflicts	Do not allow IP collisions with static routes. (Default: Yes)
DHCPDisallowNetConflicts	Do not allow network collisions with static routes. (Default: Yes)
EnableRouterAdvertisement	Enable Router Advertisement for this interface. (Default: No)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.78. LinkMonitor

Description

The Link Monitor allows the system to monitor one or more hosts and take action if they are unreachable.

Properties

Action	Specifies what action the system should take.
Addresses	Specifies the addresses that should be monitored.
MaxLoss	A single host is considered unreachable if this number of consecutive ping responses to that host are not replied to. (Default: 7)
PingInterval	Milliseconds between each monitor attempt. (Default: 250)
InitGracePeriod	Do not allow triggering of the link monitor for this number of seconds after the last reconfiguration. (Default: 45)
RoutingTable	Routing table used for link monitoring. (Default: main)
UseSharedIP	Use the shared IP of an HA cluster instead of the private IP of the node. (Default: No)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.79. LocalReassSettings

Description

Parameters use for local fragment reassembly.

Properties

LocalReass_MaxConcurrent	Maximum number of concurrent local reassemblies. (Default: 256)
LocalReass_MaxSize	Maximum size of a locally reassembled packet. (Default: 10000)
LocalReass_NumLarge	Number of large (>2K) local reassembly buffers (of the above size). (Default: 32)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.80. LocalUserDatabase

Description

A local user database contains user accounts used for authentication purposes.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
Comments	Text describing the current object. (Optional)

3.80.1. User

Description

User credentials may be used in User Authentication Rules, which in turn are used in e.g. PPP, IPsec XAuth, Web Authentication, etc

Properties

Name	Specifies the username to add into the user database. (Identifier)
Password	The password for this user.
Groups	Specifies the user groups that this user is a member of, e.g. Administrators. (Optional)
IPPool	If the user is logging in over PPTP/L2TP it will be assigned this static IP. (Optional)
AutoAddRouteNet	PPTP/L2TP networks behind the user. (Optional)
AutoAddRouteMetric	Metric for the network. (Optional)
SSHKeys	Public keys used to log in via SSH. (Optional)
Comments	Text describing the current object. (Optional)

3.81. LogReceiverFWLog

Description

A FWLog receiver is used to receive log events from the system in the FWlog format.

Properties

Name	Specifies a symbolic name for the log receiver. (Identifier)
IPAddress	Destination IP address.
Port	Destination port. (Default: 999)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Optional; Default: Emergency,Alert,Critical,Error,Warning,Notice,Info)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.81.1. LogReceiverMessageException

The definitions here are the same as in Section 3.40.1, "LogReceiverMessageException" .

3.82. LogReceiverMemory

Description

A memory log receiver is used to receive and keep log events in system RAM.

Properties

Name	Specifies a symbolic name for the log receiver. (Identifier)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Optional; Default: Emergency,Alert,Critical,Error,Warning,Notice,Info)
Comments	Text describing the current object. (Optional)

3.82.1. LogReceiverMessageException

The definitions here are the same as in Section 3.40.1, "LogReceiverMessageException" .

3.83. LogReceiverSyslog

Description

A Syslog receiver is used to receive log events from the system in the standard Syslog format.

Properties

Name	Specifies a symbolic name for the log receiver. (Identifier)
IPAddress	Specifies the IP address of the log receiver.
Port	Specifies the port number of the log service. (Default: 514)
Facility	Specifies what facility is used when logging. (Default: local0)
Hostname	Specifies a unique hostname. If not configured, the IP address of the sending interface will be sent as hostname. (Optional)
RFC5424	Send Syslog messages according to RFC5424. (Default: No)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Optional; Default: Emergency,Alert,Critical,Error,Warning,Notice,Info)
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.83.1. LogReceiverMessageException

The definitions here are the same as in Section 3.40.1, "LogReceiverMessageException" .

3.84. LogSettings

Description

Advanced log settings.

Properties

LogSendPerSecLimit

Limits how many log packets the security gateway may send out per second. (Default: 2000)

AlarmRepeatInterval

Repetition interval for continuous alarms (in seconds). (Default: 60)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.85. LoopbackInterface

Description

Loopback interfaces will take all packets sent through them and pass them back up a different interface as newly received packets.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
LoopTo	Loopback interface. (Optional)
IP	Interface address.
Network	The network of the interface.
Broadcast	The broadcast address of the connected network. (Optional)
Metric	Specifies the metric for the auto-created route. (Default: 100)
AutoInterfaceNetworkRoute	Automatically add a route for this virtual LAN interface using the given network. (Default: Yes)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.86. MarvellEthernetPCIDriver

Description

Marvell (88E8001,88E8053,88E8062) Fast and Gigabit Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.87. MiscSettings

Description

Miscellaneous Settings

Properties

UDPSrcPort0	How to treat UDP packets with source port 0. (Default: DropLog)
Port0	How to treat TCP/UDP packets with destination port 0 and TCP packets with source port 0. (Default: DropLog)
WatchdogTimerTime	Number of non-responsive seconds before watchdog is triggered (0=disable). (Default: 180)
BufFloodRebootTime	How long to allow completely flooded buffers before rebooting the Security Gateway. (Default: 3600)
ScrSave	Screen saver selection. (Default: ScrSaveBlank)
StatusBar	Status bar control. (Default: Auto)
ScrSaveTime	Idle seconds before screen saver is automatically activated (0=disable). (Default: 300)
HighBuffers_Dynamic	Allocate the HighBuffers value dynamically. (Default: Yes)
HighBuffers	Number of packet buffers to allocate in addition to the ~200 initial buffers. (Default: 1024)
LocalUndelivered	How to treat (allowed) packets to the Security Gateway that do not match open ports (snmp, scp, netcon, etc). (Default: DropLog)
MaxPipeUsers	Max number of concurrently tracked pipe users. (Default: 1024)
Reassembly_MaxConnections	Maximum percentage of the maximum allowed connections that data reassembly may be performed on. (Default: 80)
Reassembly_MaxProcessingMem	Maximum percentage of device memory that may be used for processing data on reassembled connections. (Default: 3)
WCFPerfLog	Enables periodical logging of Web Content Filtering resolving performance. (Default: Disabled)
AppCtl_FreeMemOptLevel	Percentage level of free memory when the Application Control subsystem will optimize its memory usage and free up memory (0=disabled). (Default: 5)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.88. MulticastSettings

Description

Advanced Multicast Settings.

Properties

AutoAddMulticastCoreRoute	Auto generate core route for "224.0.0.1-239.255.255.255". (Default: Yes)
IGMPBeforeRules	Allows IGMP traffic to enter the Security Gateway by default. (Default: Yes)
IGMPMaxGlobalRequestsPerSecond	Maximum number of requests per second. (Default: 1000)
IGMPMaxRequestsPerSecond	Maximum number of requests per interface per second. (Default: 100)
IGMPReactToOwnQueries	The Security Gateway should always respond with Member Reports, even to Queries originating from itself. (Default: No)
IGMPRobustnessVariable	IGMP is robust to 'value' - 1 packet losses. (Default: 2)
IGMPQueryInterval	The interval (ms) between general queries sent by the Security Gateway. (Default: 125000)
IGMPQueryResponseInterval	The maximum time (ms) until a host/client has to send an answer to a query. (Default: 10000)
IGMPStartupQueryInterval	The general query interval (ms) to use during the startup phase (default: 1/4 of the 'IGMP Query Interval' parameter. (Default: 30000)
IGMPStartupQueryCount	The number of startup queries to send during the startup phase. (Default: 2)
IGMPLastMemberQueryInterval	The maximum time (ms) until a host/client has to send an answer to a group and group-and-source specific query. (Default: 5000)
IGMPUnsolicitedReportInterval	The time between repetitions (ms) of an initial membership report. (Default: 1000)
IGMPRouterVersion	Multiple IGMP querying routers on a network must use the same IGMP version. (Default: IGMPv3)
IGMPLowestCompatibleVersion	Lowest IGMP compatibility mode. (Default: IGMPv1)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.89. NATPool

Description

A NAT Pool is used for NATing multiple concurrent connections to using different source IP addresses.

Properties

Name	Specifies a symbolic name for the NAT Pool. (Identifier)
Type	Specifies how NAT'ed connections are assigned a NAT IP address. (Default: stateful)
IPSource	Specify which IP Address source to use. (Default: IPRange)
IPPool	Specifies the IP Pool used for retrieving IP addresses for NAT translation.
IPPoolIPs	The number of IP addresses to get from the IP Pool.
IPRange	Specifies the range of IP addresses used for NAT translation.
StateKeepAlive	The number of seconds that stateful NAT state will be kept in absence of new connections. (Default: 120)
MaxStates	Maximum number of statefully tracked NATPool states. (Default: 16384)
ProxyARPAllInterfaces	Always select all interfaces, including new ones, for publishing routes needed for receiving traffic on NATPool addresses. (Default: No)
ProxyARPInterfaces	Specifies the interface/interfaces on which the security gateway should publish routes needed for the relay via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

3.90. OSPFProcess

Description

An OSPF Router Process defines a group of routers exchanging routing information via the Open Shortest Path First routing protocol.

Properties

Name	Specifies a symbolic name for the OSPF process. (Identifier)
RouterID	Specifies the IP address that is used to identify the router. If no router ID is configured, it will be computed automatically based on the highest IP address of any interface participating in the OSPF process. (Optional)
PrivRouterID	The private router ID of this high availability node. (Optional)
RFC1583	Enable this if the security gateway will be used in a environment that consists of routers that only support RFC 1583. (Default: No)
SPFHoldTime	Specifies the minimum time, in seconds, between two SPF calculations. (Default: 10)
SPFDelayTime	Specifies the delay time, in seconds, between when OSPF receives a topology change and when it starts a SPF calculation. (Default: 5)
LSAGroupPacing	This specifies the time in seconds at which interval the OSPF LSAs are collected into a group and refreshed. (Default: 10)
RoutesHoldtime	This specifies the time in seconds that the routing table will be kept unchanged after a reconfiguration of OSPF entries or a HA failover. (Default: 45)
RefBandwidthValue	Set the reference bandwidth that is used when calculating the default interface cost for routes. (Default: 1)
RefBandwidthUnit	Sets the reference bandwidth unit. (Default: Gbps)
MemoryMaxUsage	Maximum amount in bytes of RAM that the OSPF process is allowed to use. The default is one percent of installed RAM. Specifying 0 indicates that the OSPF process is allowed to use all available RAM. (Optional)
DebugPacket	Enables or disabled logging of general packet parsing events and also specifies the details of the log. (Default: Off)
DebugHello	Enables or disabled logging of hello packets and also specifies the details of the log. (Default: Off)

DebugDDesc	Enables or disabled logging of database description packets and also specifies the details of the log. (Default: Off)
DebugExchange	Enables or disabled logging of exchange packets and also specifies the details of the log. (Default: Off)
DebugLSA	Enables or disabled logging of LSA events and also specifies the details of the log. (Default: Off)
DebugSPF	Enables or disabled logging of SPF calculation events and also specifies the details of the log. (Default: Off)
DebugRoute	Enables or disabled logging of routing table manipulation events and also specifies the details of the log. (Default: Off)
AuthType	Specifies the authentication type for the OSPF protocol exchanges. (Default: None)
AuthPassphrase	Specifies the passphrase used for authentication. (Optional)
AuthMD5ID	Specifies the MD5 key ID used for MD5 digest authentication.
AuthMD5Key	A 128-bit key used to produce the MD5 digest. (Optional)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

3.90.1. OSPFArea

Description

An OSPF area is a sub-domain within the OSPF process which collects OSPF interfaces, neighbors, aggregates and virtual links.

Properties

Name	Specifies a symbolic name for the area. (Identifier)
AreaID	Specifies the area id, if 0.0.0.0 is specified this is the backbone area.
Stub	Enable to make the router automatically advertises a default route so that routers in the stub area can reach destinations outside the area. (Default: No)
StubSummarize	Become a default router for stub area (Summarize). (Default: Yes)

StubMetric	Route metric for stub area. (Optional)
FilterExternal	Specifies the network addresses allowed to be imported into this area from external routing sources. (Optional)
FilterInterArea	Specifies the network addresses allowed to be imported from other routers inside the area. (Optional)
Comments	Text describing the current object. (Optional)

3.90.1.1. OSPFInterface

Description

Select and define the properties of an interface that should be made a member of the Router Process.

Properties

Interface	Specifies which interface in the security gateway will be used for this OSPF interface. (Identifier)
Type	Auto, Broadcast, Point-to-point or Point-to-multipoint. (Default: Auto)
Network	Specifies the network related to the configured OSPF interface. (Optional)
MetricType	Metric value or Bandwidth. (Default: MetricValue)
Metric	Specifies the routing metric for this OSPF interface. (Default: 10)
BandwidthValue	Specifies the bandwidth for this OSPF interface.
BandwidthUnit	Specifies the bandwidth unit. (Default: Mbps)
UseDefaultAuth	Use the authentication configuration specified in the OSPF process. (Default: Yes)
AuthType	Specifies the authentication type for the OSPF protocol exchanges. (Default: None)
AuthPassphrase	Specifies the passphrase used for authentication. (Optional)
AuthMD5ID	Specifies the MD5 key ID used for MD5 digest authentication.
AuthMD5Key	A 128-bit key used to produce the MD5 digest. (Optional)
HelloInterval	Specifies the number of seconds between HELLO packets sent from the interface. (Default: 10)
RtrDeadInterval	If no HELLO packets are received from a neighbor within this interval (in seconds), that neighbor

	router will be declared to be down. (Default: 40)
RxmtInterval	Specifies the number of seconds between retransmissions of LSAs to neighbors on this interface. (Default: 5)
RtrPrio	Specifies the router priority, a higher number increases this routers chance of becoming DR or BDR, if 0 is specified this router will not be eligible in the DR/BDR election. (Default: 1)
InfTransDelay	Specifies the estimated transmit delay for the interface in seconds. This value represents the maximum time it takes to forward a LSA packet trough the router. (Default: 1)
WaitInterval	Specifies the number of seconds between the time when the interface brought up and the election of the DR and BDR. This value should be higher than the hello interval. (Default: 40)
Passive	Enable to make it possible to include networks into the OSPF routing process, without running OSPF on the interface connected to that network. (Default: No)
IgnoreMTU	Enable to allow OSPF MTU mismatches. (Default: No)
Comments	Text describing the current object. (Optional)

3.90.1.2. OSPFNeighbor

Description

For point-to-point and point-to-multipoint networks, specify the IP addresses of directly connected routers.

Properties

Interface	Specifies the OSPF interface of the neighbor.
IPAddress	IP Address of the neighbor.
Metric	Specifies the metric of the neighbor. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.90.1.3. OSPFAggregate

Description

An aggregate is used to replace any number of smaller networks belonging to the local (intra) area with one contiguous network which may then be advertised or hidden.

Properties

Network	The aggregate network used to combine several small routes.
Advertise	Advertise the aggregate. (Default: Yes)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.90.1.4. OSPFVLink**Description**

An area that does not have a direct connection to the backbone must have at least one area border router with a virtual link to a backbone router, or to another router with a link to the backbone.

Properties

Name	Specifies a symbolic name for the virtual link. (Identifier)
RouterID	The ID of the router on the other side of the virtual link.
UseDefaultAuth	Use the authentication configuration specified in the OSPF process. (Default: Yes)
AuthType	Specifies the authentication type for the OSPF protocol exchanges. (Default: None)
AuthPassphrase	Specifies the passphrase used for authentication. (Optional)
AuthMD5ID	Specifies the MD5 key ID used for MD5 digest authentication.
AuthMD5Key	A 128-bit key used to produce the MD5 digest. (Optional)
Comments	Text describing the current object. (Optional)

3.91. Pipe

Description

A pipe defines basic traffic shaping parameters. The pipe rules then determines which traffic goes through which pipes.

Properties

Name	Specifies a symbolic name for the pipe. (Identifier)
LimitKbpsTotal	Total bandwidth limit for this pipe in kilobits per second. (Optional)
LimitPPSTotal	Total packet per second limit for this pipe. (Optional)
LimitKbps0	Specifies the bandwidth limit in kbps for precedence 0 (the lowest precedence). (Optional)
LimitPPS0	Specifies the packet per second limit for precedence 0 (the lowest precedence). (Optional)
LimitKbps1	Specifies the bandwidth limit in kbps for precedence 1. (Optional)
LimitPPS1	Specifies the packet per second limit for precedence 1. (Optional)
LimitKbps2	Specifies the bandwidth limit in kbps for precedence 2. (Optional)
LimitPPS2	Specifies the packet per second limit for precedence 2. (Optional)
LimitKbps3	Specifies the bandwidth limit in kbps for precedence 3. (Optional)
LimitPPS3	Specifies the packet per second limit for precedence 3. (Optional)
LimitKbps4	Specifies the bandwidth limit in kbps for precedence 4. (Optional)
LimitPPS4	Specifies the packet per second limit for precedence 4. (Optional)
LimitKbps5	Specifies the bandwidth limit in kbps for precedence 5. (Optional)
LimitPPS5	Specifies the packet per second limit for precedence 5. (Optional)
LimitKbps6	Specifies the bandwidth limit in kbps for precedence 6. (Optional)
LimitPPS6	Specifies the packet per second limit for precedence 6. (Optional)
LimitKbps7	Specifies the bandwidth limit in kbps for

	precedence 7 (the highest precedence). (Optional)
LimitPPS7	Specifies the packet per second limit for precedence 7 (the highest precedence). (Optional)
UserLimitKbpsTotal	Total bandwidth limit per group in the pipe in kilobits per second. (Optional)
UserLimitPPSTotal	Total throughput limit per group in the pipe in packets per second. (Optional)
UserLimitKbps0	Specifies the bandwidth limit per group in kbps for precedence 0 (the lowest precedence). (Optional)
UserLimitPPS0	Specifies the throughput limit per group in PPS for precedence 0 (the lowest precedence). (Optional)
UserLimitKbps1	Specifies the bandwidth limit per group in kbps for precedence 1. (Optional)
UserLimitPPS1	Specifies the throughput limit per group in PPS for precedence 1. (Optional)
UserLimitKbps2	Specifies the bandwidth limit per group in kbps for precedence 2. (Optional)
UserLimitPPS2	Specifies the throughput limit per group in PPS for precedence 2. (Optional)
UserLimitKbps3	Specifies the bandwidth limit per group in kbps for precedence 3. (Optional)
UserLimitPPS3	Specifies the throughput limit per group in PPS for precedence 3. (Optional)
UserLimitKbps4	Specifies the bandwidth limit per group in kbps for precedence 4. (Optional)
UserLimitPPS4	Specifies the throughput limit per group in PPS for precedence 4. (Optional)
UserLimitKbps5	Specifies the bandwidth limit per group in kbps for precedence 5. (Optional)
UserLimitPPS5	Specifies the throughput limit per group in PPS for precedence 5. (Optional)
UserLimitKbps6	Specifies the bandwidth limit per group in kbps for precedence 6. (Optional)
UserLimitPPS6	Specifies the throughput limit per group in PPS for precedence 6. (Optional)
UserLimitKbps7	Specifies the bandwidth limit per group in kbps for precedence 7 (the highest precedence). (Optional)
UserLimitPPS7	Specifies the throughput limit per group in PPS for precedence 7 (the highest precedence). (Optional)
Grouping	Grouping enables per-port/IP/network static bandwidth limits as well as dynamic balancing between groups. (Default: None)

GroupingNetworkSize	If users are grouped according to source or destination network, the size of the network has to be specified by this setting. (Default: 0)
Dynamic	Enable dynamic balancing of groups. (Default: No)
PrecedenceMin	Specifies the lowest allowed precedence for traffic in this pipe. If a packet with a lower precedence enters, its precedence is raised to this value. (Default: 0)
PrecedenceDefault	Specifies the default precedence for the pipe. If a packet enters this pipe without a set precedence, it gets assigned this value. Should be higher than or equal to the minimum precedence. (Default: 0)
PrecedenceMax	Specifies the highest allowed precedence for traffic in this pipe. If a packet with a higher precedence enters, its precedence is lowered to this value. Should be higher than or equal to the default precedence. (Default: 7)
Comments	Text describing the current object. (Optional)

3.92. PipeRule

Description

A Pipe Rule determines traffic shaping policy - which Pipes to use - for one or more types of traffic with the same granularity as the standard ruleset.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the object. (Optional)
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
ForwardChain	Specifies one or more pipes to be used for forward traffic. (Optional)
ReturnChain	Specifies one or more pipes to be used for return traffic. (Optional)
Precedence	Specifies what precedence should be assigned to the packets before sent into a pipe. (Default: FromPipe)
FixedPrecedence	Specifies the fixed precedence.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.93. PPPoETunnel

Description

A PPPoE interface is a PPP (point-to-point protocol) tunnel over an existing physical Ethernet interface. Its IP address is dynamically assigned.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
EthernetInterface	The physical Ethernet interface that connects to the PPPoE server network.
IP	The host name to store the assigned IP address in.
Network	The network from which traffic should be routed into the tunnel.
DNS1	IP of the primary DNS server. (Optional)
DNS2	IP of the secondary DNS server. (Optional)
Username	Specifies the username to use for this PPPoE tunnel.
Password	The password to use for this PPPoE tunnel.
ServiceName	Specifies the PPPoE server service name used to distinguish between two or more PPPoE servers attached to the same network. (Optional)
PPPAuthNoAuth	Allow no authentication for this tunnel. (Default: No)
PPPAuthPAP	Use PAP authentication protocol for this tunnel. User name and password are sent in plaintext. (Default: Yes)
PPPAuthCHAP	Use CHAP authentication protocol for this tunnel. (Default: Yes)
PPPAuthMSCHAP	Use MS-CHAP authentication protocol for this tunnel. (Default: Yes)
PPPAuthMSCHAPv2	Use MS-CHAP v2 authentication protocol for this tunnel. (Default: Yes)
DialOnDemand	Enable Dial-on-demand which means that the PPPoE tunnel will not be setup until traffic is sent on the interface. (Default: No)
ActivitySensing	Specifies if the dial-on-demand should trigger on inbound or outbound traffic or both. (Default: BiDirectional)
IdleTimeout	Idle timeout in seconds for dial-on-demand. (Default: 3600)

Metric	Specifies the metric for the auto-created route. (Default: 90)
AutoInterfaceNetworkRoute	Automatically add a route for this interface using the given remote network. (Default: Yes)
Schedule	The schedule defines when the PPPoE tunnel should be active. (Optional)
ForceUnnumbered	Force the PPPoE tunnel to be unnumbered. (Default: No)
SpecifyManually	Make it possible to manually specify IP Address object. (Default: No)
MTU	Specifies the size (in bytes) of the largest packet that can be passed onward. (Default: 1492)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.94. PPPSettings

Description

Settings related to the PPP protocol.

Properties

InitialResendTime

Initial time in milliseconds to wait before sending a new configuration request if no server response is received. (Default: 200)

PPP_MaxResends

The maximum number of PPP layer resends. (Default: 10)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.95. PSK

Description

PSK (Pre-Shared Key) authentication is based on a shared secret that is known only by the parties involved.

Properties

Name	Specifies a symbolic name for the pre-shared key. (Identifier)
Type	Specifies the type of the shared key.
PSKAscii	Specifies the PSK as a passphrase.
PSKHex	Specifies the PSK as a hexadecimal key.
Comments	Text describing the current object. (Optional)

3.96. R8139EthernetPCIDriver

Description

RealTek (8139) Fast Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.97. R8169EthernetPCIDriver

Description

RealTek (8169,8110) Gigabit Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.98. RadiusAccounting

Description

External RADIUS server used to collect user statistics.

Properties

Name	Specifies a symbolic name for the server. (Identifier)
IPAddress	The IP address of the server.
Port	The UDP port of the server. (Default: 1813)
RetryTimeout	The retry timeout, in seconds, used when trying to contact the RADIUS accounting server. If no response has been given after for example 2 seconds, the security gateway will try again by sending a new AccountingRequest packet. (Default: 2)
SharedSecret	The shared secret phrase for the Authenticator generation.
SourceIPSelection	Which IP should be used as a source IP. (Default: Automatic)
SourceIP	The IP address to be used as source IP.
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.99. RadiusRelay

Description

RADIUS relay for intercepting packets from a user endpoint and sending packets to a remote RADIUS server.

Properties

Name	Specifies a symbolic name for the relay. (Identifier)
SourceInterface	Specifies the name of the receive interface for RADIUS relay requests.
ClientIPFilter	Specifies the network that the AP belongs to.
ListeningIP	Specifies the local IP address on which the system receives Access Point requests. This parameter is optional and will use IP of source interface, if not set. (Optional)
ListeningPort	Specifies the listening port on which the system receives Access Point requests. (Default: 1812)
RemoteServerIP	Specifies the IP address of the remote RADIUS server.
RemoteServerPort	Specifies the port of the remote RADIUS server. (Default: 1812)
SendingIP	Specifies the local IP address from which the system sends requests to the remote Remote RADIUS server. This parameter is optional and will use IP of routed destination interface, if not set. (Optional)
IdleTimeout	A successfully authenticated user will be logged out automatically after this many seconds, if no traffic has been received from the user's IP address. (Default: 1800)
SessionTimeout	A successfully authenticated user will be logged out automatically after this many seconds, even if traffic has been received from the user's IP address. (Default: 0)
UseServerTimeouts	Use timeouts received from the authentication server. If no values are received, the manually specified values will be used. (Default: No)
DHCPServer	Specifies the DHCP server rule that is responsible for distributing leases for authenticated users.
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)

RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.100. RadiusServer

Description

External RADIUS server used to verify user names and passwords.

Properties

Name	Specifies a symbolic name for the server. (Identifier)
IPAddress	The IP address of the server.
Port	The UDP port of the server. (Default: 1812)
RetryTimeout	The retry timeout, in seconds, used when trying to contact the RADIUS server. If no response has been given after for example 2 seconds, the security gateway will try again by sending a new Access-Request packet. (Default: 2)
SharedSecret	The shared secret phrase for the Authenticator generation.
SourceIPSelection	Which IP should be used as a source IP. (Default: Automatic)
SourceIP	The IP address to be used as source IP.
RoutingTable	Specifies the routing table the clients host route should be added to. (Default: main)
Comments	Text describing the current object. (Optional)

3.101. RealTimeMonitorAlert

Description

Monitors a statistical value. Log messages are generated if the value goes below the lower threshold or above the high threshold.

Properties

Index	The index of the object, starting at 1. (Identifier)
Monitor	Statistical value.
SampleTime	Interval in seconds between checking the statistic. (Optional)
LowThreshold	Log if statistical value goes below this threshold. (Optional)
HighThreshold	Log if statistical value goes above this threshold. (Optional)
BackoffInterval	The minimum number of seconds between consecutive log messages. (Default: 60)
Continuous	If set, generate event if the value goes from being outside the threshold values, back to within acceptable limits again. (Default: No)
LogMessageID	ID of generated log messages. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.102. RemoteIDList

Description

List of Remote IDs that are allowed access when using Pre Shared Keys as authentication method.

Properties

Type	Specifies the type of the shared key.
PSKAscii	Specifies the PSK as a passphrase.
PSKHex	Specifies the PSK as a hexadecimal key.
IDType	Selects the type of remote identity to use.
IDValue	Specify the remote identity of the tunnel ID.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.103. RemoteMgmtHTTP

Description

Configure HTTP/HTTPS management to enable remote management to the system.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
Interface	Specifies the interface for which remote access is granted.
HTTP	Enable remote management via HTTP. (Default: No)
HTTPS	Enable remote management via HTTPS. (Default: No)
AuthSource	Optionally enable authentication from an external source. Note that a Local User Database must ALWAYS be configured to prevent administrative lockout in cases where the external source may not be available. (Default: LocalOnly)
AuthOrder	Specifies if the local database should be queried before or after the external database. (Default: LocalLast)
LocalUserDatabase	Specifies the local user database to use for login.
AccessLevel	Optionally restrict the access level of users authenticated by the local database. (Default: Admin)
RadiusServers	Specifies the authentication servers that will be used to authenticate users matching this rule.
RadiusMethod	Specifies the authentication method used for encrypting the user password. (Default: PAP)
ChallengeExpire	How long, in seconds, before RADIUS challenge expires. (Default: 160)
PrimaryRetryInterval	How many seconds to wait before trying to use the primary server again if it has failed. (Default: 0)
AdminGroups	Restricts administration access to specific user groups. (Optional)
AuditGroups	Restricts auditing access to specific user groups. (Optional)
Network	Specifies the network for which remote access is granted.
Comments	Text describing the current object. (Optional)

3.104. RemoteMgmtNetcon

Description

Configure Netcon management to enable remote management to the system.

Properties

Name	Specifies a symbolic name for the object. (Default: NetconMgmt)
Interface	Specifies the interface for which remote access is granted.
Mode	Configure, Console or Uptimepoll. (Default: Configure)
IdleTimeout	Number of seconds of inactivity until the Netcon console user is automatically logged out. (Default: 900)
Key	64 byte Netcon PSK.
Network	Specifies the network for which remote access is granted.
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.105. RemoteMgmtSettings

Description

Setup and configure methods and permissions for remote management of this system.

Properties

NetconBiDirTimeout	Specifies the amount of seconds to wait for the administrator to log in before reverting to the previous configuration. (Default: 30)
WebUIBeforeRules	Enable HTTP(S) traffic to the security gateway regardless of configured IP Rules. (Default: Yes)
WWWsrv_HTTPPort	Specifies the HTTP port for the web user interface. (Default: 80)
WWWsrv_HTTPSPort	Specifies the HTTPS port for the web user interface. (Default: 443)
WebUIAllowLoginAutoComplete	Allow the web browser to remember the username and password on the login page. (Default: Yes)
SSHBeforeRules	Enable SSH traffic to the security gateway regardless of configured IP Rules. (Default: Yes)
HTTSPCertificate	Specifies host certificate to use for HTTPS traffic. Only RSA certificates are supported. (Optional)
HTTSPRootCertificates	Specifies eventual root certificates to use for HTTPS traffic. (Optional)
NetconBeforeRules	Enable netcon traffic to the security gateway regardless of configured IP Rules. (Default: Yes)
NetConMaxChannels	The maximum number of concurrent Netcon channels. The Netcon channels consists of the following: console, realtime logger, stat poll or send/receive file context. (Default: 18)
SNMPBeforeRules	Enable SNMP traffic to the security gateway regardless of configured IP Rules. (Default: Yes)
SNMPRequestLimit	Maximum number of SNMP packets that will be processed each second. (Default: 100)
SNMPSysContact	The contact person for this managed node. (Default: N/A)
SNMPSysName	The name for this managed node. (Default: N/A)
SNMPSysLocation	The physical location of this node. (Default: N/A)
SNMPIfDescription	What to display in the SNMP MIB-II ifDescr variables. (Default: Name)
SNMPIfAlias	What to display in the SNMP ifMIB ifAlias variables. (Default: Hardware)

LocalConsoleIdleTimeout	Number of seconds of inactivity until the local console user is automatically logged out. (Default: 900)
WebUIIdleTimeout	Number of seconds of inactivity until the HTTP(S) session is closed. (Default: 900)
NetconIdleTimeout	Number of seconds of inactivity until the Netcon session is close. (Default: 600)

**Note**

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.106. RemoteMgmtSNMP

Description

Configure SNMP management to enable SNMP polling.

Properties

Name	Specifies a symbolic name for the object. (Identifier)
Interface	Specifies the interface for which remote access is granted.
SNMPGetCommunity	Specifies the name of the community to be granted rights to remotely monitor the security gateway.
Network	Specifies the network for which remote access is granted.
Comments	Text describing the current object. (Optional)

3.107. RemoteMgmtSSH

Description

Configure a Secure Shell (SSH) Server to enable remote management access to the system.

Properties

Name	Specifies a symbolic name for the SSH server. (Identifier)
Interface	Specifies the interface for which remote access is granted.
Port	The listening port for the SSH server. (Default: 22)
AllowAuthMethodPassword	Allow password client authentication. (Default: Yes)
AllowAuthMethodPublicKey	Allow public key client authentication. (Default: Yes)
AllowHostKeyDSA	Allow DSA public key algorithm. (Default: Yes)
AllowHostKeyRSA	Allow RSA public key algorithm. (Default: Yes)
AllowKexDH14	Allow Diffie-Hellman Group 14 key exchange algorithm. (Default: Yes)
AllowKexDH1	Allow Diffie-Hellman Group 1 key exchange algorithm. (Default: Yes)
AllowAES128	Allow AES-128 encryption algorithm. (Default: Yes)
AllowAES192	Allow AES-192 encryption algorithm. (Default: Yes)
AllowAES256	Allow AES-256 encryption algorithm. (Default: Yes)
AllowBlowfish	Allow Blowfish encryption algorithm. (Default: Yes)
Allow3DES	Allow 3DES encryption algorithm. (Default: Yes)
AllowMACSHA1	Allow SHA1 integrity algorithm. (Default: Yes)
AllowMACMD5	Allow MD5 integrity algorithm. (Default: Yes)
AllowMACSHA196	Allow SHA1-96 integrity algorithm. (Default: Yes)
AllowMACMD596	Allow MD5-96 integrity algorithm. (Default: Yes)
Banner	Specifies the greeting message to display when the user logs in. (Optional)
MaxSessions	The maximum number of clients that can be connected at the same time. (Default: 5)
SessionIdleTime	The number of seconds a user can be idle before the session is closed. (Default: 1800)
LoginGraceTime	When the user has supplied the username, the

	password has to be provided within this number of seconds or the session will be closed. (Default: 30)
AuthenticationRetries	The number of retries allowed before the session is closed. (Default: 3)
AuthSource	Optionally enable authentication from an external source. Note that a Local User Database must ALWAYS be configured to prevent administrative lockout in cases where the external source may not be available. (Default: LocalOnly)
AuthOrder	Specifies if the local database should be queried before or after the external database. (Default: LocalLast)
LocalUserDatabase	Specifies the local user database to use for login.
AccessLevel	Optionally restrict the access level of users authenticated by the local database. (Default: Admin)
RadiusServers	Specifies the authentication servers that will be used to authenticate users matching this rule.
RadiusMethod	Specifies the authentication method used for encrypting the user password. (Default: PAP)
ChallengeExpire	How long, in seconds, before RADIUS challenge expires. (Default: 160)
PrimaryRetryInterval	How many seconds to wait before trying to use the primary server again if it has failed. (Default: 0)
AdminGroups	Restricts administration access to specific user groups. (Optional)
AuditGroups	Restricts auditing access to specific user groups. (Optional)
Network	Specifies the network for which remote access is granted.
Comments	Text describing the current object. (Optional)

3.108. RouteBalancingInstance

Description

A route balancing instance is associated with a routingtable and defines how to make use of multiple routes to the same destination.

Properties

RoutingTable	Specify routingtable to deploy route load balancing in. (Identifier)
Algorithm	Specify which algorithm to use when balancing the routes. (Default: RoundRobin)
Comments	Text describing the current object. (Optional)

3.109. RouteBalancingSpilloverSettings

Description

Settings associated with the spillover algorithm.

Properties

Interface	Interface to threshold limit. (Identifier)
HoldTime	Number of consecutive seconds over/under the threshold limit to trigger state change for the affected routes. (Default: 30)
OutboundThreshold	Outbound threshold limit. (Optional)
OutboundUnit	The outbound units. (Default: kbps)
InboundThreshold	Inbound threshold limit. (Optional)
InboundUnit	The inbound units. (Default: kbps)
Comments	Text describing the current object. (Optional)

3.110. RouterAdvertisement

Description

Enabling Router Advertisement will answer Solicitations and periodically send out Advertisements. Stateless address autoconfiguration (SLAAC) will only work correctly if the configured network prefix is 64 (RFC4862).

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the Router Advertisement.
Interface	Specifies the name of the interface to advertise on.
UseGlobalRASettings	Use global RA advanced settings. (Default: Yes)
RAMaxInterval	Maximum time between sending unsolicited multicast Router Advertisement. (Default: 600s). (Default: 600)
RAMinInterval	Minimum time between sending unsolicited multicast Router Advertisement. Will be automatically adjusted if set to less than 3 seconds or greater than $.75 * \text{Max RA Interval}$. (Default: 200)
RAAutoLifetime	Auto adjust the Router Lifetime field using the following formula; $3 * \text{MaxRtrAdvInterval}$. (Default: Yes)
RADefaultLifetime	The value to be placed in the Router Lifetime field of Router Advertisements sent from the SGW, in seconds. (Default: 1800s). (Default: 1800)
RAReachableTime	The value to be placed in the Reachable Time field in the Router Advertisement messages SGW. The value zero means unspecified. (Default: 0s). (Default: 0)
RARetransTimer	The value to be placed in the Retrans Timer field in the Router Advertisement messages sent by the SGW. The value zero means unspecified. (Default: 0s). (Default: 0)
RAManagedFlag	Indicates that addresses are available via DHCPv6. (Default: False). (Default: No)
RAOtherConfigFlag	Indicates that other configuration information is available via DHCPv6. (Default: False). (Default: No)
RACurHopLimit	The default value to be placed in the Cur Hop Limit field in the Router Advertisement messages sent by the SGW. The value zero means unspecified. (Default: 64). (Default: 64)
RALinkMTU	The value to be placed in MTU options sent. A value of zero indicates that no MTU options are

sent. (Default: 0). (Default: 0)

Comments

Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.110.1. RA_PrefixInformation

Description

Specifies a Router Advertisement Prefix Information option.

Properties

Name Specifies a symbolic name for the Prefix Information.

Prefix Specifies the network prefix.

RAValidLifetime The value to be placed in the Valid Lifetime in the Prefix Information option. The value of 999999999 represents infinity. (Default: 2592000s). (Default: 2592000)

RAPreferredLifetime The value to be placed in the Preferred Lifetime in the Prefix Information option. The value of 999999999 represents infinity. (Default: 604800s). (Default: 604800)

RAOnLinkFlag Indicates that the advertised prefix can be used for on-link determination. (Default: True). (Default: Yes)

RAAutonomousFlag Indicates that the advertised prefix can be used for stateless address configuration. (Default: True). (Default: Yes)

Comments

Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.111. RoutingRule

Description

A Routing Rule forces the use of a routing table in the forward and/or return direction of traffic on a connection. The ordering parameter of the routing table determines if it is consulted before or after the main routing table.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
ForwardRoutingTable	The forward routing table will be used for packets from the connection originator to the connection endpoint.
ReturnRoutingTable	The return routing table will be used for packets traveling in the reverse direction.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
SourceInterface	Specifies the name of the source interface to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.112. RoutingSettings

Description

Configure the routing capabilities of the system.

Properties

RouteFailOver_IfacePollInterval	Time (ms) between polling of interface failure. (Default: 500)
RouteFailOver_ARPPollInterval	Time (ms) between ARP-lookup of gateways. May be overridden for each route. (Default: 1000)
RouteFailOver_PingPollInterval	Time (ms) between PING'ing of gateways. (Default: 1000)
RouteFailOver_GraceTime	Time (s) between startup/reconfigure and monitoring start. (Default: 30)
RouteFailOver_ConsecFails	Number of consecutive failures before route is marked as unavailable. (Default: 5)
RouteFailOver_ConsecSuccess	Number of consecutive success before route is marked as available. (Default: 5)
Transp_CAMToL3CDestLearning	Do L3 Cache learning based on destination IPs and MACs in combination with CAM table contents. (Default: Yes)
Transp_DecrementTTL	Decrement TTL on packets forwarded between transparent interfaces. (Default: No)
Transp_CAMSize_Dynamic	Allocate the CAM Size value dynamically. (Default: Yes)
Transp_CAMSize	Maximum number of entries in each CAM table. (Default: 8192)
Transp_L3CSize_Dynamic	Allocate the L3 Cache Size value dynamically. (Default: Yes)
Transp_L3CSize	Maximum number of entries in each Layer 3 Cache. (Default: 8192)
Transp_RelaySTP	Relay Spanning-Tree (STP, RSTP and MSTP) Bridge Protocol Data Units to all switch interfaces. (Default: Drop)
Transp_RelayMPLS	Forward MPLS packets to all switch interfaces. (Default: Drop)
RFO_GratuitousARPOnFail	Send gratuitous ARP on failover to alert hosts about changed interface ethernet and IP addresses. (Default: Yes)
RFO_GratuitousProxyARPOnFail	Send gratuitous ARP packets on failover to alert hosts about changed interface ethernet address of Proxy ARPed hosts in ARP cache. (Default: No)

Transparency_ATSExpire	Lifetime of an unanswered ATS entry in seconds. (Default: 3)
Transparency_ATSSize	Number of ATS entries, total. (Default: 4096)
NullEnetSender	Action to take if sender MAC in the ethernet header is the null address (0000:0000:0000). (Default: DropLog)
BroadcastEnetSender	Action to take if sender MAC in the ethernet header is the broadcast ethernet address (FFFF:FFFF:FFFF). (Default: DropLog)
MulticastEnetSender	Action to take if sender MAC in the ethernet header is a multicast ethernet address. (Default: DropLog)

**Note**

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.113. RoutingTable

Description

The system has a predefined main routing table. Alternate routing tables can be defined by the user.

Properties

Name	Specifies a symbolic name for the routing table. (Identifier)
Ordering	Specifies how a route lookup is done in a named routing table. (Default: Only)
RemoveInterfaceIPRoutes	Removes the interface routes. Makes the security gateway completely transparent. (Default: No)
Comments	Text describing the current object. (Optional)

3.113.1. Route

Description

A route defines what interface and gateway to use in order to reach a specified network.

Properties

Name	Specifies a symbolic name for the object. (Optional)
Interface	Specifies which interface packets destined for this route shall be sent through.
Gateway	Specifies the IP address of the next router hop used to reach the destination network. If the network is directly connected to the security gateway interface, no gateway address is specified. (Optional)
LocalIP	The IP address specified here will be automatically published on the corresponding interface. This address will also be used as the sender address in ARP queries. If no address is specified, the security gateway's interface IP address will be used. (Optional)
Network	Specifies the network address for this route.
RouteMonitor	Specifies if this route should be monitored for route changes for route failover purposes. (Default: No)
MonitorLinkStatus	Mark the route as down if the interface link status changes to down. (Default: No)

MonitorGateway	Mark the route as down if the next hop does not answer on ARP lookups during a specified time. (Default: No)
MonitorGatewayManualARP	Enable a manually specified ARP lookup interval. (Default: No)
MonitorGatewayARPInterval	Specifies the ARP lookup interval in milliseconds. (Default: 1000)
EnableHostMonitoring	Enables the Host Monitoring functionality. (Default: No)
Reachability	Specifies the number of hosts that are required to be reachable to consider the route to be active. (Default: ALL)
GracePeriod	Specifies the time to wait after a reconfiguration until the monitoring begins. (Default: 5)
ReachabilityCount	Minimum number of reachable hosts to consider the route to be active.
Metric	Specifies the metric for this route. (Default: 100)
ProxyARPAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.113.1.1. MonitoredHost

Description

Specify a host and a monitoring method.

Properties

Method	Monitoring method. (Default: ICMP)
IPAddress	Specifies the IP address of the host to monitor.
Port	Specifies the TCP port to monitor.
PollingInterval	Delay in milliseconds between each monitor attempt. (Default: 10000)
ReachabilityRequired	Specifies if this host is required to be reachable for

	monitoring to be successful. (Default: No)
Samples	Specifies the number of attempts to use for statistical calculations. (Default: 10)
MaxPollFails	Specifies the maximum number of failed attempts until host is considered to be unreachable. (Default: 2)
MaxAverageLatency	Specifies the max average latency for the sample attempts. (Default: 800)
RequestURL	Specifies the HTTP URL to monitor.
ExpectedResponse	Expected HTTP response.
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.113.2. Route6

Description

A route defines what interface and gateway to use in order to reach a specified network.

Properties

Name	Specifies a symbolic name for the object. (Optional)
Network	Specifies the network address for this route.
Interface	Specifies which interface packets destined for this route shall be sent through.
Gateway	Specifies the IPv6 address of the next router hop used to reach the destination network. If the network is directly connected to the security gateway interface, no gateway address is specified. (Optional)
LocalIP	The IPv6 address specified here will be automatically published on the corresponding interface. This address will also be used as the sender address in ARP queries. If no address is specified, the security gateway's interface IPv6 address will be used. (Optional)
Metric	Specifies the metric for this route. (Default: 100)
ProxyNDAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy Neighbor Discovery.

	(Default: No)
ProxyNDInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.113.3. SwitchRoute

Description

A switch route defines which interfaces the specified network can be reached on. Proxy ARP defines between which interfaces ARP is allowed.

Properties

Name	Specifies a symbolic name for the object. (Optional)
Interface	Specifies which interface packets destined for this route shall be sent through.
Network	Specifies the network address for this route.
Metric	Specifies the metric for this route. (Default: 100)
ProxyARPAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.114. ScheduleProfile

Description

A Schedule Profile defines days and dates and are then used by the various policies in the system.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
Mon	Specifies during which intervals the schedule profile is active on Mondays. (Optional)
Tue	Specifies during which intervals the schedule profile is active on Tuesdays. (Optional)
Wed	Specifies during which intervals the schedule profile is active on Wednesdays. (Optional)
Thu	Specifies during which intervals the schedule profile is active on Thursdays. (Optional)
Fri	Specifies during which intervals the schedule profile is active on Fridays. (Optional)
Sat	Specifies during which intervals the schedule profile is active on Saturdays. (Optional)
Sun	Specifies during which intervals the schedule profile is active on Sundays. (Optional)
StartDate	The date after which this Schedule should be active. (Optional)
EndDate	The date after which this Schedule is not active anymore. (Optional)
Comments	Text describing the current object. (Optional)

3.115. ServiceGroup

Description

A Service Group is a collection of service objects, which can then be used by different policies in the system.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
Members	Group members.
Comments	Text describing the current object. (Optional)

3.116. ServiceICMP

Description

An ICMP Service is an object definition representing ICMP traffic with specific parameters.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
MessageTypes	Specifies the ICMP message types that are applicable to this service. (Default: All)
EchoRequest	Enable matching of Echo Request messages. (Default: No)
EchoRequestCodes	Specifies which Echo Request message codes should be matched. (Default: 0-255)
DestinationUnreachable	Enable matching of Destination Unreachable messages. (Default: No)
DestinationUnreachableCodes	Specifies which Destination Unreachable message codes should be matched. (Default: 0-255)
Redirect	Enable matching of Redirect messages. (Default: No)
RedirectCodes	Specifies which Redirect message codes should be matched. (Default: 0-255)
ParameterProblem	Enable matching of Parameter Problem messages. (Default: No)
ParameterProblemCodes	Specifies which Parameter Problem message codes should be matched. (Default: 0-255)
EchoReply	Enable matching of Echo Reply messages. (Default: No)
EchoReplyCodes	Specifies which Echo Reply message codes should be matched. (Default: 0-255)
SourceQuenching	Enable matching of Source Quenching messages. (Default: No)
SourceQuenchingCodes	Specifies which Source Quenching message codes should be matched. (Default: 0-255)
TimeExceeded	Enable matching of Time Exceeded messages. (Default: No)
TimeExceededCodes	Specifies which Time Exceeded message codes should be matched. (Default: 0-255)
PassICMPReturn	Enable passing an ICMP error message only if it is related to an existing connection using this service. (Default: No)

Protocol	Protocol settings are only used by IP Policies. (Optional)
MaxSessionsProtocol	Specifies how many concurrent sessions that are permitted using this Protocol. (Default: 200)
ALG	An Application Layer Gateway (ALG), capable of managing advanced protocols, can be specified for this service. (Optional)
MaxSessions	Specifies how many concurrent sessions that are permitted using this service. (Default: 200)
Comments	Text describing the current object. (Optional)

3.117. ServiceICMPv6

Description

An IPv6-ICMP Service is an object definition representing IPv6-ICMP traffic with specific parameters.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
MessageTypes	Specifies the IPv6-ICMP message types that are applicable to this service. (Default: All)
EchoRequest	Enable matching of Echo Request messages. (Default: No)
EchoRequestCodes	Specifies which Echo Request message codes should be matched. (Default: 0-255)
EchoReply	Enable matching of Echo Reply messages. (Default: No)
EchoReplyCodes	Specifies which Echo Reply message codes should be matched. (Default: 0-255)
DestinationUnreachable	Enable matching of Destination Unreachable messages. (Default: No)
DestinationUnreachableCodes	Specifies which Destination Unreachable message codes should be matched. (Default: 0-255)
PacketTooBig	Enable matching of Packet Too Big messages. (Default: No)
PacketTooBigCodes	Specifies which Packet Too Big message codes should be matched. (Default: 0-255)
TimeExceeded	Enable matching of Time Exceeded messages. (Default: No)
TimeExceededCodes	Specifies which Time Exceeded message codes should be matched. (Default: 0-255)
ParameterProblem	Enable matching of Parameter Problem messages. (Default: No)
ParameterProblemCodes	Specifies which Parameter Problem message codes should be matched. (Default: 0-255)
PassICMPReturn	Enable passing an ICMP error message only if it is related to an existing connection using this service. (Default: No)
Protocol	Protocol settings are only used by IP Policies. (Optional)
MaxSessionsProtocol	Specifies how many concurrent sessions that are permitted using this Protocol. (Default: 200)

ALG	An Application Layer Gateway (ALG), capable of managing advanced protocols, can be specified for this service. (Optional)
MaxSessions	Specifies how many concurrent sessions that are permitted using this service. (Default: 200)
Comments	Text describing the current object. (Optional)

3.118. ServiceIPProto

Description

An IP Protocol Service is a definition of an IP protocol with specific parameters.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
IPProto	IP protocol number or range, e.g. "1-4,7" will match the protocols ICMP, IGMP, GGP, IP-in-IP and CBT. (Default: 0-255)
PassICMPReturn	Enable passing an ICMP error message only if it is related to an existing connection using this service. (Default: No)
Protocol	Protocol settings are only used by IP Policies. (Optional)
MaxSessionsProtocol	Specifies how many concurrent sessions that are permitted using this Protocol. (Default: 200)
ALG	An Application Layer Gateway (ALG), capable of managing advanced protocols, can be specified for this service. (Optional)
MaxSessions	Specifies how many concurrent sessions that are permitted using this service. (Default: 200)
Comments	Text describing the current object. (Optional)

3.119. ServiceTCPUDP

Description

A TCP/UDP Service is a definition of an TCP or UDP protocol with specific parameters.

Properties

Name	Specifies a symbolic name for the service. (Identifier)
DestinationPorts	Specifies the destination port or the port ranges applicable to this service.
Type	Specifies whether this service uses the TCP or UDP protocol or both. (Default: TCP)
SourcePorts	Specifies the source port or the port ranges applicable to this service. (Default: 0-65535)
SYNRelay	Enable SYN flood protection (SYN Relay). (Default: No)
PassICMPReturn	Enable passing an ICMP error message only if it is related to an existing connection using this service. (Default: No)
Protocol	Protocol settings are only used by IP Policies. (Optional)
MaxSessionsProtocol	Specifies how many concurrent sessions that are permitted using this Protocol. (Default: 200)
ALG	An Application Layer Gateway (ALG), capable of managing advanced protocols, can be specified for this service. (Optional)
MaxSessions	Specifies how many concurrent sessions that are permitted using this service. (Default: 200)
Comments	Text describing the current object. (Optional)

3.120. SSHClientKey

Description

The public key of the client connecting to the SSH server.

Properties

Name	Specifies a symbolic name for the key. (Identifier)
Type	DSA or RSA. (Default: DSA)
Subject	Value of the Subject header tag of the public key file. (Optional)
PublicKey	Specifies the public key.
Comments	Text describing the current object. (Optional)

3.121. SSLSettings

Description

Settings related to SSL (Secure Sockets Layer).

Properties

SSL_ProcessingPriority	The amount of of CPU time that SSL processing is allowed to use. (Default: Normal)
TLS_RSA_WITH_3DES_168_SHA1	Enable cipher RSA_WITH_3DES_168_SHA1. (Default: Yes)
TLS_RSA_WITH_RC4_128_SHA1	Enable cipher RSA_WITH_RC4_128_SHA1. (Default: Yes)
TLS_RSA_WITH_RC4_128_MD5	Enable cipher TLS_RSA_WITH_RC4_128_MD5. (Default: Yes)
TLS_RSA_EXPORT1024_WITH_RC4_56_SHA1	Enable cipher TLS_RSA_EXPORT1024_WITH_RC4_56_SHA1. (Default: Yes)
TLS_RSA_EXPORT512_WITH_RC4_40_MD5	Enable cipher TLS_RSA_EXPORT1024_WITH_RC4_40_MD5. (Default: No)
TLS_RSA_EXPORT512_WITH_RC2_40_MD5	Enable cipher TLS_RSA_EXPORT1024_WITH_RC2_40_MD5. (Default: No)
TLS_RSA_EXPORT_WITH_NULL_SHA1	Enable cipher TLS_RSA_EXPORT_WITH_NULL_SHA1 (no encryption, just message validation). (Default: No)
TLS_RSA_EXPORT_WITH_NULL_MD5	Enable cipher TLS_RSA_EXPORT_WITH_NULL_MD5 (no encryption, just message validation). (Default: No)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.122. SSLVPNInterface

Description

An SSL VPN interface, together with the bundled client, creates an easy to use tunnel solution for roaming users.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
OuterInterface	The physical interface that the SSL VPN interface will listen on.
ServerPort	The listening port for the SSL VPN interface. (Default: 443)
ServerIP	Listening IP for the SSL VPN interface.
ServerFQDN	Optional. FQDN of the SSL VPN server given to clients, eg: (sslvpn.example.com). (Optional)
IPAddressPool	A range, group or network that will be the IP pool from which the SSL VPN clients will receive their IP addresses.
InnerIP	Local IP for the SSL VPN interface.
PrimaryDNS	IP of the primary DNS Server. (Optional)
SecondaryDNS	IP of the secondary DNS Server. (Optional)
Routing	Describes how the traffic from the client should be routed. (Default: All-Nets)
ClientRoutes	Networks to be routed through the SSL VPN tunnel in the client.
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
ProxyARPAllInterfaces	Always select all interfaces, including new ones, for publishing routes via Proxy ARP. (Default: No)
ProxyARPInterfaces	Specifies the interfaces on which the security gateway should publish routes via Proxy ARP. (Optional)
Comments	Text describing the current object. (Optional)

3.123. SSLVPNInterfaceSettings

Description

SSL VPN interface settings.

Properties

SSLVPNBeforeRules

Pass SSL VPN connections sent to the security gateway directly to the SSL VPN engine without consulting the ruleset. (Default: Yes)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.124. ST201EthernetPCIDriver

Description

D-Link (ST201) Fast Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.125. StateSettings

Description

Parameters for the state engine in the system.

Properties

ConnReplace	What to do when the connection table is full. (Default: ReplaceLog)
LogOpenFails	Log packets that are neither part of open connections nor valid new connections. (Default: Yes)
LogReverseOpens	Log reverse connection attempts through an established connection. (Default: Yes)
LogStateViolations	Log packets that violate stateful tracking rules; for instance, TCP connect sequences. (Default: Yes)
LogConnections	Log connections opening and closing. (Default: Log)
LogConnectionUsage	Log for every packet that passes through a connection. (Default: No)
MaxConnections_Dynamic	Allocate the Max Connection value dynamically. (Default: Yes)
MaxConnections	Maximum number of simultaneous connections. (Default: 8192)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.126. TCPSettings

Description

Settings related to the TCP protocol.

Properties

TCPOptionSizes	Validity of TCP header option sizes. (Default: ValidateLogBad)
TCPMSSMin	Minimum allowed TCP MSS (Maximum Segment Size). (Default: 100)
TCPMSSOnLow	How to handle too low MSS values. (Default: DropLog)
TCPMSSMax	Maximum allowed TCP MSS (Maximum Segment Size). (Default: 1460)
TCPMSSVPNMax	Limits TCP MSS for VPN connections; minimizes fragmentation. (Default: 1400)
TCPMSSOnHigh	How to handle too high MSS values. (Default: Adjust)
TCPMSSLogLevel	When to log regarding too high TCP MSS, if not logged by "TCP MSS on high". (Default: 7000)
TCPMSSAutoClamping	Automatically clamp TCP MSS according to MTU of involved interfaces - in addition to "TCP MSS max". (Default: Yes)
TCPZeroUnusedACK	Force unused ACK fields to zero; helps prevent connection spoofing. (Default: Yes)
TCPZeroUnusedURG	Force unused URG fields to zero; prevents small information leak. (Default: Yes)
TCPOPT_WSOPT	The WSOPT (Window Scale) option (common). (Default: ValidateLogBad)
TCPOPT_SACK	The SACK/SACKPERMIT (Selective ACK) options (common). (Default: ValidateLogBad)
TCPOPT_TSOPT	The TSOPT (Timestamp) option (common). (Default: ValidateLogBad)
TCPOPT_ALTCHKREQ	The ALTCHKREQ (Alternate Checksum Request) option. (Default: StripLog)
TCPOPT_ALTCHKDATA	The ALTCHKDATA (Alternate Checksum Data) option. (Default: StripLog)
TCPOPT_CC	The CC (Connection Count) option series (semi common). (Default: StripLogBad)
TCPOPT_OTHER	How to handle TCP options not specified above. (Default: StripLog)

TCPSynUrg	The TCP URG flag together with SYN; normally invalid (strip=strip URG). (Default: DropLog)
TCPSynPsh	The TCP PSH flag together with SYN; normally invalid but always used by some IP stacks (strip=strip PSH). (Default: StripSilent)
TCPSynRst	The TCP RST flag together with SYN; normally invalid (strip=strip RST). (Default: DropLog)
TCPSynFin	The TCP FIN flag together with SYN; normally invalid (strip=strip FIN). (Default: DropLog)
TCPFinUrg	The TCP URG flag together with FIN; normally invalid (strip=strip URG). (Default: DropLog)
TCPUrg	The TCP URG flag; many operating systems cannot handle this correctly. (Default: StripLog)
TCPECN	The Explicit Congestion Notification (ECN) flags. Previously known as "XMAS"/"YMAS" flags. Also used in OS fingerprinting. (Default: StripLog)
TCPRF	The TCP Reserved field: should be zero. Used in OS fingerprinting. Also part of ECN extension. (Default: StripLog)
TCPNULL	TCP "NULL" packets without SYN, ACK, FIN or RST; normally invalid, used by scanners. (Default: DropLog)
TCPSequenceNumbers	Validation of TCP sequence numbers. (Default: ValidateLogBad)
TCPAllowReopen	Allow clients to re-open TCP connections that are in the closed state. (Default: No)

**Note**

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.127. ThresholdRule

Description

A Threshold Rule defines a filter for matching specific network traffic. When the filter criterion is met, the Threshold Rule Actions are evaluated and possible actions taken.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule. (Optional)
SourceInterface	Specifies the name of the receiving interface to be compared to the received packet.
SourceNetwork	Specifies the sender span of IP addresses to be compared to the received packet.
DestinationInterface	Specifies the the destination interface to be compared to the received packet.
DestinationNetwork	Specifies the span of IP addresses to be compared to the destination IP of the received packet.
Service	Specifies a service that will be used as a filter parameter when matching traffic with this rule.
Schedule	By adding a schedule to a rule, the security gateway will only allow that rule to trigger at those designated times. (Optional)
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.127.1. ThresholdAction

Description

A Threshold Rule Action specifies what thresholds to measure, and what action to take if those thresholds are reached.

Properties

Action	Protect or Audit. (Default: Protect)
GroupBy	Specifies whether the threshold should be host- or network-based. (Default: SourceIP)
Threshold	Specifies the threshold.

ThresholdUnit	Specifies the threshold unit. (Default: ConnsSec)
BlackList	Activate BlackList. (Default: No)
BlackListTimeToBlock	The number of seconds that the dynamic black list should remain. (Optional)
BlackListBlockOnlyService	Only block the service that triggered the blacklisting. (Default: No)
BlackListIgnoreEstablished	Do not drop existing connection. (Default: No)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.128. TulipEthernetPCIDriver

Description

Tulip Fast Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.129. UpdateCenter

Description

Configure automatic updates.

Properties

AVEnabled	Automatic updates of antivirus definitions and engine. (Default: No)
IDPEnabled	Automatic updates of IDP maintenance signatures. (Default: No)
AdvancedIDPEnabled	Automatic updates of Advanced IDP signatures. (Default: No)
UpdateInterval	Specifies the interval at which the automatic update runs. (Default: Daily)
UpdateDate	Specifies the day of month when the automatic update is runs.
UpdateWeekday	Specifies the day of week when the automatic update is runs. (Default: mon)
Hourly	Specifies the number of hours between periodical updates.
UpdateHour	Specifies the hour when the update is run. (Default: 0)
UpdateMinute	Specifies the minute when the update is run. (Default: 0)
CheckForPatchReleases	Enable notifications when a release with bug fixes for existing features is available. (Default: Yes)
CheckForFeatureReleases	Enable notifications when a release with new features is available. (Default: Yes)
Comments	Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.130. URLFilterPolicy

Description

Add a URL Filtering Profile that can be used by one or many IP Policies.

Properties

Name	Specifies a symbolic name for the Profile. (Identifier)
Comments	Text describing the current object. (Optional)

3.130.1. URLFilterPolicy_URL

Description

Blacklist URLs to deny access to complete sites, to file types by extension, or to URLs with certain words in them.

Properties

Action	Whitelist or Blacklist. (Default: Blacklist)
URL	Specifies the URL to blacklist or whitelist.
Comments	Text describing the current object. (Optional)



Note

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.131. UserAuthRule

Description

The User Authentication Ruleset specifies from where users are allowed to authenticate to the system, and how.

Properties

Index	The index of the object, starting at 1. (Identifier)
Name	Specifies a symbolic name for the rule.
Agent	ARPCache, HTTP, HTTPS, XAuth, PPP. (Default: HTTP)
ChallengeExpire	How long, in seconds, before RADIUS challenge expires. (Default: 160)
AuthSource	Disallow, LDAP, RADIUS or Local.
Interface	The interface on which the connection was received.
OriginatorIP	The network object that the incoming IP address must be a part of.
TerminatorIP	Specifies the destination IP configured on the PPTP/L2TP server configuration. Only used when agent is PPP or SSL. With SSL, this is the IP address of the listening interface.
RadiusServers	Specifies the authentication servers that will be used to authenticate users matching this rule.
PrimaryRetryInterval	How many seconds to wait before trying to use the primary server again if it has failed. (Default: 0)
ResendingSTART	If the RADIUS servers fail to respond system will retry to send a START message every Interim seconds. (Default: No)
LDAPServers	Specifies the authentication servers that will be used to authenticate users matching this rule.
RadiusMethod	Specifies the authentication method used for encrypting the user password. (Default: PAP)
LocalUserDB	Specifies the local user database that will be used to authenticate users matching this rule.
LoginType	HTML form or Basic authentication. (Default: HTMLForm)
MACAuthSecret	Password used to authenticate MAC user, if empty the MAC address will be sent as password. (Optional)
MACAllowRouter	Allow cliente connected through an Router. (Default: No)

HTTPBanners	HTTP Authentication HTML Banners. (Default: Default)
RealmString	The string that is presented as a part of the 401 - Authentication Required message. (Optional)
HostCertificate	Specifies the host certificate that the security gateway sends to the client. Only RSA certificates are supported.
RootCertificate	Specifies the root certificate that was used to sign the host certificate. Only RSA certificates are supported. (Optional)
PPPAuthNoAuth	Allow no authentication. (Default: No)
PPPAuthPAP	Use PAP authentication protocol. User name and password are sent in plaintext. (Default: Yes)
PPPAuthCHAP	Use CHAP authentication protocol. (Default: Yes)
PPPAuthMSCHAP	Use MS-CHAP authentication protocol. (Default: Yes)
PPPAuthMSCHAPv2	Use MS-CHAP v2 authentication protocol. (Default: Yes)
IdleTimeout	A successfully authenticated user will be logged out automatically after this many seconds, if no traffic has been received from the user's IP address. (Default: 1800)
SessionTimeout	A successfully authenticated user will be logged out automatically after this many seconds, even if traffic has been received from the user's IP address. (Optional)
UseServerTimeouts	Use timeouts received from the authentication server. If no values are received, the manually specified values will be used. (Default: No)
MultipleUsernameLogins	Specifies how multiple username logins will be handled. (Default: AllowMultiple)
ReplaceIdleTime	Replace existing user if idle for more than this number of seconds. (Default: 10)
AccountingServers	Specifies the accounting servers that will be used to report user usage matching this rule. (Optional)
PrimaryRetryIntervalAcc	How many seconds to wait before trying to use the primary server again if it has failed. (Default: 0)
BytesSent	Enable reporting of the number of bytes sent by the user. (Default: Yes)
PacketsSent	Enable reporting of the number of packets sent by the user. (Default: Yes)
BytesReceived	Enable reporting of the number of bytes received by the user. (Default: Yes)

PacketsReceived	Enable reporting of the number of packets received by the user. (Default: Yes)
SessionTime	Enable reporting of the number of seconds the session lasted. (Default: Yes)
SupportInterimAccounting	Enable Interim Accounting Messages to update the accounting server with the current status of an authenticated user. (Default: No)
ServerInterimControl	Let the RADIUS server determine the interval that interim accounting events should be sent. (Default: Yes)
InterimValue	The interval in seconds in which interim accounting events should be sent. (Default: 600)
LogEnabled	Enable logging. (Default: Yes)
LogSeverity	Specifies with what severity log events will be sent to the specified log receivers. (Default: Default)
Comments	Text describing the current object. (Optional)

**Note**

If no `Index` is specified when creating an instance of this type, the object will be placed last in the list and the `Index` will be equal to the length of the list.

3.132. VLAN

Description

Use a VLAN to define a virtual interface compatible with the IEEE 802.1Q / 802.1ad Virtual LAN standard.

Properties

Name	Specifies a symbolic name for the interface. (Identifier)
VLANID	The virtual LAN ID used for this virtual LAN interface. Two virtual LANs cannot have the same VLAN ID and type if they are based on the same interface. (Default: 0)
BaseInterface	Interface where this VLAN is being tunneled.
Type	VLAN type. (Default: 0x8100)
IP	The IP address of the virtual LAN interface.
Network	The network address of the virtual LAN interface.
DefaultGateway	The default gateway of the virtual LAN interface. (Optional)
Broadcast	The broadcast address of the virtual LAN interface. (Optional)
DHCPEnabled	Enable DHCP client on this interface. (Default: No)
DHCPHostName	Optional DHCP Host Name. Leave blank to use default name. (Optional)
DHCPDNS1	IP of the primary DNS server. (Optional)
DHCPDNS2	IP of the secondary DNS server. (Optional)
DHCPPreferredIP	Set a preferred IP address which will be included in the request to the DHCP server. (Optional)
DHCPAllowStaticRoutes	Allow the use of static routes send from the DHCP server. (Default: No)
DHCPPreferredLeaseTime	Set a preferred lease time which will be included in the request to the DHCP server. (Optional)
DHCPLeaseFilter	Allowed IP address range(s) for the DHCP lease. (Optional)
DHCPServerFilter	IP address range(s) for the DHCP servers from which leases are accepted. (Optional)
DHCPDisallowIPConflicts	Do not allow IP collisions with static routes. (Default: Yes)
DHCPDisallowNetConflicts	Do not allow network collisions with static routes. (Default: Yes)

EnableIPv6	Enable processing of IPv6 traffic on this interface. (Default: No)
IPv6IP	The IPv6 address of the virtual LAN interface.
IPv6Network	The IPv6 network of the virtual LAN interface.
IPv6DefaultGateway	The default gateway of the virtual LAN interface. (Optional)
PrivateIP	The private IP address of this high availability node. (Optional)
Metric	Specifies the metric for the auto-created route. (Default: 100)
AutoSwitchRoute	Enable transparent mode, which means that a switch route is added automatically for this virtual LAN interface. (Default: No)
AutoInterfaceNetworkRoute	Automatically add a route for this virtual LAN interface using the given network. (Default: Yes)
AutoDefaultGatewayRoute	Automatically add a default route for this virtual LAN interface using the given default gateway. (Default: Yes)
PrioCopyPolicy	Set the QoS to VLAN priority copy policy. (Default: Inherit)
EnableRouterAdvertisement	Enable Router Advertisement for this interface. (Default: No)
MemberOfRoutingTable	All or Specific. (Default: All)
RoutingTable	Specifies the PBR table to insert the interface IP route into. It also means that the specified routing table will be used for all routing lookups, unless overridden by a PBR rule. (Default: main)
Comments	Text describing the current object. (Optional)

3.133. VLANSettings

Description

Settings for IEEE 802.1Q based Virtual LAN interfaces.

Properties

UnknownVLANTags

VLAN packets tagged with an unknown ID.
(Default: DropLog)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

3.134. WebContentFilteringPolicy

Description

Add a Web Content Filtering Profile that can be used by one or many IP Policies.

Properties

Name	Specifies a symbolic name for the Profile. (Identifier)
AuditMode	Web Content Filtering audit mode. (Default: No)
FilteringCategories	Web content categories to block. (Optional)
NonManagedAction	Action to take for content that hasn't been classified. (Default: Allow)
AllowOverride	Allow the user to display a blocked site. (Default: No)
OverrideUpdateOnAccess	Restart the override timer on each new access to disallowed categories. (Default: Yes)
OverrideTimeToLive	Seconds that all disallowed categories will be allowed for the host that requested the override. (Default: 300)
AllowReclassification	Allow reclassification of sites. (Default: No)
Comments	Text describing the current object. (Optional)

3.135. X3C905EthernetPCIDriver

Description

3com Fast Ethernet Adaptor.

Properties

Comments

Text describing the current object. (Optional)



Note

This object type does not have an identifier and is identified by the name of the type only. There can only be one instance of this type.

Alphabetical Index

Commands

A

about, 31
activate, 20
add, 20
alarm, 31
appcontrol, 31
arp, 32
arpsnoop, 33
ats, 34
authagent, 34
authagentsnoop, 35

B

blacklist, 35
buffers, 37

C

cam, 37
cancel, 22
cc, 22
certcache, 38
cfglog, 38
commit, 23
connections, 39
cpuid, 40
crashdump, 40
cryptostat, 40

D

dconsole, 41
delete, 23
dhcp, 41
dhcprelay, 42
dhcpserver, 43
dhcpv6server, 44
dns, 44
dnsbl, 45
dynroute, 45

E

echo, 86

F

frags, 46

H

ha, 47
help, 86
history, 87
hostmon, 47
httpalg, 47
httpposter, 48
hwm, 49

I

idppipes, 49
ifstat, 50
igmp, 50
ihs, 51
(see also ipsechastat)
ikesnoop, 51
ippool, 52
ipsecdefines, 53
ipsecglobalstats, 53
ipsechastat, 53
ipsecstats, 54
ipsectunnels, 54

K

killsa, 55

L

languagefiles, 56
ldap, 56
license, 57
linkmon, 58
logout, 58
logsnoop, 87
ls, 89

M

memory, 58

N

natpool, 59
nd, 59
ndsnoop, 60
netcon, 61
netobjects, 61

O

ospf, 61

P

pcapdump, 63
pciscan, 65
ping, 85
pipes, 66
pptpalg, 67
pskgen, 24

R

reconfigure, 67
reject, 25
rekeysa, 68
reset, 26
route, 68
(see also routes)
routemon, 68
routes, 69
rtmonitor, 70
rules, 70

S

script, 90
 selftest, 71
 services, 73
 sessionmanager, 74
 set, 27
 settings, 75
 show, 28
 shutdown, 75
 sipalg, 76
 sshserver, 78
 sslvpn, 79
 stats, 79
 sysmsgs, 80

T

techsupport, 80
 time, 80

U

uarules, 81
 undelete, 29
 updatecenter, 81
 userauth, 82

V

vlan, 83
 vpnstats, 84
 (see also ipsecstats)

Object types

A

Access, 98
 AddressFolder, 100
 AdvancedScheduleOccurrence, 104
 AdvancedScheduleProfile, 104
 ALG_FTP, 105
 ALG_H323, 106
 ALG_HTTP, 106
 ALG_HTTP_URL, 108
 ALG_POP3, 108
 ALG_PPTP, 109
 ALG_SIP, 109
 ALG_SMTP, 110
 ALG_SMTP_Email, 111
 ALG_TFTP, 112
 ALG_TLS, 112
 AntiVirusPolicy, 114
 AppControlSettings, 115
 ApplicationRule, 116
 ApplicationRuleSet, 116
 ARPND, 118
 ARPNDSettings, 119
 AuthAgent, 122
 AuthenticationSettings, 123

B

BlacklistWhiteHost, 124
 BNE2EthernetPCIDriver, 125
 BroadcomEthernetPCIDriver, 126

C

Certificate, 127
 COMPortDevice, 128
 ConfigModePool, 129
 ConnTimeoutSettings, 130

D

DateTime, 131
 DefaultInterface, 132
 Device, 133
 DHCPRelay, 134
 DHCPRelaySettings, 136
 DHCPServer, 137
 DHCPServerCustomOption, 138
 DHCPServerPoolStaticHost, 138
 DHCPServerSettings, 140
 DHCPv6Server, 141
 DHCPv6ServerPoolStaticHost, 142
 DHCPv6ServerSettings, 143
 DiagnosticsSettings, 144
 DNS, 145
 DynamicRoutingRule, 146
 DynamicRoutingRuleAddRoute, 147
 DynamicRoutingRuleExportOSPF, 147
 DynDnsClientCjbNet, 149
 DynDnsClientDyndnsOrg, 150
 DynDnsClientDyngCx, 151
 DynDnsClientPeanutHull, 152

E

E1000EthernetPCIDriver, 153
 E100EthernetPCIDriver, 154
 Ethernet, 155
 EthernetAddress, 101, 103
 EthernetAddressGroup, 101, 103
 EthernetDevice, 157
 EthernetSettings, 158
 EventReceiverSNMP2c, 160

F

FileControlPolicy, 161
 FragSettings, 162

G

GRETunnel, 164

H

HighAvailability, 165
 HTTPALGBanners, 166
 HTTPAuthBanners, 167
 HTTPPoster, 168
 HWM, 169
 HWMSettings, 170

I

ICMPSettings, 171
 ID, 172
 IDList, 172
 IDPRule, 173
 IDPRuleAction, 173
 IGMPRule, 175
 IGMPSetting, 177
 IKEAlgorithms, 178
 InterfaceGroup, 180

IP4Address, 102, 103
 IP4Group, 102, 103
 IP4HAddress, 101, 103
 IP6Address, 100, 103
 IP6Group, 100, 103
 IP6in4Tunnel, 181
 IPPolicy, 182, 189, 190
 IPPool, 185
 IPRule, 186, 189, 190
 IPRuleFolder, 189, 190
 IPRuleSet, 190
 IPsecAlgorithms, 191
 IPsecTunnel, 193
 IPsecTunnelSettings, 196
 IPSettings, 198
 ixgbeEthernetPCIDriver, 201
 IXP4NPEEthernetDriver, 202

L

L2TPClient, 203
 L2TPServer, 205
 L2TPServerSettings, 207
 L2TPv3Client, 208
 L2TPv3Server, 209
 LDAPDatabase, 210
 LDAPServer, 211
 LengthLimSettings, 212
 LinkAggregation, 213
 LinkMonitor, 215
 LocalReassSettings, 216
 LocalUserDatabase, 217
 LogReceiverFWLog, 218
 LogReceiverMemory, 219
 LogReceiverMessageException, 160, 218, 219, 220
 LogReceiverSyslog, 220
 LogSettings, 221
 LoopbackInterface, 222

M

MarvellEthernetPCIDriver, 223
 MiscSettings, 224
 MonitoredHost, 264
 MulticastSettings, 226

N

NATPool, 227

O

OSPFAggregate, 231
 OSPFArea, 229
 OSPFInterface, 230
 OSPFNeighbor, 231
 OSPFProcess, 228
 OSPFVLink, 232

P

Pipe, 233
 PipeRule, 236
 PPPoETunnel, 237
 PPPSettings, 239
 PSK, 240

R

R8139EthernetPCIDriver, 241
 R8169EthernetPCIDriver, 242
 RA_PrefixInformation, 259
 RadiusAccounting, 243
 RadiusRelay, 244
 RadiusServer, 246
 RealTimeMonitorAlert, 247
 RemoteIDList, 248
 RemoteMgmtHTTP, 249
 RemoteMgmtNetcon, 250
 RemoteMgmtSettings, 251
 RemoteMgmtSNMP, 253
 RemoteMgmtSSH, 254
 Route, 263
 Route6, 265
 RouteBalancingInstance, 256
 RouteBalancingSpilloverSettings, 257
 RouterAdvertisement, 258
 RoutingRule, 260
 RoutingSettings, 261
 RoutingTable, 263

S

ScheduleProfile, 267
 ServiceGroup, 268
 ServiceICMP, 269
 ServiceICMPv6, 271
 ServiceIPProto, 273
 ServiceTCPUDP, 274
 SSHClientKey, 275
 SSLSettings, 276
 SSLVPNInterface, 277
 SSLVPNInterfaceSettings, 278
 ST201EthernetPCIDriver, 279
 StateSettings, 280
 SwitchRoute, 266

T

TCPSettings, 281
 ThresholdAction, 283
 ThresholdRule, 283
 TulipEthernetPCIDriver, 285

U

UpdateCenter, 286
 URLFilterPolicy, 287
 URLFilterPolicy_URL, 287
 User, 217
 UserAuthRule, 288

W

WebContentFilteringPolicy, 294

V

VLAN, 291
 VLANSettings, 293

X

X3C905EthernetPCIDriver, 295



CLAVISTER®

Clavister AB
Sjögatan 6J
SE-89160 Örnsköldsvik
SWEDEN

Phone: +46-660-299200
www.clavister.com